

Package: dgraphs (via r-universe)

October 1, 2026

Title Data-Derived Graph Construction Utilities

Version 0.3.0.9000

Description Constructs data-derived graphs from numerical observations using mutual, shared-neighbor, intersection, geodesic, radius, adaptive-radius, minimum-spanning-tree completion, and optional iterated adaptive neighborhood methods. Provides graph conversion, pruning, diagnostics, spectral embedding, endpoint detection, and path utilities, with reproducible synthetic geometries and point sampling for graph and embedding experiments. The implemented graph constructions include methods described by Jarvis and Patrick (1973) [<doi:10.1109/T-C.1973.223640>](https://doi.org/10.1109/T-C.1973.223640), Brito et al. (1997) [<doi:10.1016/S0167-7152\(96\)00213-1>](https://doi.org/10.1016/S0167-7152(96)00213-1), Berry and Sauer (2019) [<doi:10.3934/fods.2019001>](https://doi.org/10.3934/fods.2019001), and Gower and Ross (1969) [<doi:10.2307/2346439>](https://doi.org/10.2307/2346439).

License MIT + file LICENSE

Copyright file inst/COPYRIGHTS

URL <https://pgajer.github.io/dgraphs/>,
<https://github.com/pgajer/dgraphs>

BugReports <https://github.com/pgajer/dgraphs/issues>

Encoding UTF-8

Language en-US

Roxygen list(markdown = TRUE)

SystemRequirements C++17

Depends R (>= 4.1.0)

Imports FNN, igraph (>= 2.2.0), nloptr, parallel, stats, Rcpp

LinkingTo BH, nloptr, Rcpp, RcppEigen

Suggests shiny, bslib, plotly, grip, digest, geometry, htmltools, htmlwidgets, ivue (>= 0.1.0), knitr, Matrix, rmarkdown, rgl, testthat (>= 3.0.0), withr

VignetteBuilder knitr
Config/testthat/edition 3
Config/roxygen2/version 8.0.0
Config/pak/sysreqs cmake libglpk-dev libxml2-dev
Repository <https://pgajer.r-universe.dev>
Date/Publication 2026-10-01 10:54:45 UTC
RemoteUrl <https://github.com/pgajer/dgraphs>
RemoteRef HEAD
RemoteSha 9c17cbea5c553c858076a2e13422fe6987feea12

Contents

dgraphs-package	5
as_igraph	6
build.ian.backend	7
build.iknn.graphs.and.selectk	8
compare.adj.lists	10
compare.paths	11
compute.geodesic.stats	11
compute.graph.diameter	13
compute.graph.distance	13
compute.graph.endpoint.scores	14
compute.graph.summary.pmf	16
compute.graph.summary.stability	18
compute.stability.metrics	19
compute.vertex.geodesic.stats	20
convert.adjacency.list.to.adjacency.matrix	21
convert.adjacency.to.edge.matrix	22
convert.to.undirected	23
convert.weighted.adjacency.matrix.to.adjacency.list	23
count.edges	24
create.cknn.graph	24
create.cmst.graph	26
create.geodesic.iknn.graph	28
create.graph	29
create.grid.graph	30
create.ian.graph	31
create.iknn.graphs	34
create.iterated.iknn.graphs	36
create.maximal.packing	38
create.mknn.graph	39
create.mknn.graphs	42
create.path.graph	44
create.plm.graph	45
create.rknn.graph	45

create.rknn.graphs	48
create.single.iknn.graph	49
create.sknn.graph	52
create.sknn.graphs	55
create.subgraph	56
create.threshold.distance.graph	57
detect.graph.endpoints	57
detect.local.extrema	60
dgraph	61
edge.diff	62
edge.lengths.synthetic.geometry	63
embed.quadform.surface	63
embed.synthetic.geometry	64
explore.graphs	65
extract.trajectory.edge.lengths	66
fermat.distances	67
fermat.knn	69
geodesic.core.endpoints	71
geodesic.disk	72
geodesic.knn	73
geodesic.knnx	74
get.shortest.path	75
graph.connected.components	75
graph.embedding	76
graph.geodesic.distances	77
graph.spectral.embedding	78
graph.spectrum	79
graph.summary.divergence	81
identical.vertex.set.weighted.graph.similarity	82
inspect.path.graph	83
inspect.path.graph.series	84
inspect.synthetic_geometry_sample	85
isometry.distance.correlations	85
isometry.distortion.quantiles	86
isometry.geodesic.diagnostics	87
isometry.rel.abs.error	88
isometry.rel.rms.error	89
isometry.scale	90
jensen.shannon.divergence	90
join.graphs	91
minh.limit	92
nerve.graph	92
overlap.distribution.plot	93
path.dist	93
path.length	94
plot.build_iknn_graphs_and_selectk	95
plot.cst_graph_mixing_stats	96
plot.dgraph	96

plot.geodesic_stats	98
plot.iknn_stability_metrics	99
plot.lkNNgraphs	100
plot.vertex_geodesic_stats	101
print.build_iknn_graphs_and_selectk	102
print.dgraph	103
print.geodesic_stats	103
print.graph.constructors	104
print.knn.outliers	105
print.maximal_packing	106
print.mknn_graph	106
print.mknn_graphs	107
print.mst_completion_graph	108
print.packing_validation	109
print.path.graph.plm	109
print.summary.knn.outliers	110
print.summary.mst_completion_graph	111
quadform.gradient	112
quadform.metric	112
read.graph.benchmark	113
register.graph.project	114
remove.knn.outliers	115
rm.self.loops	117
sample.synthetic.geometry	118
subdivide.path	119
summarize.isometry.deviation	120
summary.geodesic_stats	121
summary.lkNN	122
summary.iknn_graphs	122
summary.iterated_iknn_graphs	124
summary.knn.outliers	125
summary.local_extrema	126
summary.mknn_graphs	126
summary.mst_completion_graph	128
summary.rknn_graphs	129
summary.vertex_geodesic_stats	130
synthetic.circle	131
synthetic.helix	132
synthetic.point.line.junction	132
synthetic.quadform	133
synthetic.sampling.clustered	134
synthetic.sampling.dirichlet.zeros	135
synthetic.sampling.gapped.uniform	136
synthetic.sampling.grid.interval	137
synthetic.sampling.quadform.lab	137
synthetic.sampling.truncated.normal	138
synthetic.sampling.uniform.box	139
synthetic.sampling.uniform.disk	140

synthetic.sampling.uniform.interval	140
synthetic.sampling.uniform.rectangle	141
synthetic.simplex	142
synthetic.sphere.cap	142
synthetic.stratified	143
synthetic.stratum.point	144
synthetic.stratum.rectangle	144
synthetic.stratum.segment	145
synthetic.torus.patch	146
synthetic.trefoil	147
validate.maximal.packing	147
validate.synthetic.geometry	149
validate.synthetic.sampling	150
verify.maximal.packing	150
vertices	151
vertices.local_extrema	152
wgraph.prune.long.edges	153

Index	154
--------------	------------

dgraphs-package	<i>dgraphs: Data-Derived Graph Construction Utilities</i>
-----------------	---

Description

Construct and analyze graphs derived from numerical observations.

Start here

- **Finding your way around dgraphs:** a task-oriented catalog of public functions and object methods.
- **Synthetic geometry and point sampling:** reproducible curves, surfaces, embeddings and graph examples.
- **Constructing and Diagnosing Data-Derived Graphs:** graph-family comparisons, connectivity repair and diagnostics.

These links open installed HTML guides. From the console, use `vignette("function-guide", package = "dgraphs")` or `vignette("synthetic-geometry", package = "dgraphs")`.

Author(s)

Maintainer: Pawel Gajer <pgajer@gmail.com>

Authors:

- Pawel Gajer <pgajer@gmail.com>

Other contributors:

- Sunil Arya (ANN library) [contributor]

- David M. Mount (ANN library) [contributor]
- University of Maryland (ANN library) [copyright holder]
- Yixuan Qiu (Spectra library) [contributor, copyright holder]
- Anna Araslanova (Spectra LOBPCG solver) [contributor, copyright holder]
- Gael Guennebaud (Spectra linear algebra routines) [contributor, copyright holder]
- Jitse Niesen (Spectra linear algebra routines) [contributor, copyright holder]
- Netherlands eScience Center (Spectra eigensolver routines) [contributor, copyright holder]
- Danil Kirsanov (Polyhedral geodesic library) [contributor, copyright holder]

See Also

[create.graph\(\)](#), [create.sknn.graph\(\)](#), [create.rknn.graph\(\)](#), [graph.geodesic.distances\(\)](#),
[create.path.graph\(\)](#), [plot.dgraph\(\)](#), [sample.synthetic.geometry\(\)](#)

Examples

```
graph <- create.graph("chain", n = 5)
print(graph)
graph.geodesic.distances(graph, vertices = c(1, 5))
# The endpoint distance is four unit-length edges.
```

as_igraph

Convert a dgraph to igraph

Description

Convert a dgraph to igraph

Usage

```
as_igraph(graph, stage = "final")
```

Arguments

graph	A dgraph object, including isolates.
stage	Stored graph stage.

Value

An undirected igraph. Edge lengths are named length; other attributes retain their names. No implicit weight or unit lengths are added. For metric paths pass `weights = igraph::E(g)$length` explicitly; for hop distance pass `weights = NA`.

Examples

```
graph <- dgraph(list(2L, 1L, integer()), list(0, 0, numeric()))
ig <- as_igraph(graph)
igraph::vcount(ig)
igraph::E(ig)$length
```

build.ian.backend	<i>Build the Optional IAN Backend</i>
-------------------	---------------------------------------

Description

Compile the pinned IAN and Clarabel sources installed with dgraphs in a new directory. The supported build target is macOS arm64. Setup requires Python 3, Apple's C++ compiler/SDK, and matching native Cargo/Rust tools (Rust ≥ 1.77). An initial build needs cached crates or network access. No tools are installed by this function. Compilation is explicit and never starts inside `create.ian.graph()` or ordinary package installation.

Usage

```
build.ian.backend(
  build.dir,
  python = "python3",
  cargo = "cargo",
  rustc = "rustc",
  cxx = "clang++",
  offline = FALSE
)
```

Arguments

build.dir	New output directory, including logs and source copies. Existing files/directories are refused. A path containing spaces is allowed.
python	Python 3 command or executable path.
cargo	Cargo command or executable path from a native arm64 toolchain.
rustc	Rust compiler command or path from the same toolchain as cargo.
cxx	C++ compiler command or executable path.
offline	Logical scalar. If TRUE, Cargo uses only cached dependencies.

Value

The absolute path to `dgraphs_ian.so`, invisibly. Save this path and pass it to `create.ian.graph(..., backend = path)`. Reuse the built module with the same R installation; rebuild when changing R runtime or backend sources. Build errors retain available logs and raise an R error. No shared package library is modified. Build records identify source files and tool commands.

See Also

[create.ian.graph\(\)](#)

Examples

```
## Not run:
backend <- build.ian.backend("ian-build")
fit <- create.ian.graph(matrix(c(0, 1, 2), ncol = 1), backend = backend)
stopifnot(fit$complete)

## End(Not run)
```

build.iknn.graphs.and.selectk

Build iKNN Graphs and Select a Neighborhood Size

Description

Builds an iKNN graph sequence and selects k from structural edit-distance stability, label-mixing stability, or both.

Usage

```
build.iknn.graphs.and.selectk(
  X,
  k.values,
  method = c("both", "edit", "mixing", "none"),
  pca.dim = 100,
  variance.explained = 0.99,
  trim.disconnected = TRUE,
  edit.min.lcc.frac = 1,
  edit.eps = 0.05,
  labels = NULL,
  perm.blocks = NULL,
  mixing.metric = c("homophily.effect", "homophily.z", "homophily.adjusted",
    "assortativity.effect", "assortativity.z", "homophily", "assortativity",
    "conductance.median", "conductance.wmean"),
  mixing.min.lcc.frac = 0.98,
  mixing.eps = 0.05,
  mixing.require.local.extremum = TRUE,
  mixing.window = 1L,
  n.perm = 200L,
  use.edge.weights = TRUE,
  weights.are.edge.lengths = FALSE,
  affinity.method = c("exp", "inv"),
  affinity.sigma = NULL,
  affinity.sigma.from = c("k.cc.mixing", "k.max.lcc", "k.trim"),
```

```

    affinity.eps = 1e-08,
    simplify.multiple = TRUE,
    seed = 1L,
    verbose = TRUE,
    ...
)

```

Arguments

<code>X</code>	Numeric observation-by-feature matrix.
<code>k.values</code>	Strictly increasing integer vector of neighborhood sizes, each between 1 and $n - 1$.
<code>method</code>	Selection criterion.
<code>pca.dim, variance.explained</code>	PCA controls forwarded to <code>create.iknn.graphs()</code> .
<code>trim.disconnected</code>	Logical; trim to a largest connected component when the requested connectivity tail is absent.
<code>edit.min.lcc.frac, edit.eps</code>	Connectivity and tolerance controls for edit-distance selection.
<code>labels, perm.blocks</code>	Optional labels and permutation blocks for mixing selection.
<code>mixing.metric, mixing.min.lcc.frac, mixing.eps</code>	Mixing criterion, connectivity threshold, and tolerance.
<code>mixing.require.local.extremum, mixing.window</code>	Local-extremum controls for the mixing curve.
<code>n.perm</code>	Number of label permutations.
<code>use.edge.weights, weights.are.edge.lengths</code>	Edge-weight interpretation.
<code>affinity.method, affinity.sigma, affinity.sigma.from, affinity.eps</code>	Controls for converting edge lengths to affinities.
<code>simplify.multiple</code>	Logical; simplify loops and multiple edges.
<code>seed</code>	Random seed.
<code>verbose</code>	Logical; report progress.
<code>...</code>	Additional arguments forwarded to <code>create.iknn.graphs()</code> .

Value

An object of class "build_iknn_graphs_and_selectk" containing the graph sequence, connectivity diagnostics, selection curves, selected neighborhood sizes, trimming metadata, and call parameters.

Examples

```

set.seed(1)
x <- matrix(rnorm(60), ncol = 2)
selected <- build.iknn.graphs.and.selectk(x, k.values = seq.int(2, 4),
  method = "edit",
  verbose = FALSE)
selected$k.opt.edit

```

compare.adj.lists	<i>Compare Two Adjacency Lists</i>
-------------------	------------------------------------

Description

Compare Two Adjacency Lists

Usage

```
compare.adj.lists(adj.list1, adj.list2, verbose = FALSE)
```

Arguments

adj.list1	First adjacency list.
adj.list2	Second adjacency list.
verbose	Logical; print the indices of vertices with different neighbor sets. Defaults to FALSE.

Value

TRUE when each vertex has the same neighbor set in both lists, ignoring order; otherwise FALSE.

Examples

```

graph <- list(c(2L, 3L), 1L, 1L)
compare.adj.lists(graph, list(c(3L, 2L), 1L, 1L))

```

compare.paths	<i>Compare Paths Across Hop Limits</i>
---------------	--

Description

Compare Paths Across Hop Limits

Usage

compare.paths(path.result, from, to)

Arguments

- path.result A path.graph.series object.
- from Source vertex index.
- to Target vertex index.

Value

Data frame describing path availability and length by hop limit.

Examples

```
graph <- list(2L, c(1L, 3L), 2L)
lengths <- list(1, c(1, 2), 2)
series <- create.path.graph(dgraph(graph, lengths), h.values = 1:2)
compare.paths(series, from = 1, to = 3)
```

compute.geodesic.stats	<i>Compute Geodesic Statistics for Grid Vertices</i>
------------------------	--

Description

Analyzes how the number of geodesics scales with radius for each grid vertex. This function helps determine if collapsing/clustering geodesics is necessary and provides insights into the graph structure around grid vertices.

Usage

```
compute.geodesic.stats(
  adj.list,
  length.list,
  min.radius = 0.2,
  max.radius = 0.5,
  n.steps = 5,
  n.packing.vertices = length(adj.list),
  max.packing.iterations = 20,
  packing.precision = 1e-04,
  verbose = FALSE
)
```

Arguments

<code>adj.list</code>	List of integer vectors. Each vector contains indices of vertices adjacent to the corresponding vertex. Indices should be 1-based.
<code>length.list</code>	List of numeric vectors. Each vector contains weights of edges corresponding to adjacencies in <code>adj.list</code> .
<code>min.radius</code>	Numeric. Minimum radius as a fraction of graph diameter.
<code>max.radius</code>	Numeric. Maximum radius as a fraction of graph diameter.
<code>n.steps</code>	Integer. Number of radius steps to test.
<code>n.packing.vertices</code>	Integer. Number of vertices in the grid/packing.
<code>max.packing.iterations</code>	Integer. Maximum iterations for packing algorithm.
<code>packing.precision</code>	Numeric. Precision parameter for packing algorithm.
<code>verbose</code>	Logical. Whether to print progress information.

Value

A list of class "geodesic_stats" containing:

radii Numeric vector. Actual radii used in the analysis.

geodesic_rays Matrix. Number of geodesic rays for each vertex at each radius.

composite_geodesics Matrix. Number of composite geodesics for each vertex at each radius.

path_overlap List of matrices. Overlap statistics for each vertex at each radius.

grid_vertices Integer vector. The vertices selected as grid vertices.

summary Data frame. Summary statistics for each radius.

Examples

```
graph <- create.graph("circle", n = 8, sampling = "uniform")
stats <- compute.geodesic.stats(graph.adjacency(graph), graph.lengths(graph), min.radius = 0.3,
  max.radius = 0.5, n.steps = 2, n.packing.vertices = 4)
stats$summary
```

```
compute.graph.diameter
```

Compute a Weighted Graph Diameter

Description

Compute a Weighted Graph Diameter

Usage

```
compute.graph.diameter(graph, stage = "final")
```

Arguments

graph	A dgraph with stored lengths.
stage	Stored graph stage.

Value

A list containing the diameter and the farthest path details.

Examples

```
graph <- list(2L, c(1L, 3L), 2L)
weights <- list(1, c(1, 2), 2)
compute.graph.diameter(dgraph(graph, weights))$diameter
```

```
compute.graph.distance
```

Compute a Weighted Shortest-Path Distance

Description

Compute a Weighted Shortest-Path Distance

Usage

```
compute.graph.distance(graph, i, j, stage = "final")
```

Arguments

graph	A dgraph with stored lengths.
i	Source vertex.
j	Target vertex.
stage	Stored graph stage.

Value

Numeric shortest-path distance.

Examples

```
graph <- list(2L, c(1L, 3L), 2L)
weights <- list(1, c(1, 2), 2)
compute.graph.distance(i = 1, j = 3, graph = dgraph(graph, weights))
```

compute.graph.endpoint.scores

Compute Graph Endpoint Scores from a 3D Embedding

Description

Computes endpointness diagnostics for graph vertices by selecting graph-geodesic neighborhoods and evaluating how concentrated the corresponding 3D embedding directions are. This targets terminal arm tips in an embedding rather than graph-theoretic degree-1 vertices.

For each vertex x , let $u_1, \dots, u_m$ be unit vectors in the embedding from x to graph-geodesic neighbors of x . The function computes:

$$s_{\min}(x) = \min_{i < j} u_i^\top u_j$$

$$s_q(x) = \text{quantile}\{u_i^\top u_j : i < j\}$$

$$m(x) = \left\| \frac{1}{\sum_i w_i} \sum_i w_i u_i \right\|$$

$$\text{score}(x) = m(x) \frac{1 + s_q(x)}{2}$$

Neighborhoods are selected in graph-geodesic space while directions are taken from the supplied 3D embedding.

Usage

```
compute.graph.endpoint.scores(
  adj.list,
  length.list,
  layout.3d,
  neighborhood = c("geodesic_k", "geodesic_radius"),
  k = c(10L, 20L, 30L),
  radius = NULL,
  q = 0.1,
  neighbor.weighting = c("uniform", "inverse_distance", "gaussian"),
  gaussian.sigma = NULL,
  min.neighborhood.size = 3L,
  scale.aggregate = c("mean", "median", "min", "max"),
  verbose = FALSE
)
```

Arguments

<code>adj.list</code>	Graph adjacency list (1-based vertex indices).
<code>length.list</code>	Edge-length list aligned with <code>adj.list</code> .
<code>layout.3d</code>	Numeric matrix or data frame with 3 columns giving the 3D embedding coordinates for graph vertices.
<code>neighborhood</code>	Character string. Either "geodesic_k" (default) or "geodesic_radius".
<code>k</code>	Integer vector of geodesic neighborhood sizes used when <code>neighborhood = "geodesic_k"</code> .
<code>radius</code>	Positive numeric vector of geodesic radii used when <code>neighborhood = "geodesic_radius"</code> .
<code>q</code>	Quantile used for <code>s.q</code> . Must lie in $[0, 1]$. Default is 0.1.
<code>neighbor.weighting</code>	Character string controlling neighbor weights for <code>m</code> and weighted pair quantiles. One of "uniform" (default), "inverse_distance", or "gaussian".
<code>gaussian.sigma</code>	Optional positive numeric scale used when <code>neighbor.weighting = "gaussian"</code> . If NULL, the median positive geodesic neighborhood distance is used per vertex and scale.
<code>min.neighborhood.size</code>	Minimum number of usable neighbors required after removing zero-length embedding vectors. Must be at least 2.
<code>scale.aggregate</code>	How to aggregate scores across multiple neighborhood scales. One of "mean" (default), "median", "min", or "max".
<code>verbose</code>	Logical; if TRUE, prints progress.

Value

A list with aggregated per-vertex scores, per-scale score matrices, and neighborhood diagnostics.

Examples

```
chain <- create.graph("chain", n = 8)
layout <- cbind(seq_len(8), 0, 0)
scores <- compute.graph.endpoint.scores(graph.adjacency(chain), graph.lengths(chain), layout,
  k = c(2, 3), min.neighborhood.size = 2)
head(scores$summary)
```

```
compute.graph.summary.pmf
```

Compute a graph summary as a probability mass function

Description

Converts a graph-like object into a named probability mass function (PMF) describing one selected graph summary. This provides a standardized bridge between graph objects and divergence functions such as [jensen.shannon.divergence\(\)](#).

Supported v1 summaries are:

- "degree_distribution"
- "edge_weight_distribution"
- "component_size_distribution"
- "neighborhood_label_distribution"

"component_size_distribution" is included primarily as a diagnostic for disconnectedness / fragmentation, not as a general-purpose default stability summary.

Usage

```
compute.graph.summary.pmf(
  graph,
  summary = c("degree_distribution", "edge_weight_distribution",
    "component_size_distribution", "neighborhood_label_distribution"),
  labels = NULL,
  edge.attribute = "length",
  stage = "final",
  bins = NULL,
  n.bins = 20L,
  bin.method = c("auto", "fixed_width", "fixed_quantile", "explicit"),
  normalize = TRUE,
  support = NULL,
  zero.pad = TRUE,
  return.details = TRUE
)
```

Arguments

graph	A dgraph object.
summary	Summary type to compute.
labels	Optional label vector used for "neighborhood_label_distribution". Must have length equal to the number of vertices.
edge.attribute	Edge quantity for the edge-value distribution; default "length".
stage	Stored graph stage to summarize.
bins	Optional numeric vector of histogram breaks used for "edge_weight_distribution".
n.bins	Integer number of bins used when bins is NULL and the summary is "edge_weight_distribution".
bin.method	Character string controlling automatic bin construction for "edge_weight_distribution".
normalize	Logical; if TRUE, convert counts to a PMF.
support	Optional support to align the resulting PMF to.
zero.pad	Logical; if TRUE and support is provided, missing support entries are padded with zero mass.
return.details	Logical; if TRUE, return a structured list. Otherwise return the named PMF directly.

Value

If `return.details = TRUE`, a list with fields:

- `summary`: summary type used.
- `pmf`: named probability mass function.
- `support`: support of the PMF.
- `counts`: named raw-count vector before normalization.
- `metadata`: list of summary-specific metadata.

Otherwise, returns the named PMF vector.

Examples

```
graph <- dgraph(list(c(2L, 3L), 1L, 1L))
compute.graph.summary.pmf(graph, summary = "degree_distribution")
```

compute.graph.summary.stability

Compute graph-summary stability across a graph sequence

Description

Computes a divergence-based stability curve across consecutive graphs in a sequence. This function provides a generalized sequence-level analogue of the degree-profile Jensen-Shannon calculation currently used in `compute.stability.metrics()`.

Usage

```
compute.graph.summary.stability(
  graphs,
  summary = c("degree_distribution", "edge_weight_distribution",
    "component_size_distribution", "neighborhood_label_distribution"),
  divergence = c("js"),
  labels = NULL,
  summary.args = list(),
  k.values = NULL,
  graph.type = c("geom", "isize"),
  return.details = TRUE
)
```

Arguments

<code>graphs</code>	Either a list of graph-like objects or an object of class "iknn_graphs".
<code>summary</code>	Summary type to compare across consecutive graph pairs.
<code>divergence</code>	Divergence type. Currently only "js".
<code>labels</code>	Optional shared vertex-label vector used for "neighborhood_label_distribution".
<code>summary.args</code>	Optional named list forwarded to graph.summary.divergence() .
<code>k.values</code>	Optional integer vector of k values. If <code>graphs</code> is an "iknn_graphs" object and <code>k.values</code> is NULL, the values are derived from its <code>k.values</code> attribute.
<code>graph.type</code>	If <code>graphs</code> is an "iknn_graphs" object, choose either "geom" or "isize".
<code>return.details</code>	Logical; if TRUE, return a structured list.

Value

If `return.details = TRUE`, a list with fields:

- `summary`: summary type used.
- `divergence`: divergence type used.
- `k.values`: full k sequence.
- `k.transition.values`: k values corresponding to consecutive-graph transitions.

- values: vector of divergence values of length `length(k.values) - 1`.
- details: optional pairwise details for each transition.

Otherwise, returns only the divergence vector.

Examples

```
graphs <- list(
  dgraph(list(2L, c(1L, 3L), 2L)),
  dgraph(list(c(2L, 3L), c(1L, 3L), c(1L, 2L))),
  create.graph("complete", 3)
)
compute.graph.summary.stability(
  graphs,
  summary = "degree_distribution"
)$values
```

```
compute.stability.metrics
```

Compute Stability Metrics Across a Sequence of IkNN Graphs

Description

Computes stability diagnostics across the pruned IkNN graphs produced by `create.iknn.graphs()`. Metrics include edit distances between consecutive graphs, graph-summary Jensen-Shannon divergence, edge-count diagnostics, local minima, and smoothed trend fits for plotting.

Usage

```
compute.stability.metrics(
  graphs,
  graph.type = c("geom", "isize"),
  summary = c("degree_distribution", "edge_weight_distribution",
    "component_size_distribution", "neighborhood_label_distribution"),
  divergence = c("js"),
  labels = NULL,
  summary.args = list()
)
```

Arguments

<code>graphs</code>	An object of class "iknn_graphs" returned by <code>create.iknn.graphs()</code> .
<code>graph.type</code>	Character string, either "geom" or "isize".
<code>summary</code>	Graph-summary family used for the divergence curve.
<code>divergence</code>	Divergence used for consecutive-graph comparison. Currently only "js".
<code>labels</code>	Optional vertex-label vector used when <code>summary = "neighborhood_label_distribution"</code> .
<code>summary.args</code>	Optional named list forwarded to <code>compute.graph.summary.stability()</code> .

Value

An object of class "iknn_stability_metrics".

Examples

```
set.seed(1)
x <- matrix(rnorm(60), ncol = 2)
graphs <- create.iknn.graphs(x, k.values = seq.int(2, 4), compute.full = TRUE,
  verbose = FALSE)
stability <- compute.stability.metrics(graphs)
stability$edit.distances
```

```
compute.vertex.geodesic.stats
```

Compute Geodesic Statistics for a Single Grid Vertex

Description

Analyzes how the number of geodesics scales with radius for a specific grid vertex.

Usage

```
compute.vertex.geodesic.stats(
  adj.list,
  length.list,
  grid.vertex,
  min.radius = 0.2,
  max.radius = 0.5,
  n.steps = 5,
  n.packing.vertices = length(adj.list),
  packing.precision = 1e-04
)
```

Arguments

<code>adj.list</code>	List of integer vectors. Each vector contains indices of vertices adjacent to the corresponding vertex. Indices should be 1-based.
<code>length.list</code>	List of numeric vectors. Each vector contains weights of edges corresponding to adjacencies in <code>adj.list</code> .
<code>grid.vertex</code>	Integer. The grid vertex to analyze.
<code>min.radius</code>	Numeric. Minimum radius as a fraction of graph diameter.
<code>max.radius</code>	Numeric. Maximum radius as a fraction of graph diameter.
<code>n.steps</code>	Integer. Number of radius steps to test.
<code>n.packing.vertices</code>	Integer. Number of vertices in the grid/packing.
<code>packing.precision</code>	Numeric. Precision threshold for packing convergence.

Value

A data frame of class "vertex_geodesic_stats" with columns:

radius Actual radius used.

rays Number of geodesic rays within radius.

composite_geodesics Number of composite geodesics.

overlap_min Minimum overlap ratio.

overlap_p05 5th percentile overlap ratio.

overlap_p25 25th percentile overlap ratio.

overlap_median Median overlap ratio.

overlap_p75 75th percentile overlap ratio.

overlap_p95 95th percentile overlap ratio.

overlap_max Maximum overlap ratio.

Examples

```
graph <- create.graph("circle", n = 8, sampling = "uniform")
compute.vertex.geodesic.stats(graph.adjacency(graph), graph.lengths(graph),
  grid.vertex = 1, min.radius = 0.3,
  max.radius = 0.5, n.steps = 2)
```

```
convert.adjacency.list.to.adjacency.matrix
```

Convert an Adjacency List to an Adjacency Matrix

Description

Convert an Adjacency List to an Adjacency Matrix

Usage

```
convert.adjacency.list.to.adjacency.matrix(
  adj.list,
  weight.list = NULL,
  mode = "undirected",
  remove.self.loops = TRUE
)
```

Arguments

adj.list Adjacency list.

weight.list Optional edge-weight list aligned with **adj.list**.

mode Either "undirected" or "directed".

remove.self.loops Logical; if TRUE, remove diagonal entries.

Value

Numeric adjacency matrix.

Examples

```
graph <- list(c(2L, 3L), 1L, 1L)
weights <- list(c(1, 2), 1, 2)
convert.adjacency.list.to.adjacency.matrix(graph, weights)
```

convert.adjacency.to.edge.matrix

Convert an Adjacency List to an Edge Matrix

Description

Convert an Adjacency List to an Edge Matrix

Usage

```
convert.adjacency.to.edge.matrix(adj.list, weight.list = NULL)
```

Arguments

`adj.list` A 1-based adjacency list.

`weight.list` Optional edge-weight list aligned with `adj.list`.

Value

A list with `edge.matrix` and `weights`.

Examples

```
graph <- list(c(2L, 3L), 1L, 1L)
convert.adjacency.to.edge.matrix(graph)
```

convert.to.undirected *Convert a Directed Adjacency List to an Undirected Adjacency List*

Description

Convert a Directed Adjacency List to an Undirected Adjacency List

Usage

```
convert.to.undirected(adj.list)
```

Arguments

adj.list Directed adjacency list.

Value

An adjacency list with reciprocal edges added and duplicate neighbors removed.

Examples

```
directed <- list(2L, integer(0), 1L)
convert.to.undirected(directed)
```

convert.weighted.adjacency.matrix.to.adjacency.list
Convert a Weighted Adjacency Matrix to Lists

Description

Convert a Weighted Adjacency Matrix to Lists

Usage

```
convert.weighted.adjacency.matrix.to.adjacency.list(A)
```

Arguments

A Numeric square adjacency matrix.

Value

A list with adj.list and weight.list.

Examples

```
A <- matrix(c(0, 1, 0, 1, 0, 2, 0, 2, 0), nrow = 3)
convert.weighted.adjacency.matrix.to.adjacency.list(A)
```

count.edges

*Count Edges in an Undirected Adjacency List***Description**

Count Edges in an Undirected Adjacency List

Usage

```
count.edges(adj.list)
```

Arguments

adj.list Adjacency list for an undirected graph.

Value

Number of undirected edges.

Examples

```
count.edges(list(c(2L, 3L), 1L, 1L))
```

create.cknn.graph

*Compute a Continuous-kNN Graph***Description**

Creates an undirected continuous-kNN graph using local scale distances. Let σ_i be the distance from observation i to its k .scale-th non-self nearest neighbor. Vertices are adjacent when

$$\|x_i - x_j\|_2 \leq \delta \sqrt{\sigma_i \sigma_j}.$$

This is a convenience wrapper around `create.rknn.graph()` with `type = "adaptive.radius"` and `radius.rule = "geomean"`. It is useful as a named data-derived graph construction in geodesic reconstruction benchmarks.

Usage

```

create.cknn.graph(
  X,
  k.scale,
  delta = 1,
  radius.search = c("ann", "all.pairs"),
  return.timing = FALSE,
  graph.detail = c("full", "minimal"),
  prune.method = c("none", "local.geodesic", "global.geodesic.ratio"),
  max.path.edge.ratio.deviation.thld = 0.1,
  path.edge.ratio.percentile = 0.5,
  prune.tau = 1.05,
  prune.local.k = NULL,
  with.pruned.edge.stats = FALSE,
  connect.components = FALSE,
  connect.method = c("component.mst", "component.mst.ann", "global.mst"),
  bridge.k = NULL,
  bridge.k.max = NULL,
  bridge.growth = 2
)

```

Arguments

<code>X</code>	Numeric matrix or data frame with observations in rows.
<code>k.scale</code>	Positive integer smaller than <code>nrow(X)</code> . Defines local scale distances σ_i .
<code>delta</code>	Positive numeric scalar multiplying the geometric-mean adaptive radius.
<code>radius.search</code>	Character scalar. "ann" uses the bundled ANN kd-tree exact radius-search back-end inherited from <code>create.rknn.graph()</code> . "all.pairs" uses the direct $O(n^2)$ reference path.
<code>return.timing</code>	Logical scalar. If TRUE, attach the same construction timing table returned by <code>create.rknn.graph()</code> , including ANN setup, local-scale search, fixed-radius candidate search, edge materialization, and graph finalization when <code>radius.search = "ann"</code> .
<code>graph.detail</code>	Character scalar. "full" returns the complete graph lifecycle object. "minimal" returns only core graph fields and is allowed only with <code>prune.method = "none"</code> and <code>connect.components = FALSE</code> .
<code>prune.method</code>	Character scalar. "none" disables geometric pruning. "local.geodesic" applies the experimental local geometric pruning stage before optional MST connectivity repair. "global.geodesic.ratio" applies whole-graph geodesic-ratio pruning before optional MST connectivity repair.
<code>max.path.edge.ratio.deviation.thld</code>	Numeric scalar in $[0, 0.2)$. For <code>prune.method = "global.geodesic.ratio"</code> , an edge may be removed when the shortest alternative path is at most $1 + \text{max.path.edge.ratio.deviation.thld}$ times the direct edge length.
<code>path.edge.ratio.percentile</code>	Numeric scalar in $[0, 1]$. For <code>prune.method = "global.geodesic.ratio"</code> , only edges at or above this edge length percentile are considered.

prune.tau	Numeric scalar greater than 1. For local geometric pruning, an edge may be removed when a retained local alternative path is at most this multiplicative factor times the direct edge length.
prune.local.k	Integer scalar or NULL. Number of nearest neighbors used to form local neighborhoods for pruning. For fixed-radius graphs, NULL uses the median positive raw graph degree, clipped to $[1, n - 1]$. For adaptive-radius graphs, NULL defaults to <code>k.scale</code> .
with.pruned.edge.stats	Logical scalar. If TRUE, return a data frame with one row per locally pruned edge.
connect.components	Logical scalar. If TRUE, add MST bridge edges so the final graph is connected whenever possible.
connect.method	Character scalar. "component.mst" adds exact shortest inter-component bridges. "component.mst.ann" tries sparse ANN bridge candidates before automatic exact fallback. "global.mst" unions the graph with the full Euclidean MST.
bridge.k	Integer scalar or NULL. Initial ANN bridge neighborhood size for <code>connect.method = "component.mst.ann"</code> .
bridge.k.max	Integer scalar or NULL. Maximum ANN bridge neighborhood size before exact fallback.
bridge.growth	Numeric scalar greater than 1. Multiplicative growth factor for ANN bridge neighborhoods.

Value

A list inheriting from "cknn_graph" and "adaptive_radius_graph". It contains the same lifecycle fields as `create.rknn.graph()` with `type = "adaptive.radius"`, `radius_rule = "geomean"`, `radius_factor = delta`, and `graph_rule = "continuous.knn"`.

Examples

```
X <- matrix(c(0, 1, 3), ncol = 1)
as.matrix(graph.edges(create.cknn.graph(X, k.scale = 1, delta = 1))[, c("from", "to")])
```

create.cmst.graph	<i>Construct a Minimal Spanning Tree (MST) Completion Graph</i>
-------------------	---

Description

Constructs a completion of the Minimal Spanning Tree (MST) graph from a numeric data matrix. The graph is constructed in two steps: first, a MST is built connecting all data points using minimal total edge length; then, additional edges are added between any pair of points whose Euclidean distance is less than or equal to a quantile threshold based on the MST edge length distribution.

Usage

```
create.cmst.graph(
  X,
  q.thld = 0.9,
  pca.dim = 100,
  variance.explained = 0.99,
  verbose = TRUE
)
```

Arguments

<code>X</code>	A numeric matrix or data frame of shape $n \times d$, where each row represents a data point in d -dimensional space.
<code>q.thld</code>	Numeric scalar between 0 and 1 (exclusive). The quantile threshold for MST completion. Edges are added between points whose distance is less than or equal to the <code>q.thld</code> -quantile of MST edge weights. Default is 0.9.
<code>pca.dim</code>	Positive integer or NULL. If provided and <code>ncol(X) > pca.dim</code> , dimensionality is reduced to this many principal components before graph construction. Must be less than $\min(n-1, p)$ where n is the number of observations and p is the number of variables. Default is 100.
<code>variance.explained</code>	Numeric between 0 and 1 (exclusive) or NULL. If provided, selects the minimal number of PCA components such that this proportion of total variance is retained (up to <code>pca.dim</code> components). Ignored if <code>pca.dim</code> is NULL. Default is 0.99.
<code>verbose</code>	Logical. If TRUE, prints progress messages during computation. Default is TRUE.

Details

The MST completion process enhances connectivity in the original MST by adding edges between vertices that are "close" according to the distance distribution in the MST. This can be useful for creating more robust graph representations of data that maintain local structure while avoiding long-range connections.

When PCA is applied (either through `pca.dim` or `variance.explained`), the data is first centered and projected onto the leading principal components before graph construction. This can significantly reduce computation time for high-dimensional data while preserving the most important variation.

Value

A `dgraph` with `raw` (MST) and `final` (completed) stages. Use graph accessors to inspect topology and lengths; construction details are in `metadata`.

References

Gower, J. C., & Ross, G. J. S. (1969). Minimum spanning trees and single linkage cluster analysis. *Applied Statistics*, 18(1), 54-64.

See Also

`stats::prcomp()` for principal component analysis.

Examples

```
set.seed(123)
X <- matrix(rnorm(60), nrow = 20, ncol = 3)
graph <- create.cmst.graph(X, verbose = FALSE)
graph.order(graph)
nrow(graph.edges(graph))
```

```
create.geodesic.iknn.graph
```

Create a graph-geodesic iKNN graph

Description

Each cover contains its source vertex plus its k nearest other vertices. Equal distances are resolved by ascending vertex index. Intersecting covers create edges whose lengths are shortest-path distances in the input graph.

Usage

```
create.geodesic.iknn.graph(graph, k, small.component = c("error", "truncate"))
```

Arguments

<code>graph</code>	A dgraph with stored finite, nonnegative lengths.
<code>k</code>	Number of nearest other vertices; integer $1 \leq k < n$.
<code>small.component</code>	Default "error" requires at least $k + 1$ vertices in every component. "truncate" uses all reachable other vertices in smaller components, recording per-vertex effective k in neighborhood metadata.

Value

A dgraph with a final stage, lengths and an overlap edge attribute. `metadata$neighborhood` records requested and effective sizes and the tie rule.

Examples

```
graph <- create.graph("chain", 3)
create.geodesic.iknn.graph(graph, k = 1)
```

create.graph

*Create a Standard Graph***Description**

Construct a standard topology or a simple geometric graph. All types return a `dgraph()` and use compact, 1-based adjacency indices. `type` is required; type names and names in `...` must match exactly.

Usage

```
create.graph(type, n = NULL, ..., labels = NULL)
```

Arguments

<code>type</code>	Graph type: "empty", "complete", "chain", "cycle", "complete_bipartite", "star", "random" or "circle".
<code>n</code>	Number of vertices. Required except when inferred from chain <code>x</code> , bipartite sizes or star arms. If supplied alongside those arguments, it must agree. Empty graphs permit zero vertices; chains require at least two, cycles and circles at least three, and other types at least one.
<code>...</code>	Named type-specific arguments, described below. Unknown, duplicated, unnamed and irrelevant arguments error.
<code>labels</code>	Optional unique, nonmissing character or numeric vertex labels, one per vertex. Labels name adjacency lists and are stored in <code>metadata\$labels</code> ; they never change adjacency indices. For chains with <code>x</code> , supply labels in the original input order.

Value

A `dgraph` with one final stage and construction information in `metadata`, including type. Inspect it with `graph.adjacency()`, `graph.lengths()`, `graph.edges()` and `graph.order()`.

Types and arguments

`empty`, `complete`, `cycle` Only `n` and `labels`. These return topology without stored lengths. A `cycle` closes a chain with one edge.

`chain` `span = 1` connects up to `span` positions on each side, giving at most $2 * \text{span}$ neighbors. It must be an integer from 1 to $n - 1$; it does not use the nearest-neighbor meaning of `k`. Optional finite numeric `x` orders vertices by coordinate (ties by input position) and supplies absolute coordinate differences as lengths. Without `x`, lengths are one. Optional vector `y` requires `x` and is reordered with it. `Metadata` contains `order` (sorted-to-input indices), `x.sorted` and `y.sorted`.

`complete_bipartite` Required sizes, two positive integers. All pairs across the two parts are connected; there are no within-part edges or stored lengths. Vertices in the first part come first.

star Required arms, at least two positive integer edge counts. Chains of those lengths share vertex 1 as their center. Thus $n = 1 + \text{sum}(\text{arms})$; all-one arms give an ordinary star. Vertices are numbered along successive arms. No lengths are stored.

circle `sampling = "uniform"` or `"random"` (default), `edge.length = "arc"` (default) or `"chord"`, and optional seed. Vertices are ordered by angle on the unit circle and consecutive vertices, including last-to-first, are connected. Arc lengths measure the shorter unit-circle arc between endpoints, even when the gap in the sampling order exceeds π . Chords are Euclidean distances. Metadata contains angles (radians) and coordinates (x/y columns).

random Required finite `mean.degree`, `connected = TRUE`, and optional seed. The edge count is $\text{floor}(n * \text{mean.degree} / 2)$; $0 \leq \text{mean.degree} \leq n - 1$. If connected, this count must be at least $n - 1$. A randomly ordered growing tree is built first, then a uniform subset of remaining pairs is added. This is not uniform sampling over connected graphs or spanning trees. If disconnected graphs are allowed, a uniform subset of all pairs is sampled. Each undirected edge receives one independent length uniform between 0.5 and 1.5. Candidate-pair storage is quadratic in n ; this constructor is intended for small examples. Metadata records requested and realized mean degrees and connectivity.

Random numbers

For `random` and `circle`, `seed = NULL` uses and advances the caller's current random stream. An explicit nonnegative integer seed makes the call reproducible under the current RNG kind and restores the caller's RNG state afterwards, including an initially absent state. Uniform circle sampling consumes no random numbers. The richer geometry sampling API has its own seed/state continuation contract; see [sample.synthetic.geometry\(\)](#).

Examples

```
graph.order(create.graph("empty", n = 4))
graph.edges(create.graph("complete", n = 3))
chain <- create.graph("chain", x = c(3, 1, 2), span = 1,
                     labels = c("third", "first", "second"))
graph.adjacency(chain)
graph.lengths(chain)
graph.edges(create.graph("cycle", n = 4))
graph.order(create.graph("complete_bipartite", sizes = c(2, 3)))
graph.order(create.graph("star", arms = c(2, 3, 1)))
graph.edges(create.graph("random", n = 6, mean.degree = 2, seed = 10))
circle <- create.graph("circle", n = 8, sampling = "uniform",
                      edge.length = "chord")
circle$metadata$coordinates
```

create.grid.graph

Create a Refined Graph with Approximately Uniform Edge Spacing

Description

Create a Refined Graph with Approximately Uniform Edge Spacing

Usage

```
create.grid.graph(
  adj.list,
  length.list,
  grid.size,
  start.vertex = 1L,
  snap.tolerance = 0.1
)
```

Arguments

adj.list Input graph adjacency list.
length.list Edge-length list matching adj.list.
grid.size Target grid size parameter.
start.vertex Starting vertex used for breadth-first grid placement.
snap.tolerance Grid snapping tolerance.

Value

A dgraph object. Use [graph.adjacency\(\)](#), [graph.lengths\(\)](#), [graph.edges\(\)](#) and [graph.stages\(\)](#) to inspect its stored graph stages. Construction and diagnostic information is stored in metadata.

Examples

```
chain <- create.graph("chain", n = 3)
grid <- create.grid.graph(graph.adjacency(chain), graph.lengths(chain), grid.size = 5)
grid$metadata$grid_vertices
```

create.ian.graph	<i>Construct an Iterated Adaptive Neighborhood Graph</i>
------------------	--

Description

Construct the initial Gabriel graph, adapt local scales and prune edges, returning graphs, affinities and diagnostics. By default, proposed bridge edges are protected so that pruning retains connectivity, and the audited retry-power numerical policy permits one checked retry after an eligible solver rejection. These are explicit variants of reference IAN.

Usage

```
create.ian.graph(
  X,
  distances = NULL,
  specimen.ids = NULL,
  participant.ids = NULL,
```

```

graph = NULL,
diagnostics = c("summary", "full"),
backend = NULL,
max.solves = 10000L,
numerical.policy = "IAN evaluated-LP retry-power 0.1",
preserve.connectivity = TRUE
)

```

Arguments

<code>X</code>	Finite numeric specimen-by-feature matrix, at least two rows and one column. There is no fixed experimental row cap. Input size must fit R/native index representations and available memory. Dense distances and affinities require quadratic storage: each n-by-n double matrix uses $8 \times n \times n$ bytes before overhead. Several matrices/copies coexist; this is not a peak-memory estimate. Initial Gabriel construction has cubic worst-case cost. Full diagnostics retain additional dense data. See the backend guide for tested sizes.
<code>distances</code>	Optional unsquared distance matrix or dist. When absent, Euclidean distances are computed with <code>stats::dist(X)</code> . Supplied distances are used exactly; duplicate feature rows must have identical distance rows. Coordinates are always required to define duplicate profiles. Row/column order must match <code>X</code> ; named distances must match specimen IDs.
<code>specimen.ids</code>	Unique nonempty IDs; defaults to row names or row numbers.
<code>participant.ids</code>	Optional specimen-level nonempty IDs, possibly repeated.
<code>graph</code>	Reserved supplied-graph argument; currently must be NULL. The actual initial Gabriel graph is always constructed by IAN.
<code>diagnostics</code>	"summary" or "full"; full includes dense LP payloads.
<code>backend</code>	Optional path to the separately built <code>dgraphs_ian.so</code> module.
<code>max.solves</code>	Positive integer safety limit; reaching it returns refusal.
<code>numerical.policy</code>	Exactly "IAN evaluated-LP 1.0" (strict, without retries) or "IAN evaluated-LP retry-power 0.1" (default: one eligible checked retry).
<code>preserve.connectivity</code>	Logical scalar, default TRUE. Use FALSE for reference pruning, which may disconnect the graph. With TRUE, cache encountered bridges and skip them before testing each proposed edge's pruning eligibility. Check noncached edges in the current graph after preceding deletions. Skips do not consume the deletion allowance. All vertices are retained. An initially disconnected graph returns refusal. This explicit variant does not change the numerical solver policy.

Details

Build the optional module once with `build.ian.backend()` and pass its returned path as `backend`. The supported build target is macOS arm64. The function itself does not compile code, download dependencies or launch an external solver. See `system.file("ian", "README.md", package = "dgraphs")` for the numerical contract, setup requirements and bounded qualification.

Input rows are specimens; graph vertices are unique feature profiles in first-occurrence order. Always check complete before using final_graph. Invalid R arguments or an unavailable backend raise an R error. Numerical refusal and interruption during engine execution return an incomplete result with the available diagnostics. Memory exhaustion or process termination is not a recoverable-result guarantee.

The default numerical policy is IAN evaluated-LP retry-power 0.1. A rejected original return remains rejected. Its single eligible retry must itself pass strict solver success and the unchanged original-unit checks. numerical.policy="IAN evaluated-LP 1.0" together with preserve.connectivity=FALSE selects the previous strict/reference behavior. This public default adoption changes neither policy's implementation.

The returned top-level fields are complete, error, initial_graph, final_graph, last_valid_graph, mapping, scales, affinity, diagnostics and backend. Graphs are [dgraph\(\)](#) objects with metric edge lengths in input distance units; affinity values are separate similarities. Mapping contains one-based representatives and member_to_profile, plus specimen, profile and participant IDs. Repeated participant IDs do not merge specimens. Error information contains kind, code and message. diagnostics\$solver_history retains both accepted and rejected attempts. Backend information identifies the selected policies, source and settings. Checkpoint/resume is not exposed through this R interface.

Value

A list with complete, structured error, initial Gabriel graph, final_graph only on full completion, last_valid_graph (possibly partial), profile mapping, local scales and an affinity matrix distinct from metric edge lengths. Graph indices and mappings are one-based. Full traces retain original zero-based core indices and declare this in diagnostics. Summary diagnostics include per-solve status, acceptance, settings, residuals and iteration counts. Refusal and interruption return incomplete structured results; invalid R arguments error before native execution. Interrupts are checked at engine events; they do not interrupt an active solver call. In connectivity mode, diagnostics\$connectivity contains protected.edges (one-based profile rows and IDs, first/last encounter iteration, count and first statistic), per-iteration history, and stop.reason. Iterations in this summary are one-based. Protected edges are encountered proposals, not necessarily edges that would pass the pruning criteria. Full traces also include every edge proposal and whether eligibility was tested. A complete pass with no deletion stops, including when statistical candidates remain protected. Partial results retain available protection diagnostics; final_graph remains NULL if later optimization or affinity construction fails.

See Also

[build.ian.backend\(\)](#)

Examples

```
# Set this variable to the path returned by build.ian.backend().
backend <- Sys.getenv("DGRAPHS_IAN_BACKEND")
if (nzchar(backend) && file.exists(backend)) {
  X <- rbind(c(0, 0), c(1, 0), c(2, 0), c(0, 0))
  fit <- create.ian.graph(X, backend = backend,
    specimen.ids = c("alpha", "beta", "gamma", "delta"))
  stopifnot(fit$complete)
```

```

graph.edges(fit$initial_graph)
graph.edges(fit$final_graph)
fit$mapping$member_to_profile # Four specimens, three unique profiles.
fit$diagnostics$connectivity$protected.edges
}

```

create.iknn.graphs *Create intersection k-nearest neighbor graphs with dual pruning*

Description

For each $k \in [k_{\min}, k_{\max}]$, builds an intersection-weighted k-NN graph and applies two pruning schemes: (1) geometric (path-to-edge ratio) and (2) intersection-size. Optionally performs PCA before graph construction.

Usage

```

create.iknn.graphs(
  X,
  k.values,
  max.path.edge.ratio.deviation.thld = 0.1,
  path.edge.ratio.percentile = 0.5,
  threshold.percentile = 0,
  compute.full = TRUE,
  with.isize.pruning = FALSE,
  with.edge.pruning.stats = FALSE,
  pca.dim = 100,
  variance.explained = 0.99,
  knn.metric = c("euclidean", "linf.simplex"),
  linf.tol = sqrt(.Machine$double.eps),
  verbose = TRUE,
  knn.cache.path = NULL,
  knn.cache.mode = c("none", "read", "write", "readwrite")
)

```

Arguments

X	A numeric matrix (or object coercible to a numeric matrix) with rows = observations and columns = features.
k.values	Strictly increasing integer vector of neighborhood sizes, each between 1 and n - 1.
max.path.edge.ratio.deviation.thld	Numeric in $[0, 0.2)$. Geometric pruning removes an edge (i, j) when there exists an alternative path between i and j whose path/edge length ratio minus 1.0 is <i>less than</i> this threshold. This is a deviation threshold δ in $[0, 0.2)$. Internally we compare the path-to-edge ratio R to $1 + \delta$.

path.edge.ratio.percentile	Numeric in $[0, 1]$. Only edges with length above this percentile are considered for geometric pruning.
threshold.percentile	Numeric in $[0, 0.5]$. Percentile threshold for quantile-based edge length pruning. Default is 0 (no quantile pruning). When greater than 0, edges in the top $(1 - \text{threshold.percentile})$ quantile by length are removed if their removal preserves graph connectivity. For example, <code>threshold.percentile = 0.9</code> removes edges in the top 10%. This pruning is applied after geometric pruning and targets unusually long edges based on absolute edge lengths rather than path-to-edge ratios.
compute.full	Logical controlling graph-list outputs. If TRUE, return <code>geom_pruned_graphs</code> (and <code>isize_pruned_graphs</code> when with <code>isize.pruning = TRUE</code>). If FALSE, both graph lists are NULL and only summary outputs are returned (<code>k_statistics</code> , plus <code>edge_pruning_stats</code> when requested).
with.isize.pruning	Logical. If TRUE, compute and return intersection-size pruned graphs/statistics. Default is FALSE.
with.edge.pruning.stats	Logical. If TRUE, compute and return edge-level pruning statistics. Default is FALSE.
pca.dim	Positive integer or NULL. If not NULL and <code>ncol(X) > pca.dim</code> , PCA is used to reduce to at most <code>pca.dim</code> components.
variance.explained	Numeric in $(0, 1]$ or NULL. If not NULL, choose the smallest number of PCs whose cumulative variance explained exceeds this threshold, capped by <code>pca.dim</code> .
knn.metric	Character scalar specifying the geometry used for kNN search. "euclidean" uses ordinary ambient Euclidean distance. "linf.simplex" uses the unfolded intrinsic metric on the L^∞ -simplex and requires rows of <code>X</code> to be L^∞ -normalized.
linf.tol	Positive numeric tolerance used only when <code>knn.metric = "linf.simplex"</code> to identify active simplex faces and validate that <code>max(row) = 1</code> . Native graph construction is serial.
verbose	Logical; print progress and timing.
knn.cache.path	Optional character scalar path to a binary kNN cache file. Used only when <code>knn.cache.mode != "none"</code> .
knn.cache.mode	Character cache mode: • "none": always compute kNN; do not read/write cache. • "read": read kNN from cache only; if cache is missing/invalid, error. • "write": always compute kNN and atomically write/overwrite cache. • "readwrite": read valid cache when available; if cache file is missing, compute and write cache; if cache exists but is invalid, error.

Details

Geometric pruning uses the deviation threshold `max.path.edge.ratio.deviation.thld` and the filtering percentile `path.edge.ratio.percentile`. Intersection-size pruning currently uses a maximum alternative path length of 2.

Output behavior by flags:

- `compute.full = FALSE`: both `geom_pruned_graphs` and `isize_pruned_graphs` are NULL.
- `compute.full = TRUE` and `with.isize.pruning = FALSE`: `geom_pruned_graphs` is returned and `isize_pruned_graphs` is NULL.

Value

A list of class "iknn_graphs" with entries:

k_statistics Matrix of per- k edge counts and reductions. (If the C++ side supplies column names, they're preserved. Otherwise we add names consistent with what the C++ returns.)

geom_pruned_graphs If `compute.full=TRUE`, list of geometrically pruned graphs (adjacency + weights); otherwise NULL.

isize_pruned_graphs If `compute.full=TRUE` and `with.isize.pruning=TRUE`, list of intersection-size pruned graphs; otherwise NULL.

edge_pruning_stats If `with.edge.pruning.stats=TRUE`, list (per k) of edge-level statistics; otherwise NULL.

Examples

```
# Generate sample data
X <- matrix(rnorm(100 * 5), 100, 5)

# Basic usage
res1 <- create.iknn.graphs(X, k.values = seq.int(3, 10), compute.full = FALSE)

# With custom pruning parameters
res2 <- create.iknn.graphs(X, k.values = seq.int(3, 10),
  max.path.edge.ratio.deviation.thld = 0.1,
  path.edge.ratio.percentile = 0.5, compute.full = TRUE, verbose = TRUE)

# View statistics for each k
print(res2$k_statistics)
```

create.iterated.iknn.graphs

Create iterated graph-geodesic iKNN graphs

Description

Constructs G_0 with `create.iknn.graphs()`, then constructs $G_1, G_2, \dots, G_m$ by repeatedly applying `create.geodesic.iknn.graph()` to each graph in the `k.values` sequence. This implements the iterated nerve rule

$$\{i, j\} \in E(G_{t+1}) \iff kNN_{G_t}(i) \cap kNN_{G_t}(j) \neq \emptyset,$$

with edge length

$$\ell_{t+1}(i, j) = d_{G_t}(i, j).$$

Usage

```
create.iterated.iknn.graphs(
  X,
  k.values,
  n.iterations = 3L,
  small.component = c("error", "truncate"),
  max.path.edge.ratio.deviation.thld = 0,
  path.edge.ratio.percentile = 0.5,
  threshold.percentile = 0,
  pca.dim = 100,
  variance.explained = 0.99,
  verbose = TRUE,
  knn.cache.path = NULL,
  knn.cache.mode = c("none", "read", "write", "readwrite")
)
```

Arguments

<code>X</code>	Numeric matrix with rows as observations and columns as features.
<code>k.values</code>	Strictly increasing integer vector of neighborhood sizes, each between 1 and $n - 1$.
<code>n.iterations</code>	Non-negative integer number of geodesic rebuilds after G_0 . The default 3 returns G_0 , G_1 , G_2 , and G_3 .
<code>small.component</code>	Component-size policy forwarded to every geodesic rebuild.
<code>max.path.edge.ratio.deviation.thld</code> , <code>path.edge.ratio.percentile</code> , <code>threshold.percentile</code>	Initial G_0 pruning arguments forwarded to <code>create.iknn.graphs()</code> . The default deviation and quantile thresholds are zero so that G_0 is the unpruned iKNN 1-skeleton.
<code>pca.dim</code> , <code>variance.explained</code> , <code>verbose</code> , <code>knn.cache.path</code> , <code>knn.cache.mode</code>	Additional arguments forwarded to <code>create.iknn.graphs()</code> for the initial G_0 construction.

Value

A list of class "iterated_iknn_graphs" with entries:

k.values Integer vector of requested k values.
n_iterations Number of geodesic rebuilds after G_0 .
initial_graphs The "iknn_graphs" object returned by `create.iknn.graphs()` for G_0 .
graphs Nested list named G_0 , G_1 , ...; each entry is a named list of graph objects for $k.values$.
summary Data frame with one row per iteration and k .

Examples

```
set.seed(1)
X <- matrix(rnorm(30), ncol = 2)
out <- create.iterated.iknn.graphs(X, k.values = seq.int(2, 3), n.iterations = 1,
  verbose = FALSE)
out$summary
```

```
create.maximal.packing
```

Create a Maximal Packing of Vertices in a Graph

Description

Creates a maximal packing of vertices based on a specified grid size. The algorithm places vertices in the graph using a separation distance that produces a vertex set packing of size approximately equal to the given grid size. A vertex packing is a set of vertices where each pair is separated by at least a specified distance.

Usage

```
create.maximal.packing(
  adj.list,
  length.list,
  grid.size,
  max.iterations = 20,
  precision = 0.1
)
```

Arguments

<code>adj.list</code>	A list where each element is a vector of adjacent vertex indices (1-based) for the corresponding vertex. Must represent an undirected graph.
<code>length.list</code>	A list where each element is a vector of edge weights corresponding to the adjacencies in <code>adj.list</code> . All weights must be positive.
<code>grid.size</code>	A positive integer (≥ 2) specifying the approximate separation distance between vertices in the packing.
<code>max.iterations</code>	Maximum number of iterations for the algorithm to converge. Default is 20.
<code>precision</code>	Precision threshold for convergence of the algorithm. Must be between 0 and 0.5. Default is 0.1.

Details

The function computes a maximal packing by iteratively selecting vertices that are approximately `grid.size` apart from each other. The process starts from one of the graph's diameter endpoints (determined automatically) and continues until no more vertices can be added to the packing without violating the distance constraint.

The returned `graph_diameter` represents the longest shortest path in the graph, which provides insight into the graph's overall structure and extent.

The `max_packing_radius` value indicates the minimum distance that separates any two vertices in the packing. This value is determined through binary search to achieve a packing of approximately the requested size.

The function validates input parameters and ensures that the graph structure is properly specified before computing the packing. The graph must be undirected (symmetric adjacency) and connected.

Value

A maximal_packing result containing its graph (a dgraph), `grid_vertices` (packing indices), `graph_diameter`, and `max_packing_radius` (the guaranteed separation of packing vertices).

See Also

[validate.maximal.packing](#), [verify.maximal.packing](#)

Examples

```
adj.list <- list(c(2), c(1, 3), c(2, 4), c(3, 5), c(4))
length.list <- list(c(1), c(1, 1), c(1, 1), c(1, 1), c(1))

result <- create.maximal.packing(adj.list, length.list, grid.size = 2)
result$grid_vertices
result$max_packing_radius
```

create.mknn.graph

Compute a Mutual k-Nearest Neighbor Graph with Weights

Description

Creates an undirected graph where two points are connected by an edge if and only if they are present in each other's k-nearest neighbor (kNN) lists. The weight of each edge represents the distance between the connected vertices.

Usage

```

create.mknn.graph(
  X,
  k,
  prune.method = c("none", "local.geodesic", "global.geodesic.ratio"),
  max.path.edge.ratio.deviation.thld = 0.1,
  path.edge.ratio.percentile = 0.5,
  prune.tau = 1.05,
  prune.local.k = NULL,
  with.pruned.edge.stats = FALSE,
  connect.components = FALSE,
  connect.method = c("component.mst", "component.mst.ann", "global.mst"),
  bridge.k = NULL,
  bridge.k.max = NULL,
  bridge.growth = 2
)

```

Arguments

<code>X</code>	A numeric matrix or data frame where each row represents a data point and each column represents a feature/dimension.
<code>k</code>	A positive integer specifying the number of nearest neighbors to consider, excluding self; require $1 \leq k < n$.
<code>prune.method</code>	Character scalar. "none" disables geometric pruning. "local.geodesic" applies the experimental local geometric pruning stage before optional MST connectivity repair. "global.geodesic.ratio" applies whole-graph geodesic-ratio pruning before optional MST connectivity repair.
<code>max.path.edge.ratio.deviation.thld</code>	Numeric scalar in $[0, 0.2)$. For <code>prune.method = "global.geodesic.ratio"</code> , an edge may be removed when the shortest alternative path is at most $1 + \text{max.path.edge.ratio.deviation.thld}$ times the direct edge length.
<code>path.edge.ratio.percentile</code>	Numeric scalar in $[0, 1]$. For <code>prune.method = "global.geodesic.ratio"</code> , only edges at or above this edge length percentile are considered.
<code>prune.tau</code>	Numeric scalar greater than 1. For local geometric pruning, an edge may be removed when a retained local alternative path is at most this multiplicative factor times the direct edge length.
<code>prune.local.k</code>	Integer scalar or NULL. Number of nearest neighbors used to form local neighborhoods for pruning. Defaults to <code>k</code> .
<code>with.pruned.edge.stats</code>	Logical scalar. If TRUE, return a data frame with one row per locally pruned edge.
<code>connect.components</code>	Logical scalar. If TRUE, add MST bridge edges so the final graph is connected whenever possible.

<code>connect.method</code>	Character scalar. "component.mst" adds exact shortest inter-component bridges. "component.mst.ann" tries sparse ANN bridge candidates before automatic exact fallback. "global.mst" unions the graph with the full Euclidean MST.
<code>bridge.k</code>	Integer scalar or NULL. Initial ANN bridge neighborhood size for <code>connect.method = "component.mst.ann"</code> .
<code>bridge.k.max</code>	Integer scalar or NULL. Maximum ANN bridge neighborhood size before exact fallback.
<code>bridge.growth</code>	Numeric scalar greater than 1. Multiplicative growth factor for ANN bridge neighborhoods.

Details

The mutual k-nearest neighbor graph is a symmetric graph where an edge between vertices *i* and *j* exists if and only if:

- *j* is among the *k* nearest neighbors of *i*, AND
- *i* is among the *k* nearest neighbors of *j*

This mutual relationship ensures that the resulting graph is undirected and typically sparser than a standard k-nearest neighbor graph.

Use graph accessors for the final graph and `graph.stages()` to list stored raw, pruned and repaired stages. Construction details are in metadata.

Value

A dgraph object. Use [graph.adjacency\(\)](#), [graph.lengths\(\)](#), [graph.edges\(\)](#) and [graph.stages\(\)](#) to inspect its stored graph stages. Construction and diagnostic information is stored in metadata.

See Also

[create.mknn.graphs](#) for creating multiple graphs with different *k* values, [summary.mknn_graphs](#) for summarizing graph properties

Examples

```
set.seed(123)
X <- matrix(rnorm(60), ncol = 2)
graph <- create.mknn.graph(X, k = 4)
graph.order(graph)
nrow(graph.edges(graph))
graph.adjacency(graph)[[1]]
```

create.mknngraphs *Create Multiple Mutual kNN Graphs with Geometric Pruning*

Description

Constructs a series of mutual k-nearest neighbor (MkNN) graphs across a range of k values, with optional geometric pruning to remove redundant edges based on alternative path analysis.

Usage

```
create.mknngraphs(
  X,
  k.values,
  max.path.edge.ratio.thld = 1.2,
  path.edge.ratio.percentile = 0.5,
  compute.full = FALSE,
  pca.dim = 100,
  variance.explained = 0.99,
  verbose = FALSE
)
```

Arguments

X	A numeric matrix where rows represent data points and columns represent features. Data frames will be converted to matrices.
k.values	Strictly increasing integer vector of neighborhood sizes, each between 1 and n - 1.
max.path.edge.ratio.thld	Maximum acceptable ratio of alternative path length to direct edge length for pruning; zero disables pruning. Edges with alternative paths having ratio <= this value will be pruned. Default is 1.2. Set to 0 to disable pruning.
path.edge.ratio.percentile	Percentile threshold (0.0-1.0) for edge lengths to consider for pruning. Only edges with length greater than this percentile are evaluated. Default is 0.5.
compute.full	Logical; if TRUE, returns complete graph structures for each k value. If FALSE, returns only summary statistics. Default is FALSE.
pca.dim	Maximum number of principal components to use if dimensionality reduction is applied. Default is 100. Set to NULL to skip dimensionality reduction.
variance.explained	Target percentage of variance to be explained by the principal components (0-1). Default is 0.99. If this can be achieved with fewer than pca.dim components, the smaller number is used. Set to NULL to use exactly pca.dim components.
verbose	Logical; if TRUE, displays progress messages. Default is FALSE.

Details

This function performs the following steps for each k value:

1. **Mutual kNN Graph Construction:** Creates a graph where edges exist only between mutually nearest neighbors.
2. **Geometric Pruning** (optional): Removes edges where alternative paths exist with acceptable length ratios. An edge (i,j) is pruned if there exists a path $i \rightarrow k \rightarrow j$ such that $(d(i,k) + d(k,j)) / d(i,j) \leq \text{threshold}$.
3. **Dimensionality Reduction** (optional): If the data has more than `pca.dim` dimensions, PCA is applied before graph construction to improve computational efficiency and reduce noise.

The geometric pruning step helps create sparser graphs by removing edges that can be well-approximated by two-hop paths, which can improve graph quality for clustering and visualization tasks.

Value

An object of class "mknn_graphs" containing:

k_statistics A data frame with columns: k (k value), n_edges (edges before pruning), n_edges_pruned (edges after pruning), n_removed (number of removed edges), reduction_ratio (proportion of edges removed).

pruned_graphs If `compute.full=TRUE`, a named list of pruned graphs for each k value. NULL otherwise.

edge_pruning_stats A list of pruning statistics for each k value, containing edge lengths and path ratios.

The returned object also has the following attributes:

- `k.values`: The requested neighborhood sizes
- `max.path.edge.ratio.thld`: The pruning threshold used
- `path.edge.ratio.percentile`: The percentile threshold used
- `pca`: If PCA was performed, contains dimensionality reduction details

See Also

[create.mknn.graph](#) for creating a single MkNN graph, [summary.mknn_graphs](#) for summarizing the results

Examples

```
set.seed(123)
X <- matrix(rnorm(80), ncol = 2)
result <- create.mknn.graphs(X, k.values = seq.int(3, 4), compute.full = TRUE, verbose = FALSE)
result$k_statistics
```

```
X.high <- matrix(rnorm(120), nrow = 20, ncol = 6)
result.pca <- create.mknn.graphs(X.high, k.values = seq.int(2, 3), pca.dim = 3, verbose = FALSE)
attr(result.pca, "pca")$n_components
```

create.path.graph

*Construct Path Graphs Across Hop Limits***Description**

Find minimum-length routes using at most each requested number of edges. Equal-length routes prefer fewer hops. One route is stored per unordered pair and can be retrieved in either direction with `get.shortest.path()`.

Usage

```
create.path.graph(graph, h.values, stage = "final")
```

Arguments

graph	A dgraph with finite nonnegative stored lengths.
h.values	One or more strictly increasing positive integer hop limits. A hop counts one traversed edge. Invalid, duplicate or unordered values error; values are never silently rounded or reordered.
stage	Stored graph stage; defaults to "final".

Details

Hop-constrained search retains a separate distance for each hop count, then selects the best route for each pair. With nonnegative lengths, limits above $n - 1$ need no additional search. For each source, auxiliary storage is proportional to $n * \min(h, n - 1)$; storing routes for all reachable pairs can require cubic space. Use small hop limits when possible.

Value

A named `path.graph.series` collection, even for one limit. Names are `h_2`, `h_4`, etc. Each member is a `path.graph` with a graph of reachable pairs, stored `shortest.paths`, and an `h` attribute recording the requested limit. Its graph stores route lengths and a `hops` edge attribute. Routes use the input graph's vertex indices. Empty graphs and isolated vertices are preserved.

Examples

```
graph <- create.graph("chain", n = 5)
paths <- create.path.graph(graph, h.values = c(2, 4))
get.shortest.path(paths[["h_4"]], from = 1, to = 5)
get.shortest.path(paths[["h_4"]], from = 5, to = 1)
compare.paths(paths, from = 1, to = 5)
```

create.plm.graph	<i>Create a Path Length Matrix Graph Structure</i>
------------------	--

Description

Create a Path Length Matrix Graph Structure

Usage

```
create.plm.graph(adj.list, length.list, h)
```

Arguments

adj.list	Adjacency list using 1-based vertex indices.
length.list	Edge-length list matching adj.list.
h	Odd positive integer maximum path length in hops.

Value

An object of class path.graph.plm.

Examples

```
graph <- list(2L, c(1L, 3L), 2L)
lengths <- list(1, c(1, 2), 2)
create.plm.graph(graph, lengths, h = 3)
```

create.rknn.graph	<i>Compute a Radius-kNN Graph</i>
-------------------	-----------------------------------

Description

Creates an undirected Euclidean radius graph from a numeric data matrix. Use type = "fixed" for a fixed-radius graph, where vertices i and j are adjacent exactly when their Euclidean distance is at most radius. Use type = "adaptive.radius" for an adaptive-radius graph based on observation-specific local scale distances.

Usage

```
create.rknn.graph(
  X,
  type = c("fixed", "adaptive.radius"),
  radius = NULL,
  k.scale = NULL,
  radius.factor = 1,
  radius.rule = c("max", "min", "geomean"),
  radius.search = c("ann", "all.pairs"),
  return.timing = FALSE,
  graph.detail = c("full", "minimal"),
  prune.method = c("none", "local.geodesic", "global.geodesic.ratio"),
  max.path.edge.ratio.deviation.thld = 0.1,
  path.edge.ratio.percentile = 0.5,
  prune.tau = 1.05,
  prune.local.k = NULL,
  with.pruned.edge.stats = FALSE,
  connect.components = FALSE,
  connect.method = c("component.mst", "component.mst.ann", "global.mst"),
  bridge.k = NULL,
  bridge.k.max = NULL,
  bridge.growth = 2
)
```

Arguments

<code>X</code>	Numeric matrix or data frame with observations in rows.
<code>type</code>	Character scalar. "fixed" builds a fixed-radius graph using <code>radius</code> . "adaptive.radius" builds an adaptive-radius graph using <code>k.scale</code> , <code>radius.factor</code> , and <code>radius.rule</code> .
<code>radius</code>	Positive numeric scalar. Edges are included when $\ x_i - x_j\ _2 \leq \text{radius}$. Required for <code>type = "fixed"</code> .
<code>k.scale</code>	Positive integer smaller than <code>nrow(X)</code> . Defines local scale distances σ_i . Required for <code>type = "adaptive.radius"</code> .
<code>radius.factor</code>	Positive numeric scalar multiplying the adaptive radius.
<code>radius.rule</code>	Character scalar. "max" uses $d_{ij} \leq \text{radius.factor} \max(\sigma_i, \sigma_j)$; "min" uses $d_{ij} \leq \text{radius.factor} \min(\sigma_i, \sigma_j)$; and "geomean" uses $d_{ij} \leq \text{radius.factor} \sqrt{\sigma_i \sigma_j}$. The "geomean" rule is the continuous-kNN support rule.
<code>radius.search</code>	Character scalar. "ann" uses the bundled ANN kd-tree to perform exact fixed-radius candidate searches before applying the pair-specific adaptive-radius rule. "all.pairs" uses the direct $O(n^2)$ pair scan and is retained as a reference path. Used only for <code>type = "adaptive.radius"</code> .
<code>return.timing</code>	Logical scalar. If TRUE, attach a construction timing table for adaptive-radius graphs.
<code>graph.detail</code>	Character scalar. "full" returns the complete graph lifecycle object for adaptive-radius graphs. "minimal" returns only the graph fields needed by fitting code and is currently allowed only for adaptive-radius graphs with <code>prune.method = "none"</code> and <code>connect.components = FALSE</code> .

<code>prune.method</code>	Character scalar. "none" disables geometric pruning. "local.geodesic" applies the experimental local geometric pruning stage before optional MST connectivity repair. "global.geodesic.ratio" applies whole-graph geodesic-ratio pruning before optional MST connectivity repair.
<code>max.path.edge.ratio.deviation.thld</code>	Numeric scalar in $[0, 0.2)$. For <code>prune.method = "global.geodesic.ratio"</code> , an edge may be removed when the shortest alternative path is at most $1 + \text{max.path.edge.ratio.deviation.thld}$ times the direct edge length.
<code>path.edge.ratio.percentile</code>	Numeric scalar in $[0, 1]$. For <code>prune.method = "global.geodesic.ratio"</code> , only edges at or above this edge length percentile are considered.
<code>prune.tau</code>	Numeric scalar greater than 1. For local geometric pruning, an edge may be removed when a retained local alternative path is at most this multiplicative factor times the direct edge length.
<code>prune.local.k</code>	Integer scalar or NULL. Number of nearest neighbors used to form local neighborhoods for pruning. For fixed-radius graphs, NULL uses the median positive raw graph degree, clipped to $[1, n - 1]$. For adaptive-radius graphs, NULL defaults to <code>k.scale</code> .
<code>with.pruned.edge.stats</code>	Logical scalar. If TRUE, return a data frame with one row per locally pruned edge.
<code>connect.components</code>	Logical scalar. If TRUE, add MST bridge edges so the final graph is connected whenever possible.
<code>connect.method</code>	Character scalar. "component.mst" adds exact shortest inter-component bridges. "component.mst.ann" tries sparse ANN bridge candidates before automatic exact fallback. "global.mst" unions the graph with the full Euclidean MST.
<code>bridge.k</code>	Integer scalar or NULL. Initial ANN bridge neighborhood size for <code>connect.method = "component.mst.ann"</code> .
<code>bridge.k.max</code>	Integer scalar or NULL. Maximum ANN bridge neighborhood size before exact fallback.
<code>bridge.growth</code>	Numeric scalar greater than 1. Multiplicative growth factor for ANN bridge neighborhoods.

Value

A `dgraph`, with constructor class `radius_graph` for fixed radii or `adaptive_radius_graph` for adaptive radii. Use graph accessors for topology, lengths and retained stages; construction diagnostics are in `metadata`.

Examples

```
X <- matrix(c(0, 1, 3), ncol = 1)
as.matrix(graph.edges(create.rknn.graph(X, type = "fixed", radius = 1.1))[, c("from", "to")])
as.matrix(graph.edges(create.rknn.graph(X, type = "adaptive.radius", k.scale = 1))[, c("from", "to")])
```

create.rknn.graphs	<i>Compute Adaptive Radius-kNN Graphs Across k Values</i>
--------------------	---

Description

Creates a sequence of adaptive-radius graphs by varying the `k.scale` parameter passed to `create.rknn.graph(type = "adaptive.radius")`. By default, ANN-backed construction uses the batched C++ backend while the direct all-pairs reference path uses the scalar R loop. Set `backend = "r"` to force the scalar loop for ANN parity checks.

Usage

```
create.rknn.graphs(X, k.values, ..., backend = c("auto", "cpp", "r"))
```

Arguments

<code>X</code>	Numeric matrix or data frame with observations in rows.
<code>k.values</code>	Strictly increasing integer vector, each between 1 and <code>n - 1</code> . Returned graphs follow this order.
<code>...</code>	Additional arguments forwarded to <code>create.rknn.graph()</code> with <code>type = "adaptive.radius"</code> . The arguments <code>type</code> , <code>k.scale</code> , and <code>radius</code> are reserved by this plural constructor.
<code>backend</code>	Character scalar. "auto" uses the batched C++ ANN backend when <code>radius.search = "ann"</code> and the scalar R loop when <code>radius.search = "all.pairs"</code> . "cpp" forces the batched C++ ANN backend and therefore requires <code>radius.search = "ann"</code> . "r" forces the scalar R loop and is retained as a reference parity backend.

Value

A list of class "rknn_graphs" with components:

graphs A named list of adaptive-radius graph objects, one per `k`.

k_statistics A data frame with one row per `k` containing edge, component, and MST-repair counts.

timing Present only when forwarded options request graph timing; contains backend-specific construction timing rows.

Attributes include `k.values` and `n.vertices`.

See Also

[create.rknn.graph\(\)](#)

Examples

```
X <- matrix(c(0, 1, 3, 4), ncol = 1)
result <- create.rknn.graphs(X, k.values = seq.int(1, 2), radius.search = "all.pairs",
  graph.detail = "minimal",
  prune.method = "none")
names(result$graphs)
result$k_statistics
```

```
create.single.iknn.graph
```

Create a Single Intersection-weighted k-Nearest Neighbors Graph

Description

Creates and prunes an intersection-weighted k-nearest neighbors (IWD-kNN) graph from input data. The graph is constructed based on feature space distances and intersection sizes between neighbor sets.

Usage

```
create.single.iknn.graph(
  X,
  k,
  max.path.edge.ratio.deviation.thld = 0.1,
  prune.method = c("global.geodesic", "none", "local.geodesic", "global.geodesic.ratio"),
  prune.tau = NULL,
  prune.local.k = NULL,
  path.edge.ratio.percentile = 0.5,
  threshold.percentile = 0,
  compute.full = FALSE,
  with.isize.pruning = FALSE,
  with.edge.pruning.stats = FALSE,
  pca.dim = 100,
  variance.explained = 0.99,
  knn.metric = c("euclidean", "linf.simplex"),
  linf.tol = sqrt(.Machine$double.eps),
  connect.components = FALSE,
  connect.method = c("component.mst", "component.mst.ann", "global.mst"),
  bridge.k = NULL,
  bridge.k.max = NULL,
  bridge.growth = 2,
  with.lifecycle.branches = FALSE,
  verbose = TRUE,
  knn.cache.path = NULL,
  knn.cache.mode = c("none", "read", "write", "readwrite")
)
```

Arguments

<code>X</code>	A numeric matrix where rows represent data points and columns represent features. Data frames will be coerced to matrices.
<code>k</code>	Integer scalar. Number of nearest other vertices. Self is explicitly added to each cover, and distance ties use ascending vertex index. Must be positive and less than the number of data points.
<code>max.path.edge.ratio.deviation.thld</code>	Numeric in $[0, 0.2)$. Geometric pruning removes an edge (i, j) when there exists an alternative path between i and j whose path/edge length ratio minus 1.0 is <i>less than</i> this threshold. This is a deviation threshold δ in $[0, 0.2)$. Internally we compare the path-to-edge ratio R to $1 + \delta$. Used when <code>prune.method</code> is "global.geodesic" or "global.geodesic.ratio".
<code>prune.method</code>	Character scalar. "global.geodesic" preserves the historical whole-graph geometric pruning behavior controlled by <code>max.path.edge.ratio.deviation.thld</code> and <code>path.edge.ratio.percentile</code> . "global.geodesic.ratio" is a separately named alias for that whole-graph geodesic-ratio behavior. "local.geodesic" applies the same experimental local geometric pruning stage used by sKNN/mKNN. "none" disables geometric pruning; quantile pruning controlled by <code>threshold.percentile</code> is still honored.
<code>prune.tau</code>	Numeric scalar greater than 1, or NULL. Multiplicative threshold for local geometric pruning. If NULL, defaults to $\max(1 + \text{max.path.edge.ratio.deviation.thld}, 1.05)$.
<code>prune.local.k</code>	Integer scalar or NULL. Number of nearest neighbors used to form local neighborhoods for local geometric pruning. Defaults to <code>k</code> .
<code>path.edge.ratio.percentile</code>	Numeric in $[0, 1]$. Only edges with length above this percentile are considered for geometric pruning.
<code>threshold.percentile</code>	Numeric in $[0, 0.5]$. Percentile threshold for quantile-based edge length pruning. Default is 0 (no quantile pruning). When greater than 0, edges in the top $(1 - \text{threshold.percentile})$ quantile by length are removed if their removal preserves graph connectivity. For example, <code>threshold.percentile = 0.9</code> removes edges in the top 10%. This pruning is applied after geometric pruning and targets unusually long edges based on absolute edge lengths rather than path-to-edge ratios.
<code>compute.full</code>	Logical. Retain additional native component diagnostics. Graph stages are always retained; available overlap values are stored as named edge attributes.
<code>with.isize.pruning</code>	Logical scalar. If TRUE, compute intersection-size pruning outputs and related statistics. Default is FALSE.
<code>with.edge.pruning.stats</code>	Logical scalar. If TRUE, compute edge-level pruning statistics. Default is FALSE.
<code>pca.dim</code>	Maximum number of principal components to use if dimensionality reduction is applied (default: 100). Set to NULL to skip dimensionality reduction.

variance.explained	Percentage of variance to be explained by the principal components (default: 0.99). If this threshold can be met with fewer components than <code>pca.dim</code> , the smaller number will be used. Set to <code>NULL</code> to use exactly <code>pca.dim</code> components.
knn.metric	Character scalar specifying the geometry used for kNN search. "euclidean" uses ordinary ambient Euclidean distance. "linf.simplex" uses the unfolded intrinsic metric on the L^∞ -simplex and requires rows of <code>X</code> to be L^∞ -normalized.
linf.tol	Positive numeric tolerance used only when <code>knn.metric</code> = "linf.simplex" to identify active simplex faces and validate that <code>max(row) = 1</code> .
connect.components	Logical scalar. If <code>TRUE</code> , add MST bridge edges to the final pruned graph so it is connected whenever possible. Currently supported only with <code>knn.metric</code> = "euclidean".
connect.method	Character scalar. "component.mst" adds exact shortest inter-component bridges. "component.mst.ann" tries sparse ANN bridge candidates before automatic exact fallback. "global.mst" unions the graph with the full Euclidean MST.
bridge.k	Integer scalar or <code>NULL</code> . Initial ANN bridge neighborhood size for <code>connect.method</code> = "component.mst.ann".
bridge.k.max	Integer scalar or <code>NULL</code> . Maximum ANN bridge neighborhood size before exact fallback.
bridge.growth	Numeric scalar greater than 1. Multiplicative growth factor for ANN bridge neighborhoods.
with.lifecycle.branches	Logical scalar. If <code>TRUE</code> , compute the additional repaired lifecycle branches <code>raw_repaired_*</code> , <code>pruned_repaired_*</code> , and <code>repaired_pruned_*</code> . This is useful for graph-geodesic reconstruction experiments but can be expensive for the historical global iKNN pruning path, so the default is <code>FALSE</code> .
verbose	Logical. If <code>TRUE</code> , print progress messages. Default is <code>TRUE</code> .
knn.cache.path	Optional character scalar path to a binary kNN cache file. Used only when <code>knn.cache.mode</code> != "none".
knn.cache.mode	Character cache mode: • "none": always compute kNN; do not read/write cache. • "read": read kNN from cache only; if cache is missing/invalid, error. • "write": always compute kNN and atomically write/overwrite cache. • "readwrite": read valid cache when available; if cache file is missing, compute and write cache; if cache exists but is invalid, error.

Details

The default accessors inspect the final graph. Use `stage = "raw"` or `stage = "pruned"` to inspect earlier stages. `graph.stages()` reports which repaired branches are retained; a missing stage is an error.

Value

A `dgraph` object. Use `graph.adjacency()`, `graph.lengths()`, `graph.edges()` and `graph.stages()` to inspect its stored graph stages. Construction and diagnostic information is stored in metadata.

Examples

```
# Create sample data
set.seed(123)
X <- matrix(rnorm(100), ncol = 2)
result <- create.single.iknn.graph(X, k = 3)
summary(result)
```

```
create.sknn.graph
```

```
Compute a Symmetric k-Nearest Neighbor Graph
```

Description

Creates an undirected symmetric k-nearest neighbor (sKNN) graph from a numeric data matrix. An edge between vertices *i* and *j* is present when either *j* is among the *k* nearest neighbors of *i*, or *i* is among the *k* nearest neighbors of *j*.

Usage

```
create.sknn.graph(
  X,
  k,
  prune.edges = FALSE,
  prune.method = c("none", "local.geodesic", "global.geodesic.ratio"),
  max.path.edge.ratio.deviation.thld = 0.1,
  path.edge.ratio.percentile = 0.5,
  prune.tau = 1.05,
  prune.local.k = NULL,
  with.pruned.edge.stats = FALSE,
  connect.components = FALSE,
  connect.method = c("component.mst", "component.mst.ann", "global.mst"),
  edge.weight = c("distance"),
  neighbor.method = c("exact", "ann"),
  ann.eps = 0,
  knn.index = NULL,
  graph.detail = c("full", "minimal"),
  bridge.k = NULL,
  bridge.k.max = NULL,
  bridge.growth = 2,
  input.type = c("observations", "distances")
)
```

Arguments

<i>X</i>	Numeric observation matrix/data frame, or a symmetric numeric distance matrix or dist object when <code>input.type = "distances"</code> .
<i>k</i>	Integer scalar. Number of non-self nearest neighbors.

prune.edges	Logical scalar. If TRUE, apply experimental local geometric edge pruning before optional MST connectivity repair.
prune.method	Character scalar. "none" disables pruning. "local.geodesic" applies experimental local geometric edge pruning. "global.geodesic.ratio" applies whole-graph geodesic-ratio pruning.
max.path.edge.ratio.deviation.thld	Numeric scalar in $[0, 0.2)$. For <code>prune.method = "global.geodesic.ratio"</code> , an edge may be removed when the shortest alternative path is at most $1 + \text{max.path.edge.ratio.deviation.thld}$ times the direct edge length.
path.edge.ratio.percentile	Numeric scalar in $[0, 1]$. For <code>prune.method = "global.geodesic.ratio"</code> , only edges at or above this edge length percentile are considered.
prune.tau	Numeric scalar greater than 1. An edge may be pruned when the shortest retained local alternative path is at most this multiplicative factor times the direct edge length.
prune.local.k	Integer scalar or NULL. Number of nearest neighbors used to form local neighborhoods for pruning. Defaults to k.
with.pruned.edge.stats	Logical scalar. If TRUE, return a data frame with one row per pruned edge and columns for direct length, replacement path length, and their ratio.
connect.components	Logical scalar. If TRUE, add MST bridge edges so that the final graph is connected whenever possible.
connect.method	Character scalar. "component.mst" adds the minimum number of shortest inter-component bridges. "component.mst.ann" tries sparse ANN bridge candidates before automatic exact fallback. "global.mst" unions the sKNN graph with the Euclidean MST on all vertices.
edge.weight	Character scalar. Currently only "distance" is supported.
neighbor.method	Character scalar. "exact" uses all pairwise distances for kNN construction. "ann" uses the bundled ANN kd-tree backend for the kNN construction itself.
ann.eps	Non-negative numeric scalar reserved for approximate ANN search. Currently only 0 is supported.
knn.index	Optional integer matrix of precomputed, one-based, ordered non-self neighbor indices. It must have <code>nrow(X)</code> rows and at least k columns. This is supported only with <code>neighbor.method = "ann"</code> and is primarily useful when constructing several graphs from one cached search.
graph.detail	Character scalar. "full" returns the complete graph lifecycle object. "minimal" skips lifecycle branch construction and is allowed only with <code>prune.method = "none"</code> , <code>prune.edges = FALSE</code> , and <code>connect.components = FALSE</code> .
bridge.k	Integer scalar or NULL. Initial number of ANN neighbors to use for sparse inter-component bridge search when <code>connect.method = "component.mst.ann"</code> . Defaults to $\max(k, 10)$, capped at $\text{nrow}(X) - 1$.
bridge.k.max	Integer scalar or NULL. Maximum number of ANN neighbors to use before exact fallback. Defaults to $\min(\text{nrow}(X) - 1, \max(50, 8 * k, \text{bridge.k}))$.

bridge.growth	Numeric scalar greater than 1. Multiplicative growth factor for bridge candidate neighborhoods.
input.type	Input interpretation. Defaults to "observations" for backward compatibility; symmetry never triggers automatic detection.

Details

With `input.type = "distances"`, supplied distances determine exact neighbor rankings, every edge length, and component/global MST repair. Distance input must be finite, nonnegative, square and symmetric, with a zero diagonal. Symmetry and diagonal tolerance is $1e-12 * \max(1, \max(X))$; accepted asymmetry is averaged and the diagonal set to zero. Row and column names, if present, must be identical and unique. Off-diagonal zeros are allowed. Triangle inequality is not tested, so symmetric dissimilarities are accepted. Ties are resolved by increasing vertex index, excluding self explicitly. ANN search/repair and pruning are unsupported for distance input and error. The series constructor validates distances and ranks neighbors once, through its largest requested `k`. Full lifecycle stages use these same distances.

With no nearest-neighbor ties, the sKNN edge rule is equivalent to

$$d_{ij} \leq \max(\sigma_i, \sigma_j),$$

where σ_i is the distance from point i to its k -th non-self nearest neighbor.

If `connect.components = TRUE`, the graph is augmented with MST edges. The default `connect.method = "component.mst"` first collapses each connected component of the sKNN graph to one component vertex, weights each component pair by the shortest data-space edge between them, and adds the minimum spanning tree of this component graph. This adds exactly $m - 1$ bridge edges when the original sKNN graph has m connected components. `connect.method = "component.mst.ann"` uses ANN nearest-neighbor bridge candidates first and automatically falls back to exact component MST when the sparse candidate graph does not connect all components. The alternative `connect.method = "global.mst"` unions the sKNN graph with the full Euclidean MST on the data points.

`neighbor.method = "exact"` computes all pairwise distances and is the deterministic reference implementation. `neighbor.method = "ann"` uses the bundled ANN kd-tree for the Euclidean kNN search step; exact parity can differ only in nearest-neighbor tie cases. Edge weights are always returned as ordinary Euclidean distances. Exact `component.mst` repair uses exact pairwise bridge distances; `component.mst.ann` uses ANN bridge candidates before guaranteed exact fallback.

If `prune.method = "local.geodesic"` or `prune.edges = TRUE`, an experimental local-geodesic pruning stage is applied after the sKNN support is built and before optional MST connectivity repair. Candidate edges are processed longest-first. For an edge (i, j) , the edge is removed only when the currently retained graph contains an alternative path from i to j , restricted to the union of their local neighborhoods, whose length is at most `prune.tau` times the direct edge length. `prune.method = "global.geodesic.ratio"` instead uses the whole graph as the alternative-path search domain and removes long edges whose shortest alternative path is within the configured geodesic-ratio threshold.

Value

A dgraph object. Use `graph.adjacency()`, `graph.lengths()`, `graph.edges()` and `graph.stages()` to inspect its stored graph stages. Construction and diagnostic information is stored in metadata.

Examples

```
X <- rbind(c(0, 0), c(1, 0), c(10, 0), c(11, 0))
g <- create.sknn.graph(X, k = 1, connect.components = TRUE)
g$metadata$n_components_before
g$metadata$n_components_after
g$metadata$mst_edge_matrix
```

create.sknn.graphs	<i>Compute a Series of Symmetric k-Nearest Neighbor Graphs</i>
--------------------	--

Description

Constructs symmetric k-nearest neighbor graphs for several values of k while performing one bundled ANN search for observations, or one exact ranking of supplied distances, at the largest requested value. The ordered non-self neighbor matrix is sliced for each graph, so lower-k graphs use exactly the same neighbor ranking as the largest graph.

Usage

```
create.sknn.graphs(
  X,
  k.values,
  ...,
  input.type = c("observations", "distances")
)
```

Arguments

X	Numeric observation matrix/data frame, or a symmetric numeric distance matrix or dist object when input.type = "distances".
k.values	Strictly increasing integer vector of neighborhood sizes, each between 1 and n - 1.
...	Named arguments forwarded to create.sknn.graph() . The k and knn.index arguments cannot be supplied. neighbor.method must be "ann" for observations or "exact" for distances if supplied.
input.type	Input interpretation. Defaults to "observations" for backward compatibility; symmetry never triggers automatic detection.

Value

A list of class "sknn_graphs" with components graphs, a named list of "sknn_graph" objects, and k_statistics, a data frame of edge and component counts. Attributes record the requested values and number of vertices.

See Also

[create.sknn.graph\(\)](#)

Examples

```
set.seed(1)
X <- matrix(rnorm(60), ncol = 3)
graphs <- create.sknn.graphs(
  X,
  k.values = c(2, 4),
  graph.detail = "minimal"
)
graphs$k_statistics
```

create.subgraph	<i>Extract an Induced Subgraph</i>
-----------------	------------------------------------

Description

Extract an Induced Subgraph

Usage

```
create.subgraph(graph, vertices, stage = "final")
```

Arguments

graph	A dgraph.
vertices	Unique vertex indices, in the desired output order.
stage	Stored stage to extract.

Value

A dgraph with compact indices and aligned lengths and attributes. `metadata$original.vertices` maps its vertices back to the original graph.

Examples

```
graph <- create.graph("chain", 4)
sub <- create.subgraph(graph, vertices = c(4, 3))
graph.edges(sub)
sub$metadata$original.vertices
```

```
create.threshold.distance.graph
```

Create a Threshold Distance Graph

Description

Create a Threshold Distance Graph

Usage

```
create.threshold.distance.graph(dist.matrix, threshold, include.names = TRUE)
```

Arguments

<code>dist.matrix</code>	Symmetric distance matrix.
<code>threshold</code>	Numeric distance threshold. Vertices with distance less than this value are connected.
<code>include.names</code>	Logical; if TRUE, preserve row names on adjacency and weight lists.

Value

A dgraph object. Use [graph.adjacency\(\)](#), [graph.lengths\(\)](#), [graph.edges\(\)](#) and [graph.stages\(\)](#) to inspect its stored graph stages. Construction and diagnostic information is stored in metadata.

Examples

```
distances <- as.matrix(dist(matrix(c(0, 1, 3), ncol = 1)))
create.threshold.distance.graph(distances, threshold = 1.5)
```

```
detect.graph.endpoints
```

Detect Graph Endpoints from a 3D Embedding

Description

Detects terminal arm tips in a graph by:

1. computing graph endpoint scores from the 3D embedding,
2. optionally smoothing those scores on the graph using [fit.rdgraph.regression\(\)](#) and [refit.rdgraph.regression\(\)](#)
3. finding graph-local maxima with [detect.local.extrema\(\)](#),
4. retaining only maxima that persist across neighborhood scales.

The function works with terminal regions in an embedding; returned endpoints need not be degree-1 vertices.

Usage

```

detect.graph.endpoints(
  adj.list,
  length.list,
  layout.3d,
  neighborhood = c("geodesic_k", "geodesic_radius"),
  k = c(10L, 20L, 30L),
  radius = NULL,
  q = 0.1,
  neighbor.weighting = c("uniform", "inverse_distance", "gaussian"),
  gaussian.sigma = NULL,
  min.neighborhood.size = 3L,
  scale.aggregate = c("mean", "median", "min", "max"),
  score.metric = c("score", "m", "s.q", "s.min"),
  smooth = FALSE,
  fitted.model = NULL,
  smooth.fit.args = NULL,
  smooth.refit.args = NULL,
  detect.max.radius = 2,
  detect.min.neighborhood.size = 2L,
  scale.stability.radius = NULL,
  min.scale.stability = 0.5,
  min.score.quantile = 0.8,
  max.endpoints = NULL,
  verbose = FALSE
)

```

Arguments

<code>adj.list</code>	Graph adjacency list (1-based vertex indices).
<code>length.list</code>	Edge-length list aligned with <code>adj.list</code> .
<code>layout.3d</code>	Numeric matrix or data frame with 3 columns giving the 3D embedding coordinates for graph vertices.
<code>neighborhood</code>	Character string. Either "geodesic_k" (default) or "geodesic_radius".
<code>k</code>	Integer vector of geodesic neighborhood sizes used when <code>neighborhood = "geodesic_k"</code> .
<code>radius</code>	Positive numeric vector of geodesic radii used when <code>neighborhood = "geodesic_radius"</code> .
<code>q</code>	Quantile used for <code>s.q</code> . Must lie in $[0, 1]$. Default is 0.1.
<code>neighbor.weighting</code>	Character string controlling neighbor weights for <code>m</code> and weighted pair quantiles. One of "uniform" (default), "inverse_distance", or "gaussian".
<code>gaussian.sigma</code>	Optional positive numeric scale used when <code>neighbor.weighting = "gaussian"</code> .
<code>min.neighborhood.size</code>	Minimum number of usable neighbors required after removing zero-length embedding vectors.

scale.aggregate	How to aggregate scores across multiple neighborhood scales. One of "mean" (default), "median", "min", or "max".
score.metric	Which score to maximize. One of "score" (default), "m", "s.q", or "s.min".
smooth	Logical; if TRUE, smooths aggregated scores on the graph before detecting extrema.
fitted.model	Optional fitted graph smoother from <code>fit.rdgraph.regression()</code> . If supplied, smoothing reuses its spectral decomposition via <code>refit.rdgraph.regression()</code> .
smooth.fit.args	Optional named list of arguments passed to <code>fit.rdgraph.regression()</code> when <code>smooth = TRUE</code> and <code>fitted.model</code> is NULL. <code>X</code> , <code>y</code> , <code>adj.list</code> , <code>length.list</code> , and <code>verbose.level</code> are filled automatically when not supplied.
smooth.refit.args	Optional named list of arguments passed to <code>refit.rdgraph.regression()</code> when smoothing aggregated score fields.
detect.max.radius	Maximum radius passed to <code>detect.local.extrema()</code> when calling endpoint candidates from the final detection score.
detect.min.neighborhood.size	Minimum neighborhood size passed to <code>detect.local.extrema()</code> when calling endpoint candidates.
scale.stability.radius	Optional non-negative geodesic radius used when translating per-scale local maxima into multiscale support. If NULL (default), uses <code>detect.max.radius</code> . This allows smoothed maxima that shift slightly inward to remain supported by nearby raw multiscale maxima.
min.scale.stability	Minimum fraction of scales for which a vertex must be a local maximum of the per-scale detection score to be retained as an endpoint. Default is 0.5.
min.score.quantile	Quantile filter applied to the final detection score before returning endpoints. Default is 0.8, which suppresses weak local maxima while keeping high-scoring terminal tips.
max.endpoints	Optional positive integer cap on returned endpoints.
verbose	Logical; if TRUE, prints progress.

Value

A list with endpoint vertices, score diagnostics, optional smoothed scores, scale stability summaries, and the local-extrema fit used for endpoint calling.

Examples

```
chain <- create.graph("chain", n = 8)
layout <- cbind(seq_len(8), 0, 0)
endpoints <- detect.graph.endpoints(graph.adjacency(chain), graph.lengths(chain),
  layout, k = c(2,
```

```

    3), min.neighborhood.size = 2, detect.max.radius = 2, detect.min.neighborhood.size = 2,
      min.score.quantile = 0.5)
endpoints$endpoints

```

detect.local.extrema *Detect Local Extrema in a Graph*

Description

Detect Local Extrema in a Graph

Usage

```

detect.local.extrema(
  adj.list,
  length.list,
  y,
  max.radius,
  min.neighborhood.size,
  detect.maxima = TRUE,
  custom.prefix = NULL
)

```

Arguments

adj.list	Graph adjacency list using 1-based vertex indices.
length.list	Edge-length list aligned with adj.list.
y	Numeric vertex function values.
max.radius	Maximum graph-geodesic radius for neighborhoods.
min.neighborhood.size	Minimum neighborhood size required.
detect.maxima	Logical; if TRUE, detect maxima, otherwise minima.
custom.prefix	Optional label prefix.

Details

Summaries use the recorded detection setting for empty results. Empty objects saved by older versions lack this setting; their summaries report NA for the extrema type because it cannot be recovered from empty vectors.

Value

A local_extrema object. Its scalar logical detect.maxima component records whether maxima or minima were requested, even when no extrema are found. The per-extremum is_maxima and type vectors are empty in that case.

Examples

```
chain <- create.graph("chain", n = 5)
extrema <- detect.local.extrema(graph.adjacency(chain), graph.lengths(chain), y = c(1, 3, 1, 2,
  0), max.radius = 1, min.neighborhood.size = 2)
extrema$vertices
```

dgraph

*Construct and Inspect an Undirected Metric Graph***Description**

A dgraph stores an undirected simple graph, including isolated vertices. Adjacency, lengths and scalar edge attributes are validated together and sorted together. Zero lengths are edges; absent lengths remain NULL.

Usage

```
dgraph(adj.list, length.list = NULL, edge.attributes = list())

graph.adjacency(graph, stage = "final")

graph.lengths(graph, stage = "final")

graph.order(graph)

graph.stages(graph)

graph.edge.attribute(graph, name, stage = "final")

graph.edges(graph, stage = "final")
```

Arguments

adj.list	List of 1-based neighbor vectors, one per vertex.
length.list	Optional aligned finite nonnegative numeric length lists.
edge.attributes	Named list of aligned scalar edge-attribute lists.
graph	A dgraph object.
stage	Stored graph stage; defaults to "final". Missing stages error.
name	Name of a stored edge attribute, for example "overlap".

Value

dgraph() returns a graph. The accessors return adjacency lists, length lists (or NULL), an ordered edge data frame, the vertex count, stage names, or the requested attribute list, respectively. Edge tables contain integer from < to, optional numeric length, and attributes.

Examples

```
graph <- dgraph(list(c(3L, 2L), 1L, 1L, integer()),
               list(c(0, 2), 2, 0, numeric()))
graph.order(graph)
graph.edges(graph)
graph.stages(graph)
graph.adjacency(graph)
graph.lengths(graph)
```

edge.diff

Compute Edge Difference Between Two Graphs

Description

Compute Edge Difference Between Two Graphs

Usage

```
edge.diff(adj.list1, adj.list2)
```

Arguments

adj.list1 First adjacency list.
adj.list2 Second adjacency list.

Value

A list containing neighbors present in graph1 but not graph2 for each vertex.

Examples

```
graph1 <- list(c(2L, 3L), 1L, 1L)
graph2 <- list(2L, 1L, integer(0))
edge.diff(graph1, graph2)
```

edge.lengths.synthetic.geometry

Exact latent-segment lengths under a synthetic geometry

Description

For quadforms this integrates the induced metric along each straight latent segment. Flat quadforms reduce exactly to Euclidean distance.

Usage

```
edge.lengths.synthetic.geometry(geometry, from, to, tolerance = 1e-10)
```

Arguments

geometry	A synthetic_quadform_geometry.
from, to	Matching endpoint matrices with one segment per row.
tolerance	Positive integration tolerance.

Value

A numeric vector of segment lengths.

Examples

```
geometry <- synthetic.quadform(1L, 1L)
edge.lengths.synthetic.geometry(geometry, matrix(0), matrix(2))
```

embed.quadform.surface

Lift coordinates onto a quadratic surface using Geometry Lab arithmetic

Description

Lift coordinates onto a quadratic surface using Geometry Lab arithmetic

Usage

```
embed.quadform.surface(latent, coefficients)
```

Arguments

latent	Finite numeric matrix with two columns.
coefficients	Three finite coefficients for u^2 , $2uv$ and v^2 .

Value

A three-column matrix. Version-1 arithmetic preserves existing Geometry Lab cloud identities and reference meshes.

Examples

```
embed.quadform.surface(matrix(c(0, 1, 0, 1), ncol = 2), c(1, 0, -1))
```

```
embed.synthetic.geometry
```

Embed latent coordinates through a synthetic geometry

Description

This deterministic operator performs no random draws. A realized `frame.matrix` is required for random-frame geometries.

Usage

```
embed.synthetic.geometry(geometry, latent, frame.matrix = NULL)
```

Arguments

<code>geometry</code>	A synthetic geometry component.
<code>latent</code>	Latent coordinates in rows.
<code>frame.matrix</code>	Optional realized orthonormal frame.

Value

A numeric matrix of observed coordinates.

Examples

```
geometry <- synthetic.circle()
embed.synthetic.geometry(geometry, matrix(c(0, pi / 2), ncol = 1))
```

explore.graphs

*Open the Graph Reconstruction Explorer***Description**

Explore saved data-geodesic graph reconstruction benchmarks using manual graph selection, metric-based selection, saved layouts and parameter scans. This is the maintained replacement for the dgraphui application.

Usage

```
explore.graphs(
  project = NULL,
  launch = TRUE,
  host = "127.0.0.1",
  port = getOption("shiny.port"),
  launch.browser = interactive(),
  ...
)
```

Arguments

project	Optional benchmark directory, benchmark manifest file, or name previously stored by <code>register.graph.project()</code> . When omitted, the app opens a project selector. No dataset is loaded or fitted automatically.
launch	If TRUE, run the application; if FALSE, return its Shiny application object without starting a server.
host	Interface on which to listen; defaults to the local computer.
port	Optional port passed to <code>shiny::runApp()</code> .
launch.browser	Whether to open the browser when launching.
...	Further arguments to <code>shiny::runApp()</code> .

Details

The optional packages shiny, bslib, plotly and digest are required only for the explorer. The optional grip package is needed only when explicitly generating a missing weighted layout. Opening a project reads saved results; it does not reconstruct graphs, fit layouts or overwrite benchmark assets. Newly generated layouts are stored in a separate dgraphs user cache.

Project registration stores locations in the user's dgraphs data directory, outside the installed package. Set `options(dgraphs.projects_dir = ...)` to choose another catalog directory. Set `options(dgraphs.graph_explore_dir = ...)` to choose the layout cache.

The default display preserves original coordinates and equal x/y/z units. Optional centering with a single scale factor preserves proportions. Per-axis normalization is labeled as distorting proportions. The displayed edge count discloses thinning above 4000 edges; saved metrics always use the complete graph and are never recomputed by display controls.

Choose Open circle demo in the app, or use the installed project below. Its two chord-weighted graphs use 12 equally spaced unit-circle points. Increasing k from 2 to 4 introduces shortcuts relative to exact shorter circle arcs. Layouts and metrics are already saved; no fitting is needed.

Value

When `launch = FALSE`, a `shiny.appobj`; otherwise the result of `shiny::runApp()`, invisibly.

See Also

`read.graph.benchmark()`, `register.graph.project()`

Examples

```
if (interactive() && all(vapply(c("shiny", "bslib", "plotly", "digest"),
                               requireNamespace, logical(1), quietly = TRUE))) {
  demo <- system.file("extdata", "graph-explorer-demo", package = "dgraphs")
  explore.graphs(demo)
}
```

extract.trajectory.edge.lengths

Extract Edge Lengths Along a Graph Path

Description

Extract Edge Lengths Along a Graph Path

Usage

```
extract.trajectory.edge.lengths(
  traj,
  adj.list,
  length.list,
  add.quantiles = FALSE
)
```

Arguments

<code>traj</code>	Numeric or integer vector of consecutive graph vertices.
<code>adj.list</code>	Adjacency list.
<code>length.list</code>	Edge-length list aligned with <code>adj.list</code> .
<code>add.quantiles</code>	Logical; if TRUE, add edge-length empirical quantiles.

Value

Data frame with consecutive vertex pairs and their edge lengths.

Examples

```
graph <- list(2L, c(1L, 3L), 2L)
lengths <- list(1, c(1, 2), 2)
extract.trajectory.edge.lengths(c(1, 2, 3), graph, lengths)
```

fermat.distances

*Compute Complete or Graph-Restricted Sample Fermat Distances***Description**

Minimize sums of powered edge lengths. Coordinate input defaults to the complete Euclidean graph, implementing the sample Fermat distance on the observed points. A symmetric kNN restriction or a supplied graph is an explicit alternative, with no automatic guarantee of the same distances.

Usage

```
fermat.distances(
  graph = NULL,
  p = 2,
  rooted = FALSE,
  vertices = NULL,
  stage = "final",
  points = NULL,
  graph.type = NULL,
  k = NULL,
  backend = "explicit",
  sources = NULL,
  targets = NULL,
  max.workspace.bytes = 512 * 1024^2,
  return.graph = FALSE
)
```

Arguments

graph	A dgraph with finite nonnegative edge lengths, interpreted as base lengths before powering. Supply exactly one of graph and points.
p	Finite numeric scalar at least one; the edge-length exponent.
rooted	Logical scalar. If TRUE, return the 1/p power of the minimum sum. Defaults to FALSE; rooting does not change minimizing paths.
vertices	Optional unique 1-based vertex indices in output order. Paths may use all vertices. NULL selects all; an empty vector selects none.
stage	Stored graph stage, default "final". Coordinate input only permits "final".
points	Finite numeric matrix or data frame, observations in rows.

<code>graph.type</code>	Coordinate construction: "complete" (default) or "sknn" (union-symmetric Euclidean kNN, without pruning or repair). Cannot accompany graph.
<code>k</code>	Required for <code>graph.type = "sknn"</code> , with $1 \leq k < n$. Not accepted for complete or supplied graphs.
<code>backend</code>	Complete-graph coordinate backend: "explicit" (the default reference) or "implicit" (evaluate edges on demand without storing adjacency). Explicitly supplied only for complete coordinate input.
<code>sources</code>	Optional unique source indices for rectangular queries with <code>backend = "implicit"</code> . For pivot-to-all distances, supply the pivot ids. Cannot accompany vertices; every point remains a possible transit vertex.
<code>targets</code>	Optional unique target indices with sources; defaults to all observations. Row and column order follow sources and targets.
<code>max.workspace.bytes</code>	Positive finite workspace allowance for the implicit backend (default 512 MiB). The estimate includes coordinates, output and linear native scratch, not total R process memory or R copies.
<code>return.graph</code>	Logical scalar; return distances together with the union of selected shortest-path edges and coverage metadata. Defaults to FALSE. Complete coordinate input uses the implicit implementation for this option, even when <code>backend = "explicit"</code> is left at its default.

Details

For base lengths l_e , the unrooted result is $\min_{\pi} \sum_{e \in \pi} l_e^p$. At $p = 1$, complete-graph coordinate distances are Euclidean; restricted distances are ordinary graph distances. Restricting edges cannot decrease the result when retained weights agree. Taking $k = n - 1$ recovers the complete graph.

Groisman, Jonckheere and Sapienza define the unrooted complete-graph estimator and prove consistency after sample-size normalization under their sampling assumptions. Their Proposition 2.12 establishes a high-probability equality for a sufficiently large nearest-neighbor restriction under its stated assumptions. It does not certify arbitrary fixed k , pruned graphs, or arbitrary supplied lengths. This function applies neither sample-size normalization nor an estimated limit constant.

Both coordinate constructions evaluate all Euclidean pairs. Explicit complete graphs store quadratic adjacency. The implicit backend uses dense Dijkstra searches with linear scratch and no graph restriction: with h sources, n observations and d coordinates its worst-case time is $O(hn^2d)$. A global numeric-range check takes $O(n^2d)$ time. *Pivot-to-all output uses $O(hn)$ storage*; full all-pairs output is still quadratic. Select pivots outside this function; no automatic pivot sampling or distance approximation is performed. Distances are computed in floating-point arithmetic. Overflow, positive powered lengths underflowing to zero, and a conservative upper bound on simple-path cost exceeding the numeric range cause errors; rescale base lengths before retrying. Multiplying lengths by $a > 0$ multiplies unrooted distances by a^p (rooted distances by a).

With `return.graph = TRUE`, one deterministic shortest-path tree is selected per source (ties need not include every minimizing path). Only paths to the requested targets contribute edges. The returned graph retains all input vertices, including unused isolated vertices. Its edge lengths are powered base lengths even when the returned distances are rooted. Thus graph geodesics reproduce the unrooted requested distances. With all sources and targets it preserves every pair; a subset guarantees only the requested pairs. The union need not be sparse. The implicit workspace estimate includes a conservative allowance for the predecessor-edge union when requested.

Value

Numeric square distance matrix, or a source-by-target matrix when sources is supplied, in requested order. Unreachable pairs are Inf. Zero-length edges are retained; duplicate points have zero distance. Point row names or graph adjacency names label the matrix. With `return.graph = TRUE`, return a list containing distances (this matrix), graph (a dgraph with powered base edge lengths), and metadata. Metadata records sources, targets, coverage (`all_pairs` or `requested_pairs`), `p`, `rooted`, `edge.weight.type`, and the backend used. Graph distances are unrooted even when the returned matrix is rooted.

References

Groisman, P., Jonckheere, M. and Sapienza, F. (2022). Nonhomogeneous Euclidean first-passage percolation and distance learning. *Bernoulli*, 28(1), 255–276. doi:10.3150/21BEJ1341. See Definitions 2.1 and 2.11 and Proposition 2.12 in <https://arxiv.org/html/1810.09398v2>.

See Also

[graph.geodesic.distances\(\)](#), [create.sknn.graph\(\)](#)

Examples

```
X <- matrix(c(0, 1, 2), ncol = 1)
fermat.distances(points = X, p = 2) # 0 -> 1 -> 2 costs 2, not 4
fermat.distances(points = X, p = 2, rooted = TRUE)
fermat.distances(points = X, graph.type = "sknn", k = 1)
g <- dgraph(list(2L, c(1L, 3L), 2L), list(1, c(1, 1), 1))
fermat.distances(g, vertices = c(1, 3))
```

fermat.knn

Find Exact Sample Fermat Nearest Neighbors

Description

Find nearest neighbors in the complete-graph sample Fermat distance using Euclidean neighbor pruning and truncated Dijkstra searches.

Usage

```
fermat.knn(points, k, p = 2, rooted = FALSE, algorithm = "kd_tree")

create.fermat.sknn.graph(
  points,
  k,
  p = 2,
  rooted = FALSE,
  algorithm = "kd_tree"
)
```

Arguments

<code>points</code>	Finite numeric matrix or data frame, observations in rows.
<code>k</code>	Number of other observations to return per row; $1 \leq k < n$.
<code>p</code>	Finite edge-length exponent at least one.
<code>rooted</code>	Logical; return the $1/p$ power of path costs if TRUE.
<code>algorithm</code>	Exact Euclidean search algorithm passed to <code>FNN::get.knnx()</code> : "kd_tree" (default) or "brute".

Details

The unrooted distance is the minimum sum of Euclidean edge lengths raised to p , allowing paths through all observations. Rooting preserves neighbor rankings. Lemma 5.6 of McKenzie and Damelin justifies pruning to directed Euclidean neighbor lists for nearest-neighbor queries. This does not establish equality of all pairwise distances on the sparse graph. The paper counts the source among its neighbors; here k excludes it.

Equal-distance neighbors at the cutoff may be selected arbitrarily; their identities need not agree across search algorithms or permutations. Duplicate observations are retained as distinct vertices with zero distance. Exactness refers to the complete-graph target, subject to floating-point arithmetic. Extremely disparate coordinate scales should be rescaled. Nonfinite computed lengths and powered costs, and positive costs that underflow to zero, cause errors.

Candidate lists and output use $O(nk)$ storage. After Euclidean search, binary-heap path searches take $O(nk^2 \log(k+1))$ time with $O(n+k^2)$ scratch. Euclidean search may be quadratic in n in high dimensions. Unlike the implicit distance backend, this function does not scan every complete-graph edge for numeric-range validation.

Value

`fermat.knn()` returns a list with n -by- k matrices `index` (1-based neighbor indices) and `distance` (in nondecreasing order), excluding self. `create.fermat.sknn.graph()` returns a dgraph formed by the union of these directed selections. Its lengths are Fermat distances, not powered direct Euclidean edges. Vertex degrees can exceed k ; components are not repaired. Use `graph.geodesic.distances()` to sum stored lengths, rather than applying `fermat.distances()` with $p > 1$ and powering them again.

References

McKenzie, D. and Damelin, S. (2019). Power Weighted Shortest Paths for Clustering Euclidean Data. Section 5, Lemma 5.6 and Algorithm 2. <https://arxiv.org/abs/1905.13345>.

See Also

`fermat.distances()`, `create.sknn.graph()`

Examples

```
X <- cbind(c(0, 1, 2, 4), 0)
fermat.knn(X, k = 2, p = 2)
graph <- create.fermat.sknn.graph(X, k = 2)
graph.edges(graph)
```

geodesic.core.endpoints

Select Graph Endpoints by Core-Eccentricity Geometry

Description

Select Graph Endpoints by Core-Eccentricity Geometry

Usage

```
geodesic.core.endpoints(
  adj.list,
  length.list,
  core.quantile = 0.1,
  endpoint.quantile = 0.9,
  use.approx.eccentricity = TRUE,
  n.landmarks = 64L,
  max.endpoints = NULL,
  seed = 1L,
  verbose = FALSE
)
```

Arguments

adj.list	Graph adjacency list using 1-based vertex indices.
length.list	Edge-length list aligned with adj.list.
core.quantile	Numeric in (0, 1) defining the low-eccentricity core.
endpoint.quantile	Numeric in [0, 1] for endpoint candidate scores.
use.approx.eccentricity	Use landmark-based eccentricity approximation.
n.landmarks	Number of landmarks when approximation is used.
max.endpoints	Optional positive cap on returned endpoints.
seed	Integer seed for landmark initialization.
verbose	Print backend progress.

Value

A geodesic_core_endpoints list of endpoints and diagnostics.

Examples

```
graph <- create.graph("chain", n = 8)
endpoints <- geodesic.core.endpoints(graph.adjacency(graph), graph.lengths(graph),
  use.approx.eccentricity = FALSE)
endpoints$endpoints
```

geodesic.disk

Geodesic Disk in a Weighted Graph

Description

Geodesic Disk in a Weighted Graph

Usage

```
geodesic.disk(adj.list, length.list, center.vertex, radius = NULL, n = NULL)
```

Arguments

adj.list	Adjacency list.
length.list	Edge-length list aligned with adj.list.
center.vertex	Center vertex.
radius	Optional geodesic radius.
n	Optional target number of reachable vertices.

Value

List with vertices, effective radius, and aligned dists.

Examples

```
graph <- list(2L, c(1L, 3L), 2L)
weights <- list(1, c(1, 2), 2)
geodesic.disk(graph, weights, center.vertex = 2, radius = 2)
```

geodesic.knn

*Find Geodesic Neighbors Within a Point Cloud***Description**

Find Geodesic Neighbors Within a Point Cloud

Usage

```
geodesic.knn(
  X,
  k,
  k.graph = 5,
  graph = NULL,
  small.component = c("error", "truncate")
)
```

Arguments

<code>X</code>	Finite numeric matrix of observations, one per row.
<code>k</code>	Number of other vertices to return, an integer in $1:(\text{nrow}(X)-1)$. Self is excluded by vertex index; coincident other observations remain valid zero-distance neighbors. Ties are ordered by vertex index.
<code>k.graph</code>	Number of other neighbors used to construct the auxiliary symmetric kNN graph. Components are not automatically connected. Ignored when graph is supplied.
<code>graph</code>	Optional dgraph containing stored edge lengths, in X row order.
<code>small.component</code>	Error if fewer than k other vertices are reachable ("error", default), or return the available neighbors ("truncate").

Value

A list with `nn.index` and `nn.dist` matrices with `k` columns and `effective.k`, the number returned per row. Under explicit truncation, absent indices and distances are NA; unreachable vertices are never reported as neighbors.

See Also

[geodesic.knnx\(\)](#), [graph.geodesic.distances\(\)](#)

Examples

```
X <- cbind(0:3, 0)
geodesic.knn(X, k = 1, k.graph = 1) # one other vertex per row
```

geodesic.knnx

*Find Geodesic Neighbors from Grid Queries to Observations***Description**

Find Geodesic Neighbors from Grid Queries to Observations

Usage

```
geodesic.knnx(
  X,
  X.grid,
  k,
  k.graph = 5,
  small.component = c("error", "truncate")
)
```

Arguments

<code>X</code>	Finite numeric matrix of data observations.
<code>X.grid</code>	Finite numeric matrix of grid query points, with the same number of coordinate columns as <code>X</code> .
<code>k</code>	Number of data observations returned per grid query, in <code>1:nrow(X)</code> . Grid and data rows have distinct identities: a coincident observation is a valid zero-distance neighbor. Ties are ordered by data row index.
<code>k.graph</code>	Number of grid vertices attached to each observation, in <code>1:nrow(X.grid)</code> . Grid vertices connect to up to twice the coordinate dimension other grid vertices. No components are automatically bridged.
<code>small.component</code>	Error on insufficient reachable observations, or explicitly "truncate" and pad absent indices and distances with NA.

Value

A list with combined coordinates `V` (grid rows first), edge pairs `E` in `V` row indices, `nn.index` (indices into `X`), `nn.dist` and `effective.k` (the number returned per grid query).

See Also

[geodesic.knn\(\)](#)

Examples

```
X.grid <- as.matrix(expand.grid(x = 0:2, y = 0:2))
X <- rbind(c(0, 0), c(1.2, 0.8), c(1.8, 1.7))
geodesic.knnx(X, X.grid, k = 2)
```

get.shortest.path	<i>Get Shortest Path Between Two Vertices</i>
-------------------	---

Description

Get Shortest Path Between Two Vertices

Usage

```
get.shortest.path(path.result, from, to)
```

Arguments

path.result	A "path.graph" object.
from	Source vertex.
to	Target vertex.

Value

A list with path (vertex indices in requested direction), length and hops, or NULL when no stored route exists within this result's hop limit. A vertex queried against itself has path from, length zero and zero hops. Routes can be retrieved in either direction.

Examples

```
graph <- list(2L, c(1L, 3L), 2L)
lengths <- list(1, c(1, 2), 2)
pg <- create.path.graph(dgraph(graph, lengths), h.values = 2)[[1L]]
get.shortest.path(pg, from = 1, to = 3)
```

graph.connected.components	<i>Assign Vertices to Connected Components</i>
----------------------------	--

Description

Assign Vertices to Connected Components

Usage

```
graph.connected.components(graph, stage = "final")
```

Arguments

graph	A dgraph.
stage	Stored graph stage.

Value

Integer vector of component IDs, one per vertex.

Examples

```
graph <- dgraph(list(2L, 1L, integer()))
graph.connected.components(graph)
```

graph.embedding	<i>Embed Graph in 2D or 3D Space</i>
-----------------	--------------------------------------

Description

Embed Graph in 2D or 3D Space

Usage

```
graph.embedding(
  graph,
  edge.attribute = NULL,
  transform = c("identity", "reciprocal"),
  dim = 2,
  method = c("fr", "kk"),
  verbose = FALSE,
  stage = "final"
)
```

Arguments

graph	A dgraph object.
edge.attribute	Explicit edge quantity, such as "length" or "conductance"; NULL uses an un-weighted layout.
transform	Use selected values directly ("identity") or their reciprocals ("reciprocal"). Selected values must be strictly positive. Fruchterman-Reingold treats larger values as stronger attraction, whereas Kamada-Kawai uses them as distances.
dim	Embedding dimension, either 2 or 3.
method	Layout method, "fr" or "kk".
verbose	Logical; print timing messages.
stage	Stored graph stage used for both topology and edge attributes.

Value

Numeric layout matrix with one row per embedded vertex.

Examples

```
set.seed(1)
graph <- create.graph("cycle", 6)
graph.embedding(graph, dim = 2, method = "fr")
```

graph.geodesic.distances

Compute Graph Geodesic Distances

Description

Compute exact shortest-path distances on a supplied graph, or on a graph constructed from coordinates. These graph distances may approximate a continuous geometric distance; construction alone does not make them exact manifold geodesics. Supply exactly one of graph and points.

Usage

```
graph.geodesic.distances(
  graph = NULL,
  vertices = NULL,
  stage = "final",
  distance = c("length", "hop"),
  points = NULL,
  graph.type = NULL,
  k = NULL
)
```

Arguments

graph	A dgraph. Construction arguments cannot accompany a graph.
vertices	Optional unique 1-based vertex indices, in output order. NULL selects all vertices; an empty vector returns a zero-by-zero matrix. Paths may traverse vertices outside the selected subset.
stage	Stored graph stage; defaults to "final". Coordinate input permits only "final".
distance	"length" sums stored lengths (and errors if absent). "hop" explicitly counts edges instead.
points	Finite numeric matrix or data frame, with one point per row and at least one row and column. Cannot accompany graph.
graph.type	Construction for coordinate input: "sknn" (default when omitted) or "mst". Symmetric kNN links a pair if either endpoint selects the other, without pruning or connectivity repair. MST builds a Euclidean minimum spanning tree, retaining zero-length edges for coincident points.
k	Required number of other neighbors for "sknn", with $1 \leq k < n$. Not accepted for "mst". In particular, $k = 1$ still constructs a symmetric kNN graph; it never switches to an MST.

Details

For repeated calculations or more construction options, build a graph separately and supply it via `graph`. Coordinate construction uses untransformed Euclidean distances. The exact symmetric-neighbor search evaluates all pairs; MST construction uses a dense Prim search with quadratic time and linear auxiliary storage. Selected-vertex output has $\text{length}(\text{vertices})^2$ entries; all-pairs output has n^2 entries.

Value

A numeric square matrix in the requested vertex order; unreachable pairs have infinite distance. Zero-length edges remain traversable. Row names from points, or adjacency labels from `graph`, label the matrix when present.

Examples

```
graph <- create.graph("chain", 5)
graph.geodesic.distances(graph, vertices = c(1, 5))
graph.geodesic.distances(create.graph("cycle", 5), distance = "hop")
X <- matrix(c(0, 0, 1, 10), ncol = 1)
graph.geodesic.distances(points = X, graph.type = "mst")
graph.geodesic.distances(points = X, graph.type = "sknn", k = 1)
```

graph.spectral.embedding

Embed a Connected Graph Using its Positive Laplacian Spectrum

Description

Embed a Connected Graph Using its Positive Laplacian Spectrum

Usage

```
graph.spectral.embedding(spectrum, dim = 2, scale = c("none", "inverse.sqrt"))
```

Arguments

spectrum	A <code>graph_spectrum</code> object returned by <code>graph.spectrum()</code> .
dim	Positive integer number of coordinates, no greater than the number of positive eigenpairs in <code>spectrum</code> .
scale	Coordinate scaling: "none" uses the orthonormal eigenvectors; "inverse.sqrt" divides each column by the square root of its eigenvalue.

Details

The spectrum object carries the eigenvalue ordering, zero-mode tolerance and component information, so embedding never discards a column by position in an arbitrary eigenvector matrix. Disconnected graphs are rejected: embed each component separately with `create.subgraph()` and `graph.spectrum()`. There is no implied distance between separate components. Singleton and empty graphs have no positive-dimensional spectral embedding.

Unscaled coordinates are a spectral representation, not original physical coordinates. On a connected graph, inverse-square-root scaling using all positive modes makes squared Euclidean distances equal to effective resistance; using fewer modes gives a truncated representation. Neither choice generally reproduces shortest-path or manifold geodesic distances. Signs and bases within tied eigenvalues can vary; choose whole tied eigenspaces when comparing embedding distances across backends.

Value

Numeric matrix with one row per vertex and columns Dim1, Dim2, and so on. Columns use the smallest dim positive eigenvalues.

See Also

`graph.spectrum()`, `graph.embedding()`

Examples

```
graph <- create.graph("chain", 8)
spectrum <- graph.spectrum(graph, nev = 3)
graph.spectral.embedding(spectrum, dim = 2)
graph.spectral.embedding(spectrum, dim = 3, scale = "inverse.sqrt")
```

graph.spectrum

Compute the Positive Spectrum of an Unweighted Graph Laplacian

Description

Compute the Positive Spectrum of an Unweighted Graph Laplacian

Usage

```
graph.spectrum(
  graph,
  nev = NULL,
  use.R = FALSE,
  return.Laplacian = FALSE,
  return.dense = FALSE,
  tol = NULL
)
```

Arguments

graph	A dgraph; the final-stage topology defines the combinatorial Laplacian $L = D - A$. Stored edge lengths and attributes are not used.
nev	Number of smallest positive eigenpairs, in increasing eigenvalue order. NULL requests all n - nullity positive modes; zero requests none. Explicit counts must be integers in that range; they are never truncated.
use.R	Logical; use base R's dense symmetric eigensolver instead of the native backend. Both return the same numerical contract.
return.Laplacian	Logical; include the graph Laplacian in the result.
return.dense	Logical; return a base matrix when TRUE, otherwise a sparse Matrix object. If Matrix is unavailable, warn and return dense. Ignored when return.Laplacian = FALSE.
tol	Positive absolute eigenvalue tolerance. By default, use $100 * .Machine$double.eps * \max(1, 2 * \max.degree)$. Computed zero modes must have absolute eigenvalues at most tol; returned modes must exceed it. An unresolved separation from zero is an error, not silent truncation.

Details

Every component contributes one zero mode, including isolated vertices. These modes are omitted from evalues and evectors; their number is determined from topology and checked against the computed spectrum. The native backend uses sparse Lanczos for partial spectra, requesting the component zero modes as well, and a dense eigensolver for the full spectrum. The R backend computes the full dense spectrum before selection. Thus a small explicit nev is preferable for large graphs. Dense solves require quadratic memory; requesting all positive modes is not a sparse operation.

Eigenvector signs and bases within repeated-eigenvalue subspaces are not unique. If nev or an embedding dimension cuts through a repeated eigenvalue, the selected subspace and embedding distances can differ between backends. Include the whole tied eigenspace for invariant comparisons.

Value

A graph_spectrum list with evalues (the requested positive eigenvalues in increasing order), evectors (one row per original vertex, one orthonormal column per eigenvalue), nullity (the exact number of connected components), components (component IDs in vertex order), and the resolved tolerance. When requested, laplacian contains L. An empty or edgeless graph has no positive modes and an n by zero eigenvector matrix when nev = NULL or nev = 0.

See Also

[graph.spectral.embedding\(\)](#), [graph.connected.components\(\)](#)

Examples

```
graph <- create.graph("chain", 8)
spectrum <- graph.spectrum(graph, nev = 3)
```

```
spectrum$values
spectrum$nullity # one omitted zero mode
graph.spectral.embedding(spectrum, dim = 2)
```

```
graph.summary.divergence
```

Compute divergence between two graphs using a selected graph summary

Description

Extracts one selected graph summary from two graph-like objects and computes a divergence between the resulting probability mass functions.

Currently the supported divergence is Jensen-Shannon divergence, implemented via [jensen.shannon.divergence\(\)](#).

Usage

```
graph.summary.divergence(
  graph1,
  graph2,
  summary = c("degree_distribution", "edge_weight_distribution",
    "component_size_distribution", "neighborhood_label_distribution"),
  divergence = c("js"),
  labels = NULL,
  summary.args = list(),
  support = NULL,
  return.details = TRUE
)
```

Arguments

graph1	First dgraph object.
graph2	Second dgraph object.
summary	Summary type to compare.
divergence	Divergence type. Currently only "js".
labels	Optional shared vertex-label vector used for "neighborhood_label_distribution".
summary.args	Optional named list forwarded to compute.graph.summary.pmf() .
support	Optional common support. If NULL, the union of the two PMF supports is used.
return.details	Logical; if TRUE, return a structured list.

Value

If `return.details = TRUE`, a list with fields:

- `summary`: summary type used.
- `divergence`: divergence type used.
- `value`: scalar divergence value.
- `pmf1`: aligned PMF for `g1`.
- `pmf2`: aligned PMF for `g2`.
- `support`: aligned support.
- `metadata`: summary-specific metadata for both graphs.

Otherwise, returns the scalar divergence value.

Examples

```
path <- dgraph(list(2L, c(1L, 3L), 2L))
triangle <- dgraph(list(c(2L, 3L), c(1L, 3L), c(1L, 2L)))
graph.summary.divergence(
  path,
  triangle,
  summary = "degree_distribution"
)
```

identical.vertex.set.weighted.graph.similarity

Weighted Graph Distance Between Graphs with Identical Vertex Sets

Description

Weighted Graph Distance Between Graphs with Identical Vertex Sets

Usage

```
identical.vertex.set.weighted.graph.similarity(
  adj.list1,
  length.list1,
  adj.list2,
  length.list2,
  calculate.normalized.deviation = FALSE
)
```

Arguments

adj.list1	First graph adjacency list.
length.list1	First graph edge weights.
adj.list2	Second graph adjacency list.
length.list2	Second graph edge weights.
calculate.normalized.deviation	Logical; if TRUE, normalize the L1 distance-matrix deviation.

Value

Numeric distance-matrix deviation.

Examples

```
graph <- list(2L, c(1L, 3L), 2L)
weights1 <- list(1, c(1, 1), 1)
weights2 <- list(1, c(1, 2), 2)
identical.vertex.set.weighted.graph.similarity(
  graph, weights1, graph, weights2
)
```

inspect.path.graph	<i>Inspect a Path Graph</i>
--------------------	-----------------------------

Description

Inspect a Path Graph

Usage

```
## S3 method for class 'path.graph'
print(x, ...)

## S3 method for class 'path.graph'
summary(object, ...)
```

Arguments

x, object	A single path.graph member from create.path.graph() .
...	Unused.

Value

print() invisibly returns its unchanged input after printing graph counts. summary() prints and invisibly returns a named list containing n.vertices, n.paths, avg.path.length (number of vertices per stored path, or NA if no paths), and avg.degree (mean adjacency-list length).

Examples

```
chain <- create.graph("chain", n = 5)
paths <- create.path.graph(chain, h.values = 2)[[1L]]
print(paths)
summary(paths)
```

```
inspect.path.graph.series
```

Inspect a Collection of Hop-Constrained Path Graphs

Description

Inspect a Collection of Hop-Constrained Path Graphs

Usage

```
## S3 method for class 'path.graph.series'
summary(object, ...)

## S3 method for class 'path.graph.series'
print(x, ...)
```

Arguments

...	Reserved for generic method arguments.
x, object	A collection returned by <code>create.path.graph()</code> .

Value

`summary()` returns a data frame of hop limits, vertex counts, edge counts and stored route counts. `print()` displays up to ten rows and returns the original collection invisibly. No paths are recomputed.

Examples

```
paths <- create.path.graph(create.graph("chain", 6), h.values = c(1, 2, 4))
print(paths)
summary(paths)
```

inspect.synthetic_geometry_sample

Inspect a Synthetic Geometry Sample

Description

Inspect a Synthetic Geometry Sample

Usage

```
## S3 method for class 'synthetic_geometry_sample'
print(x, ...)

## S3 method for class 'synthetic_geometry_sample'
summary(object, ...)

## S3 method for class 'summary.synthetic_geometry_sample'
print(x, ...)
```

Arguments

x, object	A sample returned by <code>sample.synthetic.geometry()</code> .
...	Reserved for generic method arguments.

Value

`print()` returns its input invisibly. `summary()` returns a `summary.synthetic_geometry_sample` with dimensions, geometry/sampling families, coordinate ranges, observed region counts and RNG mode. State vectors remain available in the sample's `$rng` without being printed.

Examples

```
x <- sample.synthetic.geometry(synthetic.circle(),
  synthetic.sampling.uniform.interval(0, 2*pi), n = 5, seed = 17)
print(x)
summary(x)
```

isometry.distance.correlations

Compute Distance Preservation Correlations

Description

Computes Pearson and Spearman correlations between estimated and true pairwise distances over the upper-triangular distance entries.

Usage

```
isometry.distance.correlations(
  D.estimated,
  D.true,
  true.tol = sqrt(.Machine$double.eps)
)
```

Arguments

<code>D.estimated</code>	Estimated distance matrix or dist object.
<code>D.true</code>	Ground-truth distance matrix or dist object.
<code>true.tol</code>	Non-negative tolerance. Pairs with true distance less than or equal to this value are excluded from relative metrics.

Value

Named numeric vector with entries `pearson_cor` and `spearman_cor`.

Examples

```
D <- as.matrix(dist(1:4))
isometry.distance.correlations(2 * D, D)
```

isometry.distortion.quantiles

Compute Multiplicative Distortion Quantiles

Description

Computes quantiles of the calibrated pairwise distortion

$$\rho_{ij} = \alpha \hat{D}_{ij} / D_{ij}.$$

Values near 1 indicate approximately isometric distance preservation.

Usage

```
isometry.distortion.quantiles(
  D.estimated,
  D.true,
  probs = c(0.05, 0.5, 0.95),
  scale = TRUE,
  true.tol = sqrt(.Machine$double.eps)
)
```

Arguments

<code>D.estimated</code>	Estimated distance matrix or dist object.
<code>D.true</code>	Ground-truth distance matrix or dist object.
<code>probs</code>	Numeric vector of probabilities passed to <code>stats::quantile()</code> .
<code>scale</code>	Logical scalar. If TRUE, use <code>isometry.scale()</code> to optimally rescale estimated distances before computing the error.
<code>true.tol</code>	Non-negative tolerance. Pairs with true distance less than or equal to this value are excluded from relative metrics.

Value

Named numeric vector of distortion quantiles.

Examples

```
D <- as.matrix(dist(1:4))
isometry.distortion.quantiles(1.1 * D, D)
```

`isometry.geodesic.diagnostics`

Compute Geodesic-Isometry Diagnostics

Description

Computes signed and scale-regime diagnostics for comparing estimated graph geodesic distances with reference geodesic distances. Distances are first optionally calibrated by the least-squares scale from `isometry.scale()`.

Usage

```
isometry.geodesic.diagnostics(
  D.estimated,
  D.true,
  scale = TRUE,
  true.tol = sqrt(.Machine$double.eps),
  band.probs = c(1/3, 2/3)
)
```

Arguments

<code>D.estimated</code>	Estimated distance matrix or dist object.
<code>D.true</code>	Ground-truth distance matrix or dist object.
<code>scale</code>	Logical scalar. If TRUE, use <code>isometry.scale()</code> to optimally rescale estimated distances before computing the error.

true.tol	Non-negative tolerance. Pairs with true distance less than or equal to this value are excluded from relative metrics.
band.probs	Numeric vector of two probabilities used to split reference distances into short, middle, and long distance bands.

Value

Named numeric vector with target-normalized graph-geodesic relative RMSE, signed residual bias, shortcut fraction, relative absolute residual quantiles, and median signed relative residuals in short/mid/long reference-distance bands. The relative-RMSE entry retains the historical name `rel_geodesic_stress`; it is not Kruskal's Stress-1.

Examples

```
D <- as.matrix(dist(1:4))
isometry.geodesic.diagnostics(1.1 * D, D)
```

isometry.rel.abs.error

Compute Relative Absolute Isometry Errors

Description

Computes quantiles of pairwise relative absolute errors

$$\left| \alpha \hat{D}_{ij} - D_{ij} \right| / D_{ij}.$$

Usage

```
isometry.rel.abs.error(
  D.estimated,
  D.true,
  probs = c(0.5, 0.95),
  scale = TRUE,
  true.tol = sqrt(.Machine$double.eps)
)
```

Arguments

D.estimated	Estimated distance matrix or dist object.
D.true	Ground-truth distance matrix or dist object.
probs	Numeric vector of probabilities passed to <code>stats::quantile()</code> .
scale	Logical scalar. If TRUE, use <code>isometry.scale()</code> to optimally rescale estimated distances before computing the error.
true.tol	Non-negative tolerance. Pairs with true distance less than or equal to this value are excluded from relative metrics.

Value

Named numeric vector of relative absolute error quantiles.

Examples

```
D <- as.matrix(dist(1:4))
isometry.rel.abs.error(1.1 * D, D)
```

isometry.rel.rms.error

Compute Relative RMS Isometry Error

Description

Computes the relative root-mean-square distance-matrix error after optional scalar calibration:

$$\left[\frac{\sum_{i < j} (\alpha \hat{D}_{ij} - D_{ij})^2}{\sum_{i < j} D_{ij}^2} \right]^{1/2}.$$

Usage

```
isometry.rel.rms.error(
  D.estimated,
  D.true,
  scale = TRUE,
  true.tol = sqrt(.Machine$double.eps)
)
```

Arguments

D.estimated	Estimated distance matrix or dist object.
D.true	Ground-truth distance matrix or dist object.
scale	Logical scalar. If TRUE, use <code>isometry.scale()</code> to optimally rescale estimated distances before computing the error.
true.tol	Non-negative tolerance. Pairs with true distance less than or equal to this value are excluded from relative metrics.

Value

Numeric scalar relative RMS error.

Examples

```
D <- as.matrix(dist(1:4))
isometry.rel.rms.error(2 * D, D)
```

isometry.scale

Compute the Optimal Isometry Calibration Scale

Description

Computes the least-squares scalar α that aligns estimated distances to true distances:

$$\alpha^* = \frac{\sum_{i < j} \hat{D}_{ij} D_{ij}}{\sum_{i < j} \hat{D}_{ij}^2}.$$

Usage

```
isometry.scale(D.estimated, D.true, true.tol = sqrt(.Machine$double.eps))
```

Arguments

D.estimated	Estimated distance matrix or dist object.
D.true	Ground-truth distance matrix or dist object.
true.tol	Non-negative tolerance. Pairs with true distance less than or equal to this value are excluded from relative metrics.

Value

Numeric scalar calibration scale.

Examples

```
D <- as.matrix(dist(1:4))
isometry.scale(2 * D, D)
```

jensen.shannon.divergence

Jensen-Shannon Divergence

Description

Jensen-Shannon Divergence

Usage

```
jensen.shannon.divergence(p, q)
```

Arguments

p Numeric probability vector.
q Numeric probability vector.

Value

Jensen-Shannon divergence using log base 2.

Examples

```
jensen.shannon.divergence(c(0.75, 0.25), c(0.5, 0.5))
```

join.graphs	<i>Join Two Adjacency-List Graphs</i>
-------------	---------------------------------------

Description

Join Two Adjacency-List Graphs

Usage

```
join.graphs(graph1, graph2, i1, i2)
```

Arguments

graph1 First dgraph.
graph2 Second dgraph.
i1 Vertex in graph1 to connect.
i2 Vertex in graph2 to connect.

Value

A dgraph with vertices i1 and i2 identified. Both inputs must have lengths or both omit them, and must share their edge-attribute names.

Examples

```
first <- dgraph(list(2L, 1L))
second <- dgraph(list(2L, 1L))
join.graphs(first, second, i1 = 2, i2 = 1)
```

minh.limit	<i>Find the Minimum Hop Limit for Path Existence</i>
------------	--

Description

Find the Minimum Hop Limit for Path Existence

Usage

```
minh.limit(path.result, from, to)
```

Arguments

path.result	A path.graph.series object.
from	Source vertex index.
to	Target vertex index.

Value

Minimum hop limit where the path exists, or NULL.

Examples

```
graph <- list(2L, c(1L, 3L), 2L)
lengths <- list(1, c(1, 2), 2)
series <- create.path.graph(dgraph(graph, lengths), h.values = 1:2)
minh.limit(series, from = 1, to = 3)
```

nerve.graph	<i>Construct the Nerve Graph of a Cover</i>
-------------	---

Description

Construct the Nerve Graph of a Cover

Usage

```
nerve.graph(covering.list, n.cores = 1)
```

Arguments

covering.list	List of integer vectors, one for each set in the cover.
n.cores	Number of parallel workers. Use 1 for serial execution.

Value

A dgraph with no lengths and overlap cardinalities stored in the overlap edge attribute.

Examples

```
cover <- list(c(1, 2, 3), c(3, 4), c(5, 6))
graph.edges(nerve.graph(cover, n.cores = 1))
```

overlap.distribution.plot	<i>Plot the distribution of overlap values</i>
---------------------------	--

Description

Plot the distribution of overlap values

Usage

```
overlap.distribution.plot(x, radius_idx = NULL)
```

Arguments

- | | |
|------------|---|
| x | A vertex_geodesic_stats object |
| radius_idx | Index of the radius to display. If NULL, uses the radius with the most composite geodesics. |

Value

Invisibly returns NULL

path.dist	<i>Normalized Cumulative Distance Along a Vertex Path</i>
-----------	---

Description

Normalized Cumulative Distance Along a Vertex Path

Usage

```
path.dist(s, V)
```

Arguments

- | | |
|---|---|
| s | Nonempty numeric vector of integer vertex indices in 1:nrow(V). Repeated indices are allowed and the supplied order defines the path. |
| V | Finite numeric vertex coordinate matrix with at least one row and one column. |

Value

Numeric vector of length length(s). For a positive-length path, cumulative Euclidean distances start at zero and end at one. A singleton or zero-length path returns all zeros. Empty paths and total lengths exceeding the finite numeric range are rejected.

See Also

[path.length\(\)](#), [subdivide.path\(\)](#)

Examples

```
vertices <- rbind(c(0, 0), c(1, 0), c(1, 2))
path.dist(1:3, vertices)
path.dist(2, vertices) # a singleton has normalized distance zero
```

path.length	<i>Compute Euclidean Path Length</i>
-------------	--------------------------------------

Description

Compute Euclidean Path Length

Usage

```
path.length(X)
```

Arguments

X	Finite numeric matrix whose rows are consecutive path points, with at least one row and one column.
---	---

Value

Total Euclidean length of the polyline. Singleton paths and paths whose points all coincide have length zero. Empty paths and total lengths exceeding the finite numeric range are rejected.

See Also

[path.dist\(\)](#), [subdivide.path\(\)](#)

Examples

```
path.length(rbind(c(0, 0), c(1, 0), c(1, 2)))
path.length(matrix(c(1, 2), nrow = 1)) # zero
```

plot.build_iknn_graphs_and_selectk

Plot method for build_iknn_graphs_and_selectk

Description

Plot method for build_iknn_graphs_and_selectk

Usage

```
## S3 method for class 'build_iknn_graphs_and_selectk'
plot(
  x,
  which = c("connect", "edit", "mixing"),
  connect.args = list(),
  edit.args = list(),
  mixing.args = list(),
  par.args = list(),
  ...
)
```

Arguments

x	Object from build.iknn.graphs.and.selectk().
which	Character vector selecting panels among "connect", "edit", and "mixing".
connect.args, edit.args, mixing.args	Named lists forwarded to panel plots.
par.args	Named list forwarded to <code>graphics::par()</code> .
...	Additional arguments, currently ignored.

Value

Invisibly returns x, unchanged, after producing the requested panels. If which is empty, invisibly returns NULL without plotting.

Examples

```
set.seed(1)
X <- matrix(rnorm(60), ncol = 2)
selected <- build.iknn.graphs.and.selectk(X, k.values = seq.int(2, 4),
  method = "edit",
  verbose = FALSE)
plot(selected, which = "connect")
```

```
plot.cst_graph_mixing_stats
```

Plot method for cst_graph_mixing_stats

Description

Plot method for cst_graph_mixing_stats

Usage

```
## S3 method for class 'cst_graph_mixing_stats'
plot(
  x,
  which = c("null.homophily", "null.assortativity", "mixing.matrix", "conductance"),
  ...
)
```

Arguments

x	Object from cst.graph.mixing.stats().
which	Character vector specifying panels to plot.
...	Base graphics arguments.

Value

Invisibly returns NULL after producing the requested diagnostic panels.

Examples

```
mixing <- structure(list(mixing.matrix = matrix(c(4, 1, 1, 4), 2,
  dimnames = list(c("A", "B"), c("A", "B")))),
  class = "cst_graph_mixing_stats")
plot(mixing, which = "mixing.matrix")
```

```
plot.dgraph
```

Plot a dgraph with Reusable Coordinates

Description

Draw each undirected edge once and color vertices by values or explicit colors. Coordinates are computed by [graph.embedding\(\)](#) only when absent. Layout computation remains available separately in two or three dimensions.

Usage

```
## S3 method for class 'dgraph'
plot(
  x,
  coordinates = NULL,
  vertex.values = NULL,
  vertex.colors = NULL,
  vertex.size = 1,
  edge.alpha = 0.2,
  color.palette = NULL,
  main = "",
  add.legend = TRUE,
  stage = "final",
  method = c("fr", "kk"),
  edge.attribute = NULL,
  transform = c("identity", "reciprocal"),
  projection = NULL,
  ...
)
```

Arguments

x	A dgraph.
coordinates	Optional finite numeric matrix with one row per vertex and two or three columns. Row order must match graph vertex order.
vertex.values	Optional finite numeric value per vertex, mapped through <code>color.palette</code> . Constant values use the palette midpoint and one legend key.
vertex.colors	Optional explicit color or vector of colors, one per vertex. Cannot accompany <code>vertex.values</code> . Defaults to "steelblue".
vertex.size	Nonnegative point size, one value or one per vertex.
edge.alpha	Edge opacity between zero and one.
color.palette	Color vector for numeric values; defaults to a blue-white-red palette. Requires <code>vertex.values</code> when explicitly supplied.
main	Plot title.
add.legend	Logical; show value/color keys for numeric <code>vertex.values</code> . Explicit colors have no automatically inferred numeric legend.
stage	Stored graph stage, used for both layout and drawn edges.
method	Layout method, "fr" or "kk", when coordinates are absent.
edge.attribute, transform	Explicit layout edge quantity and transform; see graph.embedding() . Layout arguments cannot accompany coordinates.
projection	For three-column coordinates, two distinct column indices to display, for example <code>c(1, 3)</code> . Three-dimensional input requires explicit projection; it is never silently flattened. Not used for two-column input.

... Named arguments to `graphics::plot.default()`, such as `xlim`, `ylim`, `axes`, `xlab`, `ylab`, or `asp`. The arguments `x`, `y` and `type` are controlled by this method and cannot be overridden.

Value

Invisibly returns the two-column coordinates actually drawn. These can be supplied to subsequent calls to reuse the layout. Graphics settings are restored after plotting.

Examples

```
graph <- create.graph("cycle", n = 6)
xy <- plot(graph, vertex.values = 1:6)
plot(graph, coordinates = xy, vertex.values = rep(1, 6))
xyz <- graph.embedding(graph, dim = 3)
plot(graph, coordinates = xyz, projection = c(1, 3), vertex.colors = "navy")
```

plot.geodesic_stats *Plot Geodesic Statistics*

Description

Creates visualizations of geodesic statistics to help understand the relationship between radius and number of geodesics.

Usage

```
## S3 method for class 'geodesic_stats'
plot(
  x,
  plot.type = c("summary", "heatmap", "vertex", "all"),
  selected.vertices = NULL,
  max.vertices = 10,
  ...
)
```

Arguments

<code>x</code>	List. Output from <code>compute.geodesic.stats()</code> .
<code>plot.type</code>	Character. Type of plot to generate: "summary" (default), "heatmap", "vertex", or "all".
<code>selected.vertices</code>	Integer vector. Specific vertices to highlight in "vertex" plots. If NULL, a random sample will be used.
<code>max.vertices</code>	Integer. Maximum number of vertices to show in vertex plot.
...	Additional arguments passed to summary

Value

Invisibly returns NULL.

Examples

```
stats <- list(
  radii = c(0.2, 0.4),
  geodesic_rays = matrix(c(2, 3, 3, 4), nrow = 2, byrow = TRUE),
  composite_geodesics = matrix(c(1, 1, 1, 2), nrow = 2, byrow = TRUE),
  grid_vertices = c(5L, 9L),
  summary = data.frame(
    radius = c(0.2, 0.4),
    avg_rays = c(2.5, 3.5),
    max_rays = c(3, 4),
    composite_ratio = c(0.4, 0.5),
    avg_overlap_median = c(0.35, 0.45)
  )
)
class(stats) <- c("geodesic_stats", "list")

plot(stats, plot.type = "summary")
plot(stats, plot.type = "vertex", selected.vertices = 5)
```

plot.iknn_stability_metrics

Plot Method for IkNN Stability Metrics

Description

Plot Method for IkNN Stability Metrics

Usage

```
## S3 method for class 'iknn_stability_metrics'
plot(x, ...)
```

Arguments

x	An object returned by compute.stability.metrics().
...	Passed to plot.IkNNgraphs().

Value

Invisibly returns TRUE after producing the stability diagnostic plot.

Examples

```
set.seed(1)
X <- matrix(rnorm(60), ncol = 2)
graphs <- create.iknn.graphs(X, k.values = seq.int(2, 4), compute.full = TRUE,
  verbose = FALSE)
stability <- compute.stability.metrics(graphs)
plot(stability, with.pwlm = FALSE)
```

plot.IkNNgraphs	<i>Plot Diagnostics for Intersection k-NN Graph Analysis</i>
-----------------	--

Description

Plot Diagnostics for Intersection k-NN Graph Analysis

Usage

```
## S3 method for class 'IkNNgraphs'
plot(
  x,
  type = "diag",
  diags = c("edist", "edge", "deg"),
  with.pwlm = TRUE,
  with.lmin = FALSE,
  breakpoint.col = "blue",
  lmin.col = "gray",
  mar = c(2.5, 2.5, 0.5, 0.5),
  mgp = c(2.5, 0.5, 0),
  tcl = -0.3,
  xline = 2.4,
  yline = 3.15,
  ...
)
```

Arguments

<code>x</code>	A list with <code>k.values</code> , <code>edit.distances</code> , <code>n.edges.in.pruned.graph</code> , and <code>js.div</code> .
<code>type</code>	Character string. Only "diag" is currently supported.
<code>diags</code>	Diagnostic panels. The supported combination is <code>c("edist", "edge", "deg")</code> .
<code>with.pwlm</code>	Logical. If TRUE, overlays smoothed trend fits.
<code>with.lmin</code>	Logical. If TRUE, shows local-minimum vertical lines.
<code>breakpoint.col</code>	Color for breakpoint vertical lines.
<code>lmin.col</code>	Color for local-minima vertical lines.
<code>mar, mgp, tcl, xline, yline</code>	Base graphics controls.
<code>...</code>	Additional arguments passed to plot.

Value

Invisibly returns TRUE.

Examples

```
diagnostics <- structure(list(k.values = 2:4, edit.distances = c(0.3, 0.2),
  n.edges.in.pruned.graph = c(6, 8, 10), js.div = c(0.1, 0.05)),
  class = "IkNNgraphs")
plot(diagnostics, with.pwlm = FALSE)
```

plot.vertex_geodesic_stats

Plot method for vertex_geodesic_stats objects

Description

Plot method for vertex_geodesic_stats objects

Usage

```
## S3 method for class 'vertex_geodesic_stats'
plot(x, ...)
```

Arguments

x	A vertex_geodesic_stats object
...	Additional arguments passed to plot

Value

Invisibly returns NULL

Examples

```
x <- data.frame(
  radius = c(0.2, 0.4, 0.6),
  rays = c(3, 5, 6),
  composite_geodesics = c(1, 2, 3),
  overlap_min = c(0.10, 0.15, 0.20),
  overlap_p05 = c(0.15, 0.20, 0.25),
  overlap_p25 = c(0.20, 0.25, 0.30),
  overlap_median = c(0.30, 0.40, 0.50),
  overlap_p75 = c(0.40, 0.50, 0.60),
  overlap_p95 = c(0.55, 0.65, 0.75),
  overlap_max = c(0.60, 0.70, 0.80),
  potential_pairs = c(3, 10, 15),
  composite_ratio = c(1/3, 0.2, 0.2),
  overlap_ratio = c(0.30, 0.40, 0.50))
```

```
)  
class(x) <- c("vertex_geodesic_stats", "data.frame")  
attr(x, "vertex") <- 7L  
  
plot(x)
```

```
print.build_iknn_graphs_and_selectk
```

Print method for build_iknn_graphs_and_selectk

Description

Print method for build_iknn_graphs_and_selectk

Usage

```
## S3 method for class 'build_iknn_graphs_and_selectk'  
print(x, ...)
```

Arguments

x	Object from build.iknn.graphs.and.selectk().
...	Unused.

Value

Invisibly returns x, unchanged, after printing its selected neighborhood sizes and trimming status.

Examples

```
set.seed(1)  
X <- matrix(rnorm(60), ncol = 2)  
selected <- build.iknn.graphs.and.selectk(X, k.values = seq.int(2, 4),  
  method = "edit",  
  verbose = FALSE)  
print(selected)
```

print.dgraph	<i>Print an Undirected Graph</i>
--------------	----------------------------------

Description

Print an Undirected Graph

Usage

```
## S3 method for class 'dgraph'  
print(x, ...)
```

Arguments

x	A dgraph.
...	Unused.

Value

The unchanged graph, invisibly.

Examples

```
print(create.graph("empty", 3))
```

print.geodesic_stats	<i>Print method for geodesic_stats objects</i>
----------------------	--

Description

Prints a brief overview of the geodesic statistics.

Usage

```
## S3 method for class 'geodesic_stats'  
print(x, ...)
```

Arguments

x	A geodesic_stats object from compute.geodesic.stats().
...	Additional arguments passed to print.

Value

The object invisibly.

Examples

```
graph <- create.graph("circle", n = 8, sampling = "uniform")
stats <- compute.geodesic.stats(graph.adjacency(graph), graph.lengths(graph), min.radius = 0.3,
  max.radius = 0.5, n.steps = 2, n.packing.vertices = 4)
print(stats)
```

```
print.graph.constructors
```

Print Graph Constructor Results

Description

Print Graph Constructor Results

Usage

```
## S3 method for class 'radius_graph'
print(x, ...)

## S3 method for class 'cknn_graph'
print(x, ...)

## S3 method for class 'rknn_graphs'
print(x, ...)

## S3 method for class 'adaptive_radius_graph'
print(x, ...)

## S3 method for class 'sknn_graphs'
print(x, ...)

## S3 method for class 'sknn_graph'
print(x, ...)
```

Arguments

x	A graph or graph-sequence object returned by the corresponding constructor.
...	Unused.

Value

The input object x, invisibly and unchanged. Prints vertex and edge counts, construction parameters, and connectivity information when present; for a sequence, prints the graph count and neighborhood sizes.

Examples

```
X <- cbind(seq_len(8), sin(seq_len(8)))
print(create.rknn.graph(X, type = "fixed", radius = 2))
print(create.cknn.graph(X, k.scale = 2))
print(create.rknn.graph(X, type = "adaptive.radius", k.scale = 2))
print(create.rknn.graphs(X, k.values = seq.int(2, 3)))
print(create.sknn.graph(X, k = 2))
```

```
print.knn.outliers      Print Method for knn.outliers Objects
```

Description

Prints a summary of the outlier detection results from `remove.knn.outliers`.

Usage

```
## S3 method for class 'knn.outliers'
print(x, ...)
```

Arguments

`x` An object of class "knn.outliers" as returned by `remove.knn.outliers`.
`...` Additional arguments passed to print methods.

Value

Invisibly returns the input object.

Examples

```
knn.res <- list(
  S.q = matrix(c(0, 0,
                1, 1,
                2, 2), ncol = 2, byrow = TRUE),
  y.q = c(1.0, 1.5, 2.0),
  nn.d = matrix(c(0.2, 0.4,
                 0.3, 0.5,
                 1.4, 1.8,
                 0.25, 0.45),
               ncol = 2, byrow = TRUE),
  d.thld = 1,
  idx = c(TRUE, TRUE, FALSE, TRUE),
  n.outliers = 1L,
  method = "qf"
)
class(knn.res) <- "knn.outliers"

knn.res
```

print.maximal_packing *Print Method for Maximal Packing Results*

Description

Print Method for Maximal Packing Results

Usage

```
## S3 method for class 'maximal_packing'
print(x, ...)
```

Arguments

x	An object of class "maximal_packing"
...	Additional arguments (currently ignored)

Value

Invisible copy of x

Examples

```
x <- list(
  graph = create.graph("chain", 4),
  graph_diameter = 3,
  max_packing_radius = 1.5,
  grid_vertices = c(1L, 4L)
)
class(x) <- "maximal_packing"

x
```

print.mknn_graph *Print Method for mknn_graph Objects*

Description

Prints a concise summary of a mutual k-nearest neighbor graph object.

Usage

```
## S3 method for class 'mknn_graph'
print(x, ...)
```

Arguments

x An object of class "mknn_graph".

... Additional arguments (currently unused).

Value

Invisibly returns the input object.

Examples

```
graph <- create.mknn.graph(matrix(c(0, 1, 3, 6), ncol = 1), k = 2)
print(graph)
```

print.mknn_graphs *Print Method for mknn_graphs Objects*

Description

Prints a concise summary of a collection of mutual k-nearest neighbor graphs.

Usage

```
## S3 method for class 'mknn_graphs'
print(x, ...)
```

Arguments

x An object of class "mknn_graphs".

... Additional arguments (currently unused).

Value

Invisibly returns the input object.

Examples

```
graphs <- create.mknn.graphs(matrix(c(0, 1, 3, 6, 9), ncol = 1),
                                k.values = 1:3, verbose = FALSE)
print(graphs)
```

`print.mst_completion_graph`*Print Method for MST Completion Graph Objects*

Description

Displays a concise summary of an MST completion graph object, including basic graph statistics and parameter information.

Usage

```
## S3 method for class 'mst_completion_graph'  
print(x, ...)
```

Arguments

<code>x</code>	An object of class <code>mst_completion_graph</code> , as returned by create.cmst.graph .
<code>...</code>	Additional arguments (currently ignored).

Details

This method provides a human-readable overview of the graph structure without displaying the full adjacency lists. For detailed inspection of graph components, use graph accessors with the desired stage. [summary](#) method.

Value

Invisibly returns the input object `x`.

See Also

[summary.mst_completion_graph](#) for more detailed summaries, [create.cmst.graph](#) for creating MST completion graphs

Examples

```
X <- rbind(c(0, 0), c(1, 0), c(0, 1), c(2, 2))  
graph <- create.cmst.graph(X, verbose = FALSE)  
print(graph)  
summary(graph)
```

```
print.packing_validation
```

Print Method for Packing Validation Results

Description

Print Method for Packing Validation Results

Usage

```
## S3 method for class 'packing_validation'  
print(x, ...)
```

Arguments

x	An object of class "packing_validation"
...	Additional arguments (currently ignored)

Value

Invisible copy of x

Examples

```
x <- list(  
  valid = TRUE,  
  is.maximal = TRUE,  
  min.packing.distance = 2,  
  max.coverage.distance = 1,  
  violations = NULL,  
  potential.additions = NULL  
)  
class(x) <- "packing_validation"  
  
x
```

```
print.path.graph.plm
```

Print a Path-Length-Metric Graph

Description

Print a Path-Length-Metric Graph

Usage

```
## S3 method for class 'path.graph.plm'  
print(x, ...)
```



```

        0.25, 0.45),
        ncol = 2, byrow = TRUE),
  d.thld = 1,
  idx = c(TRUE, TRUE, FALSE, TRUE),
  n.outliers = 1L,
  method = "qf"
)
class(knn.res) <- "knn.outliers"

summary(knn.res)

```

```
print.summary.mst_completion_graph
```

Print Summary of MST Completion Graph

Description

Formats and displays the summary information for an MST completion graph in a readable format.

Usage

```
## S3 method for class 'summary.mst_completion_graph'
print(x, digits = 3L, ...)
```

Arguments

<code>x</code>	An object of class <code>summary.mst_completion_graph</code> , as returned by summary.mst_completion_graph .
<code>digits</code>	Integer; number of significant digits for numeric output. Default is 3.
<code>...</code>	Additional arguments (currently ignored).

Value

Invisibly returns the input summary object.

Examples

```

X <- rbind(c(0, 0), c(1, 0), c(0, 1), c(2, 2))
graph <- create.cmst.graph(X, verbose = FALSE)
print(graph)
summary(graph)

```

quadform.gradient	<i>Evaluate gradients of all quadforms</i>
-------------------	--

Description

Evaluate gradients of all quadforms

Usage

```
quadform.gradient(geometry, latent)
```

Arguments

geometry	A synthetic_quadform_geometry.
latent	Finite latent coordinates in rows.

Value

For one form, an n by d matrix. For multiple forms, an n by r by d array. With no forms, an n by zero by d array.

Examples

```
geometry <- synthetic_quadform(1L, 2L, forms = list(matrix(1)))
quadform.gradient(geometry, matrix(c(-1, 0, 1), ncol = 1))
```

quadform.metric	<i>Evaluate the induced metric of a quadform geometry</i>
-----------------	---

Description

Evaluate the induced metric of a quadform geometry

Usage

```
quadform.metric(geometry, latent)
```

Arguments

geometry	A synthetic_quadform_geometry.
latent	Finite latent coordinates in rows.

Value

For one row, a d by d matrix; otherwise an n by d by d array.

Examples

```
geometry <- synthetic.quadform(1L, 2L, forms = list(matrix(1)))  
quadform.metric(geometry, matrix(c(0, 1), ncol = 1))
```

read.graph.benchmark	<i>Read a Saved Graph Reconstruction Benchmark</i>
----------------------	--

Description

Read the existing dggraphui benchmark manifest and asset tables without launching Shiny or changing any files. Asset paths relative to the run directory are resolved against that directory; absolute paths are retained.

Usage

```
read.graph.benchmark(project)
```

Arguments

project	Benchmark directory, quadform benchmark manifest file, or registered project name.
---------	--

Value

A list containing the manifest, dataset and graph indexes, saved layout index, metrics, diagnostics, and table summaries. This validates required index files; it does not guarantee that every referenced asset exists or that the scientific results are correct. Assets are loaded on demand by the explorer, which reports missing files.

See Also

[explore.graphs\(\)](#), [register.graph.project\(\)](#)

Examples

```
## Not run:  
run <- read.graph.benchmark("path/to/benchmark/run")  
run$summary  
head(run$metrics)  
  
## End(Not run)
```

```
register.graph.project
```

Remember a Graph Explorer Project

Description

Register an existing benchmark directory for the explorer's project picker. Only its name and location are saved. Scientific assets stay in place.

Usage

```
register.graph.project(project, name, overwrite = FALSE)
```

Arguments

project	Benchmark directory or quadform benchmark manifest file.
name	A nonempty, unique display name; it can also be passed as project to explore.graphs() or read.graph.benchmark() .
overwrite	Allow an existing name to point to a different directory.

Value

The updated project catalog, invisibly, with name and path columns. Set `options(dgraphs.projects_dir = ...)` to change its location.

See Also

[explore.graphs\(\)](#), [read.graph.benchmark\(\)](#)

Examples

```
## Not run:
register.graph.project("path/to/benchmark/run", name = "My graph study")
explore.graphs(project = "My graph study")

## End(Not run)
```

remove.knn.outliers	<i>Remove Outliers from a State Space Using k-Nearest Neighbors</i>
---------------------	---

Description

Identifies and removes outliers from a multivariate state space based on k-nearest neighbor distances. This function implements several strategies for outlier detection, all based on the principle that outliers tend to be isolated from the main data clusters and thus have larger distances to their nearest neighbors.

Usage

```
remove.knn.outliers(
  S,
  y = NULL,
  p = 0.98,
  dist.factor = 100,
  k = 30,
  method = "diff.dist.factor"
)
```

Arguments

S	A numeric matrix or data frame representing the state space, where each row is an observation and each column is a dimension or feature. Must contain at least k+1 observations.
y	An optional numeric vector containing values of a variable defined over the state space. If provided, must have length equal to nrow(S). The function will filter this vector to match the filtered state space.
p	A numeric value between 0 and 1 (exclusive) indicating the percentile threshold for outlier removal. The default value of 0.98 removes points whose distance to the nearest neighbor exceeds the 98th percentile of all nearest neighbor distances.
dist.factor	A positive numeric value used as a threshold factor in certain outlier detection methods. In "diff.dist.factor", points with relative jumps greater than this factor are considered outliers. Default is 100.
k	A positive integer specifying the number of nearest neighbors to compute for each point. Must be less than the number of observations in S. Default is 30.
method	A character string specifying the outlier detection method to use when k > 1. Must be one of "dist.factor", "diff.dist.factor" (default), or "default" for the unnamed method.

Details

The function determines outliers by analyzing the distances between points and their k nearest neighbors. Several detection methods are available:

When $k = 1$: Points are flagged as outliers if their distance to the nearest neighbor exceeds the p -th percentile threshold of all nearest neighbor distances.

"dist.factor": Points are considered outliers if the ratio of the k -th nearest neighbor distance to the 1st nearest neighbor distance exceeds `dist.factor`.

"diff.dist.factor" (default): For each point, finds the maximum jump in distance between consecutive neighbors, normalizes by the median jump across all points, and flags points as outliers if their relative jump exceeds `dist.factor`. This method is particularly robust as it adapts to the overall distribution of distances.

Default unnamed method: Iteratively checks if the first nearest neighbor distance exceeds the threshold or if any consecutive difference between neighbor distances exceeds the threshold.

Value

A list of class "knn.outliers" containing the following components:

S.q The filtered state space matrix with outliers removed.

y.q The filtered dependent variable (if `y` was provided), otherwise `NULL`.

nn.d A matrix of dimensions `nrow(S)` x `k` containing distances to the k nearest neighbors for each point.

d.thld The distance threshold used for outlier detection.

idx A logical vector indicating which points were kept (`TRUE`) and which were identified as outliers (`FALSE`).

n.outliers The number of outliers detected.

method The outlier detection method used.

See Also

[get.knn](#) for the k -nearest neighbor calculation, [quantile](#) for percentile calculations

Examples

```
# Create a sample dataset with outliers
set.seed(123)
n_normal <- 120
n_outliers <- 6

# Generate normal data
normal_data <- matrix(rnorm(n_normal * 2), ncol = 2)

# Generate outliers far from the main cluster
outliers <- cbind(rnorm(n_outliers, mean = 10, sd = 0.5),
                  rnorm(n_outliers, mean = 10, sd = 0.5))

# Combine data
S <- rbind(normal_data, outliers)
y <- c(rnorm(n_normal), rnorm(n_outliers, mean = 5))

# Remove outliers using the default method
```

```

result <- remove.knn.outliers(S, y, k = 10)

# Print summary
cat("Number of outliers detected:", result$n.outliers, "\n")
cat("Percentage of data retained:",
    round(100 * nrow(result$S.q) / nrow(S), 2), "%\n")

# Use a different method with more conservative threshold
result2 <- remove.knn.outliers(S, y, p = 0.95, method = "dist.factor", dist.factor = 5, k = 10)

# Plot the original and filtered state space
oldpar <- par(mfrow = c(1, 2))
plot(S, col = "gray", main = "Original State Space",
     xlab = "Dimension 1", ylab = "Dimension 2")
points(S[!result$idx, ], col = "red", pch = 16, cex = 1.2)

plot(result$S.q, col = "blue", pch = 16,
     main = "Filtered State Space",
     xlab = "Dimension 1", ylab = "Dimension 2")
legend("topright", legend = c("Retained", "Removed"),
     col = c("blue", "red"), pch = 16)
par(oldpar)

```

rm.self.loops

Remove Self-Loops from an Adjacency List

Description

Remove Self-Loops from an Adjacency List

Usage

```
rm.self.loops(adj.list)
```

Arguments

adj.list Adjacency list.

Value

The adjacency list with entries equal to their vertex index removed.

Examples

```
rm.self.loops(list(c(1L, 2L), c(1L, 2L)))
```

```
sample.synthetic.geometry
```

Realize points on a synthetic geometry with explicit random-state control

Description

Coordinates and sampling algorithms retain the existing version-1 draw order. With a seed or explicit state list, the caller's RNG kinds and seed presence/value are restored on success and errors. The opt-in current-stream mode instead advances the caller's stream. No statistical response or dataset identity is created.

Usage

```
sample.synthetic.geometry(
  geometry,
  sampling,
  n = NULL,
  seed = NULL,
  rng.plan = NULL
)
```

Arguments

geometry	A supported geometry component.
sampling	A supported sampling component. Legacy G4 is excluded.
n	Positive sample size, or NULL for fixed-size sampling.
seed	Nonnegative integer seed for standalone L'Ecuyer-CMRG sampling. Supply exactly one of seed and rng.plan.
rng.plan	Optional list with exactly version = 1L, order equal to "sampling.frame" or "frame.sampling", and sampling and frame RNG states. States are complete integer .Random.seed vectors for L'Ecuyer-CMRG or Mersenne-Twister with Inversion/Rejection. frame is NULL unless a random frame is requested. State headers retain R's binomial generator field when supported by the running R version; a newer state cannot be replayed on an R version that does not support it. Retry/substream selection belongs to the caller. The standalone seed assigns sampling its initial stream and the random frame the next independent stream. Alternatively, "current" consumes the current R stream directly, sampling before any random frame. This mode never resets RNG kinds or seed and supports the caller's selected generators, including Box-Muller's hidden cached normal value. Draws advance the stream even if a subsequent operation fails. Call set.seed() yourself when reproducibility from a known starting point is needed.

Value

A `synthetic_geometry_sample` list containing `predictors`, `latent`, `latent.mask`, `region`, `frame.matrix`, the `specifications`, `dimensions`, `intrinsic.dim.by.region` and `codimension.by.region` for simplex strata, `declared.regions`, `observed.regions`, `n`, and `sample` (the original sampler payload). `rng` contains the effective plan, states after each draw, and `final.state` for explicit continuation by a caller. In current-stream mode the plan is "current"; returned state vectors are observations, not complete replay tokens for generators with hidden state. A deterministic draw can leave these vectors NULL if no seed exists. The result has no truth or response fields.

Examples

```
x <- sample.synthetic.geometry(synthetic.circle(),
  synthetic.sampling.uniform.interval(0, 2 * pi), n = 8, seed = 7)
dim(x$predictors)
```

subdivide.path	<i>Subdivide a Path into Arc-Length Spaced Points</i>
----------------	---

Description

Subdivide a Path into Arc-Length Spaced Points

Usage

```
subdivide.path(path, n.subdivision.pts)
```

Arguments

<code>path</code>	Finite numeric matrix of consecutive path points, with at least one row and one column. Repeated consecutive points are allowed.
<code>n.subdivision.pts</code>	Integer number of output points, at least two.

Details

Points are interpolated at equally spaced cumulative Euclidean distances along the input polyline. Zero-length segments are skipped. Equal spacing along the polyline does not imply equal straight-line distances between output points that straddle a corner, and an interior vertex need not appear in the output. Distances are evaluated in floating-point arithmetic; paths whose total length exceeds the finite numeric range are rejected.

Value

Numeric matrix with `n.subdivision.pts` rows and `ncol(path)` columns, preserving coordinate column names. The first and last rows are the path endpoints. A singleton or zero-length path repeats its location in every output row. Empty paths are rejected.

See Also

`path.length()`, `path.dist()`

Examples

```
path <- rbind(c(0, 0), c(1, 0), c(1, 2))
subdivide.path(path, n.subdivision.pts = 5)
# Arc distances 0, 0.75, 1.5, 2.25, 3 give:
# (0, 0), (0.75, 0), (1, 0.5), (1, 1.25), (1, 2).
subdivide.path(matrix(c(1, 2), nrow = 1), n.subdivision.pts = 3)
```

```
summarize.isometry.deviation
```

Summarize Deviation from Isometry

Description

Computes the standard benchmark summary used to compare graph geodesic distances with reference geodesic distances: optimal scalar calibration, relative RMS error, relative absolute error quantiles, multiplicative distortion quantiles, and distance correlations.

Usage

```
summarize.isometry.deviation(
  D.estimated,
  D.true,
  scale = TRUE,
  true.tol = sqrt(.Machine$double.eps)
)
```

Arguments

<code>D.estimated</code>	Estimated distance matrix or dist object.
<code>D.true</code>	Ground-truth distance matrix or dist object.
<code>scale</code>	Logical scalar. If TRUE, use <code>isometry.scale()</code> to optimally rescale estimated distances before computing the error.
<code>true.tol</code>	Non-negative tolerance. Pairs with true distance less than or equal to this value are excluded from relative metrics.

Value

A one-row data frame.

Examples

```
D <- as.matrix(dist(1:4))
summarize.isometry.deviation(1.1 * D, D)
```

summary.geodesic_stats

Summary method for geodesic_stats objects

Description

Provides a summary table of geodesic statistics with percentages and counts for different metric types.

Usage

```
## S3 method for class 'geodesic_stats'
summary(object, type = c("rays", "composite", "overlap"), ...)
```

Arguments

object	A geodesic_stats object from compute.geodesic.stats().
type	Character. Type of summary to generate: "rays" (default), "composite", or "overlap".
...	Additional arguments passed to summary.

Value

A matrix with row for each radius and columns for each unique count value. Each cell contains a string with "percent (count)" format.

Examples

```
stats <- list(
  radii = c(0.2, 0.4),
  geodesic_rays = matrix(c(2, 3, 3, 4), nrow = 2, byrow = TRUE),
  composite_geodesics = matrix(c(1, 1, 1, 2), nrow = 2, byrow = TRUE),
  path_overlap = list(
    min = matrix(c(0.1, 0.2, 0.2, 0.3), nrow = 2, byrow = TRUE),
    p05 = matrix(c(0.1, 0.2, 0.2, 0.3), nrow = 2, byrow = TRUE),
    p25 = matrix(c(0.2, 0.3, 0.3, 0.4), nrow = 2, byrow = TRUE),
    median = matrix(c(0.3, 0.4, 0.4, 0.5), nrow = 2, byrow = TRUE),
    p75 = matrix(c(0.4, 0.5, 0.5, 0.6), nrow = 2, byrow = TRUE),
    p95 = matrix(c(0.5, 0.6, 0.6, 0.7), nrow = 2, byrow = TRUE),
    max = matrix(c(0.6, 0.7, 0.7, 0.8), nrow = 2, byrow = TRUE)
  )
)
class(stats) <- c("geodesic_stats", "list")

summary(stats)
summary(stats, type = "composite")
summary(stats, type = "overlap")
```

summary.IkNN

Summarize IkNN Graph Object

Description

Prints a summary of an IkNN graph object, including the number of vertices, edges, and pruning statistics.

Usage

```
## S3 method for class 'IkNN'
summary(object, ...)
```

Arguments

object An object of class "IkNN", typically output from create.single.iknn.graph()
... Additional arguments passed to summary().

Value

Invisibly returns NULL while printing summary information to the console

Examples

```
graph <- create.single.iknn.graph(matrix(c(0, 1, 3, 6), ncol = 1),
                                     k = 1, verbose = FALSE)
summary(graph)
```

summary.iknn_graphs

Summarize an iknn_graphs Object

Description

Provides a detailed summary of an iknn_graphs object created by the create.iknn.graphs() function. The summary includes statistics for each intersection kNN graph in the sequence, displaying information about the connectivity and structure of the graphs for different k values.

Usage

```
## S3 method for class 'iknn_graphs'
summary(object, use.isize.pruned = FALSE, ...)
```

Arguments

object	An object of class 'iknn_graphs', typically the output of create.iknn.graphs().
use.isize.pruned	Logical. If TRUE, computes and displays statistics for the intersection-size pruned graphs (isize_pruned_graphs). If FALSE (default), computes statistics for the geometrically pruned graphs (geom_pruned_graphs).
...	Additional arguments passed to or from other methods (not currently used).

Details

The summary function extracts and presents key statistics about the structure of each intersection kNN graph in the iknn_graphs object. All graphs share the same number of vertices (equal to the number of rows in the input data matrix), but they differ in the number of edges due to varying k values and the pruning methods applied during graph creation.

The function displays general information about the graph sequence, including the number of vertices, the range of k values, and the pruning parameters used. It then presents a tabular summary of statistics for each individual graph, showing how the graph structure changes as k increases.

For each intersection kNN graph, the following metrics are calculated:

- Number of edges: Total number of connections in the graph
- Mean degree: Average number of connections per vertex
- Min/Max degree: Range of vertex connectivity
- Density: Proportion of potential connections that are actually present
- Sparsity: 1 - density, measuring the proportion of missing connections

Value

Invisibly returns a data frame containing statistics for each graph. The data frame has the following columns:

idx	The index of the given k value
k	The k value for the intersection kNN graph
n_ccomp	Number of connected components of the graph
edges	Number of edges in the graph
mean_degree	Average number of connections per vertex
min_degree	Minimum vertex degree (least connected vertex)
max_degree	Maximum vertex degree (most connected vertex)
sparsity	Graph sparsity, calculated as 1 - density. It measures how many (proportion) potential connections are missing.

See Also

[create.iknn.graphs](#) for creating intersection kNN graphs.

Examples

```
# Create sample data
set.seed(123)
x <- matrix(rnorm(1000), ncol = 5)

# Generate intersection kNN graphs
iknn.res <- create.iknn.graphs(x, k.values = seq.int(3, 10),
  with.isize.pruning = TRUE)

# Summarize the geometrically pruned graphs
summary(iknn.res)

# Summarize the intersection-size pruned graphs
summary(iknn.res, use.isize.pruned = TRUE)
```

```
summary.iterated_iknn_graphs
```

Summarize Iterated Intersection k-NN Graphs

Description

Summarize Iterated Intersection k-NN Graphs

Usage

```
## S3 method for class 'iterated_iknn_graphs'
summary(object, ...)
```

Arguments

object	An object from <code>create.iterated.iknn.graphs()</code> .
...	Unused.

Value

A data frame with one row per iteration and neighborhood size, reporting vertex, edge and connected-component counts and mean, minimum and maximum degree. This is the object's stored summary component.

Examples

```
set.seed(1)
X <- matrix(rnorm(30), ncol = 2)
out <- create.iterated.iknn.graphs(X, k.values = seq.int(2, 3), n.iterations = 1,
  verbose = FALSE)
summary(out)
```

summary.knn.outliers *Summary Method for knn.outliers Objects*

Description

Provides a detailed summary of the outlier detection results from `remove.knn.outliers`.

Usage

```
## S3 method for class 'knn.outliers'
summary(object, ...)
```

Arguments

<code>object</code>	An object of class "knn.outliers" as returned by <code>remove.knn.outliers</code> .
<code>...</code>	Additional arguments (currently unused).

Value

A list of class "summary.knn.outliers" containing summary statistics.

Examples

```
knn.res <- list(
  S.q = matrix(c(0, 0,
                1, 1,
                2, 2), ncol = 2, byrow = TRUE),
  y.q = c(1.0, 1.5, 2.0),
  nn.d = matrix(c(0.2, 0.4,
                 0.3, 0.5,
                 1.4, 1.8,
                 0.25, 0.45),
               ncol = 2, byrow = TRUE),
  d.thld = 1,
  idx = c(TRUE, TRUE, FALSE, TRUE),
  n.outliers = 1L,
  method = "qf"
)
class(knn.res) <- "knn.outliers"

summary(knn.res)
```

summary.local_extrema *Summarize Local Extrema*

Description

Summarize Local Extrema

Usage

```
## S3 method for class 'local_extrema'
summary(object, ...)

## S3 method for class 'summary.local_extrema'
print(x, ...)
```

Arguments

object	A local_extrema object from detect.local_extrema() .
...	Unused.
x	A summary.local_extrema object returned by summary().

Value

summary() returns a list of class summary.local_extrema with n_extrema, extrema_type, summaries of function values, neighborhood sizes and radii, and the data frame extrema_details (labels, vertex indices, values, radii and neighborhood sizes). With no extrema, numerical summaries are NA and the data frame is empty; the type is NA for legacy empty objects without detection-type metadata. print() prints this summary and invisibly returns x unchanged.

Examples

```
chain <- create_graph("chain", n = 5)
extrema <- detect.local_extrema(graph_adjacency(chain), graph_lengths(chain), y = c(1, 3, 1, 2,
  0), max_radius = 1, min_neighborhood_size = 2)
summary(extrema)
print(summary(extrema))
```

summary.mknngraphs *Summary Method for mknngraphs Objects*

Description

Provides a comprehensive summary of mutual k-nearest neighbor graphs created by create.mknngraphs, including structural statistics and connectivity information for each k value.

Usage

```
## S3 method for class 'mknn_graphs'
summary(object, ...)
```

Arguments

object An object of class "mknn_graphs", typically output from `create.mknn.graphs`.

... Additional arguments (currently unused).

Details

The summary provides insights into how graph structure changes with `k`:

- **Connected Components:** Indicates graph fragmentation. A value of 1 means the graph is fully connected.
- **Degree Statistics:** Shows the distribution of vertex connectivity. Large differences between min and max degree may indicate hub vertices.
- **Density/Sparsity:** Measures how many of the possible edges are present. MkNN graphs are typically very sparse.

For pruned graphs, the statistics reflect the structure after geometric pruning has been applied.

Value

Invisibly returns a data frame containing graph statistics with columns:

idx Index of the `k` value (1 to number of graphs)

k The `k` value used for the graph

n_components Number of connected components

n_edges Number of edges in the graph

mean_degree Average vertex degree

min_degree Minimum vertex degree

max_degree Maximum vertex degree

density Graph density (proportion of possible edges present)

sparsity Graph sparsity (1 - density)

Examples

```
graphs <- create.mknn.graphs(matrix(c(0, 1, 3, 6, 9), ncol = 1),
                                k.values = 1:3, compute.full = TRUE, verbose = FALSE)
summary(graphs)
```

summary.mst_completion_graph

Summary Method for MST Completion Graph Objects

Description

Computes and returns a comprehensive summary of an MST completion graph, including graph statistics, edge weight distributions, and PCA information if applicable.

Usage

```
## S3 method for class 'mst_completion_graph'
summary(object, ...)
```

Arguments

object An object of class `mst_completion_graph`.
... Additional arguments (currently ignored).

Value

An object of class `summary.mst_completion_graph` containing:

n_vertices Number of vertices in the graph
n_mst_edges Number of edges in the minimal spanning tree
n_cmst_edges Number of edges in the completed graph
q_thld Quantile threshold used for completion
edge_weight_summary Five-number summary of MST edge weights
completion_threshold The actual distance threshold used
pca_applied Logical indicating if PCA was applied
pca_info PCA details (if applicable)

See Also

[print.summary.mst_completion_graph](#) for printing summaries, [create.cmst.graph](#) for creating graphs

Examples

```
X <- rbind(c(0, 0), c(1, 0), c(0, 1), c(2, 2))
graph <- create.cmst.graph(X, verbose = FALSE)
print(graph)
summary(graph)
```

summary.rknn_graphs	<i>Summarize an rknn_graphs Object</i>
---------------------	--

Description

Provides a compact table of graph characteristics for an "rknn_graphs" object created by `create.rknn.graphs()`. The table reports final edge counts, component-repair counts, degree summaries, and density/sparsity for each adaptive-radius `k.scale` value.

Usage

```
## S3 method for class 'rknn_graphs'
summary(object, ...)
```

Arguments

<code>object</code>	An object of class "rknn_graphs".
<code>...</code>	Additional arguments passed to or from other methods; currently unused.

Value

Invisibly returns a data frame with one row per graph and columns:

<code>idx</code>	Position of the graph in the returned graph sequence.
<code>k</code>	The adaptive-radius <code>k.scale</code> value.
<code>n_vertices</code>	Number of graph vertices.
<code>n_ccomp</code>	Number of connected components in the final graph.
<code>n_ccomp_before_repair</code>	Number of components before component-MST repair.
<code>edges</code>	Final number of undirected edges.
<code>edges_before_pruning</code>	Number of edges before geometric pruning.
<code>edges_after_pruning</code>	Number of edges after geometric pruning and before optional component repair.
<code>mst_edges_added</code>	Number of component-MST repair edges added.
<code>mean_degree</code>	Average vertex degree in the final graph.
<code>min_degree</code>	Minimum vertex degree.
<code>median_degree</code>	Median vertex degree.
<code>max_degree</code>	Maximum vertex degree.
<code>max_degree_over_median</code>	Ratio of maximum to median degree, or NA when the median degree is zero.
<code>universal_vertices</code>	Number of vertices adjacent to every other vertex.
<code>density</code>	Final graph density.
<code>sparsity</code>	One minus graph density.

See Also

[create.rknn.graphs\(\)](#)

Examples

```
X <- matrix(c(0, 1, 3, 4), ncol = 1)
graphs <- create.rknn.graphs(X, k.values = seq.int(1, 2), radius.search = "all.pairs",
  graph.detail = "minimal",
  prune.method = "none")
summary(graphs)
```

summary.vertex_geodesic_stats

Summary method for vertex_geodesic_stats objects

Description

Summary method for vertex_geodesic_stats objects

Usage

```
## S3 method for class 'vertex_geodesic_stats'
summary(object, ...)
```

Arguments

object	A vertex_geodesic_stats object
...	Additional arguments passed to summary

Value

A summary of the vertex geodesic statistics

Examples

```
x <- data.frame(
  radius = c(0.2, 0.4, 0.6),
  rays = c(3, 5, 6),
  composite_geodesics = c(1, 2, 3),
  overlap_min = c(0.10, 0.15, 0.20),
  overlap_p05 = c(0.15, 0.20, 0.25),
  overlap_p25 = c(0.20, 0.25, 0.30),
  overlap_median = c(0.30, 0.40, 0.50),
  overlap_p75 = c(0.40, 0.50, 0.60),
  overlap_p95 = c(0.55, 0.65, 0.75),
  overlap_max = c(0.60, 0.70, 0.80),
  potential_pairs = c(3, 10, 15),
```

```

    composite_ratio = c(1/3, 0.2, 0.2),
    overlap_ratio = c(0.30, 0.40, 0.50)
  )
  class(x) <- c("vertex_geodesic_stats", "data.frame")
  attr(x, "vertex") <- 7L

  summary(x)

```

synthetic.circle	<i>Specify a circle geometry</i>
------------------	----------------------------------

Description

Specify a circle geometry

Usage

```

synthetic.circle(
  radius = 1,
  angle.range = c(0, 2 * pi),
  ambient.dim = 2L,
  frame = c("canonical", "random.orthonormal", "supplied"),
  frame.algorithm = NULL,
  frame.matrix = NULL,
  offset = NULL
)

```

Arguments

radius	Circle radius.
angle.range	Admissible angular interval.
ambient.dim	Ambient dimension.
frame, frame.algorithm, frame.matrix, offset	Frame parameters.

Value

A synthetic geometry component.

Examples

```
synthetic.circle(radius = 2, angle.range = c(0, pi))
```

synthetic.helix	<i>Specify a helix geometry</i>
-----------------	---------------------------------

Description

Specify a helix geometry

Usage

```
synthetic.helix(
  pitch = 0.2,
  t.range = c(0, 2 * pi),
  ambient.dim = 3L,
  frame = c("canonical", "random.orthonormal", "supplied"),
  frame.algorithm = NULL,
  frame.matrix = NULL,
  offset = NULL
)
```

Arguments

pitch	Helix pitch.
t.range	Admissible parameter interval.
ambient.dim	Ambient dimension.
frame, frame.algorithm, frame.matrix, offset	Frame parameters.

Value

A synthetic geometry component.

Examples

```
synthetic.helix(pitch = 0.25, t.range = c(0, pi))
```

synthetic.point.line.junction	<i>Specify a point-line junction</i>
-------------------------------	--------------------------------------

Description

Specify a point-line junction

Usage

```
synthetic.point.line.junction(
  point.location,
  line.origin,
  line.direction,
  line.range
)
```

Arguments

point.location Point location.
 line.origin, line.direction, line.range
 Segment parameters.

Value

A two-stratum synthetic_stratified_geometry.

Examples

```
synthetic.point.line.junction(c(0, 0), c(0, 0), c(1, 0), c(0, 1))
```

synthetic.quadform	<i>Specify a quadform geometry</i>
--------------------	------------------------------------

Description

Specify a quadform geometry

Usage

```
synthetic.quadform(
  intrinsic.dim,
  ambient.dim,
  forms = list(),
  frame = c("canonical", "random.orthonormal", "supplied"),
  frame.algorithm = NULL,
  frame.matrix = NULL,
  offset = NULL
)
```

Arguments

intrinsic.dim Intrinsic dimension.
 ambient.dim Ambient dimension.
 forms List of finite symmetric quadratic-form matrices.

frame	Frame policy.
frame.algorithm	Versioned random-frame algorithm or NULL.
frame.matrix	Supplied orthonormal frame or NULL.
offset	Ambient offset or NULL.

Value

A synthetic geometry component.

Examples

```
synthetic.quadform(1L, 2L, forms = list(matrix(0.5)))
```

```
synthetic.sampling.clustered
```

Clustered sampling specification

Description

Clustered sampling specification

Usage

```
synthetic.sampling.clustered(
  cluster.count,
  observations.per.cluster,
  center.lower = -1,
  center.upper = 1,
  within.sd,
  algorithm = "centers.then.gaussian.offsets.v1"
)
```

Arguments

cluster.count	Number of clusters.
observations.per.cluster	Rows per cluster.
center.lower, center.upper	Center box bounds.
within.sd	Within-cluster standard deviation.
algorithm	Versioned draw algorithm.

Value

A fixed-size synthetic sampling component.

Examples

```
synthetic.sampling.clustered(3L, 5L, within.sd = 0.1)
```

```
synthetic.sampling.dirichlet.zeros
```

Dirichlet sampling with structural zeros

Description

Dirichlet sampling with structural zeros

Usage

```
synthetic.sampling.dirichlet.zeros(
  concentration,
  zero.fraction,
  zero.parts,
  zero.row.policy = c("first", "random"),
  count.rounding = "round",
  algorithm = "normalized.gamma.v1"
)
```

Arguments

<code>concentration</code>	Scalar or part-wise Dirichlet concentration.
<code>zero.fraction</code>	Fraction of rows receiving structural zeros.
<code>zero.parts</code>	Part indices set to zero.
<code>zero.row.policy</code>	Row-selection policy.
<code>count.rounding</code>	Count rule.
<code>algorithm</code>	Versioned draw algorithm.

Value

A synthetic sampling component.

Examples

```
synthetic.sampling.dirichlet.zeros(
  concentration = rep(1, 3), zero.fraction = 0.2, zero.parts = 1L
)
```

`synthetic.sampling.gapped.uniform`*Gapped-uniform sampling specification*

Description

Gapped-uniform sampling specification

Usage

```
synthetic.sampling.gapped.uniform(  
  intervals,  
  allocation = c("multinomial", "fixed.proportion", "fixed.count"),  
  probabilities = NULL,  
  counts = NULL,  
  rounding = c("largest.remainder", "floor.first.remainder.last"),  
  order = c("draw", "ascending"),  
  algorithm = "sequential.interval.runif.v1"  
)
```

Arguments

<code>intervals</code>	Two-column matrix of disjoint intervals.
<code>allocation</code>	Allocation policy.
<code>probabilities</code>	Optional allocation probabilities.
<code>counts</code>	Optional fixed counts.
<code>rounding</code>	Fixed-proportion rounding rule.
<code>order</code>	Ordering policy.
<code>algorithm</code>	Versioned draw algorithm.

Value

A synthetic sampling component.

Examples

```
intervals <- rbind(c(-1, -0.25), c(0.25, 1))  
synthetic.sampling.gapped.uniform(intervals, probabilities = c(0.5, 0.5))
```

synthetic.sampling.grid.interval

Deterministic interval-grid sampling specification

Description

Deterministic interval-grid sampling specification

Usage

```
synthetic.sampling.grid.interval(
  lower,
  upper,
  endpoints = c("exclude.lower", "exclude.upper", "include.both")
)
```

Arguments

lower, upper	Interval bounds.
endpoints	Endpoint convention. "exclude.lower" reproduces the historical circle grid; "include.both" reproduces the historical uniform trefoil grid.

Value

A deterministic synthetic sampling component.

Examples

```
synthetic.sampling.grid.interval(0, 2 * pi, endpoints = "exclude.lower")
```

synthetic.sampling.quadform.lab

Versioned quadratic-surface sampling used by Geometry Lab

Description

Versioned quadratic-surface sampling used by Geometry Lab

Usage

```
synthetic.sampling.quadform.lab(
  domain = c("square", "disk"),
  extent = 1,
  mode = c("uniform", "area", "grid", "center", "gap"),
  gap = 0.2,
  algorithm = "geometry.lab.v1"
)
```

Arguments

domain	Square or disk parameter domain.
extent	Positive domain radius or half-width, from 0.1 to 5.
mode	Parameter-uniform, surface-area, grid, center, or gap sampling.
gap	Empty strip half-width as a fraction of extent, from 0.01 to 0.8.
algorithm	The fixed version-1 draw and arithmetic policy.

Value

A sampling component for a canonical two-dimensional quadratic surface in three dimensions. Area sampling uses rejection sampling.

Examples

```
sampling <- synthetic.sampling.quadform.lab("disk", mode = "area")
surface <- synthetic.quadform(2, 3, list(diag(c(1, -1))))
sample.synthetic.geometry(surface, sampling, 30, seed = 4101)$n
```

```
synthetic.sampling.truncated.normal
```

Truncated-normal sampling specification

Description

Truncated-normal sampling specification

Usage

```
synthetic.sampling.truncated.normal(
  mean,
  sd,
  lower,
  upper,
  order = c("draw", "ascending"),
  algorithm = "inverse.cdf.v1"
)
```

Arguments

mean, sd	Normal parameters.
lower, upper	Truncation bounds.
order	Ordering policy.
algorithm	Versioned draw algorithm.

Value

A synthetic sampling component.

Examples

```
synthetic.sampling.truncated.normal(0, 1, -2, 2)
```

```
synthetic.sampling.uniform.box
```

Uniform-box sampling specification

Description

Uniform-box sampling specification

Usage

```
synthetic.sampling.uniform.box(  
  lower,  
  upper,  
  order = c("draw", "ascending.first.coordinate"),  
  algorithm = "column.major.runif.v1"  
)
```

Arguments

lower, upper	Scalar or coordinate-wise bounds.
order	Row ordering policy.
algorithm	Versioned draw algorithm.

Value

A synthetic sampling component.

Examples

```
synthetic.sampling.uniform.box(lower = c(-1, 0), upper = c(1, 2))
```

```
synthetic.sampling.uniform.disk
```

Uniform-disk sampling specification

Description

Uniform-disk sampling specification

Usage

```
synthetic.sampling.uniform.disk(radius = 1, algorithm = "radial.sqrt.v1")
```

Arguments

radius	Disk radius.
algorithm	Versioned draw algorithm.

Value

A synthetic sampling component.

Examples

```
synthetic.sampling.uniform.disk(radius = 2)
```

```
synthetic.sampling.uniform.interval
```

Uniform-interval sampling specification

Description

Uniform-interval sampling specification

Usage

```
synthetic.sampling.uniform.interval(
  lower,
  upper,
  order = c("draw", "ascending"),
  algorithm = "runif.v1"
)
```

Arguments

lower, upper	Interval bounds.
order	Ordering policy.
algorithm	Versioned draw algorithm.

Value

A synthetic sampling component.

Examples

```
synthetic.sampling.uniform.interval(0, 1, order = "ascending")
```

```
synthetic.sampling.uniform.rectangle
```

Uniform-rectangle sampling specification

Description

Uniform-rectangle sampling specification

Usage

```
synthetic.sampling.uniform.rectangle(  
  lower,  
  upper,  
  algorithm = "coordinate.sequential.runif.v1"  
)
```

Arguments

lower, upper	Length-two coordinate bounds.
algorithm	Versioned draw algorithm.

Value

A synthetic sampling component.

Examples

```
synthetic.sampling.uniform.rectangle(c(-1, -2), c(1, 2))
```

synthetic.simplex	<i>Specify a simplex geometry</i>
-------------------	-----------------------------------

Description

Specify a simplex geometry

Usage

```
synthetic.simplex(parts)
```

Arguments

parts	Number of compositional parts.
-------	--------------------------------

Value

A synthetic geometry component.

Examples

```
synthetic.simplex(parts = 3L)
```

synthetic.sphere.cap	<i>Specify a sphere-cap geometry</i>
----------------------	--------------------------------------

Description

Specify a sphere-cap geometry

Usage

```
synthetic.sphere.cap(
  radius = 2,
  footprint.radius = 1,
  ambient.dim = 3L,
  frame = c("canonical", "random.orthonormal", "supplied"),
  frame.algorithm = NULL,
  frame.matrix = NULL,
  offset = NULL
)
```

Arguments

radius Sphere radius.
 footprint.radius Radius of the planar cap footprint.
 ambient.dim Ambient dimension.
 frame, frame.algorithm, frame.matrix, offset
 Frame parameters.

Value

A synthetic geometry component.

Examples

```
synthetic.sphere.cap(radius = 2, footprint.radius = 1)
```

```
synthetic.stratified    Assemble a stratified geometry
```

Description

Assemble a stratified geometry

Usage

```
synthetic.stratified(strata, junctions = NULL)
```

Arguments

strata Nonempty list of compatible synthetic_stratum objects.
 junctions Optional data frame describing stratum boundary junctions.

Value

A draw-free synthetic geometry component.

Examples

```
point <- synthetic.stratum.point("point", c(0, 0))
line <- synthetic.stratum.segment("line", c(0, 1), c(0, 0), c(1, 0))
synthetic.stratified(list(point, line))
```

```
synthetic.stratum.point
```

Specify a point stratum

Description

Specify a point stratum

Usage

```
synthetic.stratum.point(id, location)
```

Arguments

id	Stable stratum identifier.
location	Finite ambient location.

Value

A draw-free synthetic_stratum.

Examples

```
synthetic.stratum.point("origin", c(0, 0))
```

```
synthetic.stratum.rectangle
```

Specify a rectangle stratum

Description

Specify a rectangle stratum

Usage

```
synthetic.stratum.rectangle(id, coordinate.ranges, origin, basis)
```

Arguments

id	Stable stratum identifier.
coordinate.ranges	Two-row matrix of finite increasing ranges.
origin	Finite ambient origin.
basis	Orthonormal ambient-by-two basis.

Value

A draw-free synthetic_stratum.

Examples

```
synthetic.stratum.rectangle(
  "square", rbind(c(-1, 1), c(-1, 1)), c(0, 0), diag(2)
)
```

```
synthetic.stratum.segment
  Specify a line-segment stratum
```

Description

Specify a line-segment stratum

Usage

```
synthetic.stratum.segment(id, coordinate.range, origin, direction)
```

Arguments

id	Stable stratum identifier.
coordinate.range	Finite increasing intrinsic range.
origin	Finite ambient origin.
direction	Unit ambient direction.

Value

A draw-free synthetic_stratum.

Examples

```
synthetic.stratum.segment("line", c(-1, 1), c(0, 0), c(1, 0))
```

synthetic.torus.patch *Specify a torus-patch geometry*

Description

Specify a torus-patch geometry

Usage

```
synthetic.torus.patch(  
  major.radius = 1,  
  minor.radius = 0.35,  
  u.range = c(-pi/2, pi/2),  
  v.range = c(-pi/2, pi/2),  
  ambient.dim = 3L,  
  frame = c("canonical", "random.orthonormal", "supplied"),  
  frame.algorithm = NULL,  
  frame.matrix = NULL,  
  offset = NULL  
)
```

Arguments

major.radius, minor.radius
Torus radii.

u.range, v.range
Admissible angular intervals.

ambient.dim
Ambient dimension.

frame, frame.algorithm, frame.matrix, offset
Frame parameters.

Value

A synthetic geometry component.

Examples

```
synthetic.torus.patch(major.radius = 2, minor.radius = 0.5)
```

synthetic.trefoil	<i>Specify a trefoil-knot geometry</i>
-------------------	--

Description

This preserves the legacy gflow parameterization: $x = \text{scale} * \sin(t) + 2 * \sin(2*t)$, $y = \text{scale} * \cos(t) - 2 * \cos(2*t)$, and $z = -\text{scale} * \sin(3*t)$.

Usage

```
synthetic.trefoil(
  scale = 1,
  t.range = c(0, 2 * pi),
  ambient.dim = 3L,
  frame = c("canonical", "random.orthonormal", "supplied"),
  frame.algorithm = NULL,
  frame.matrix = NULL,
  offset = NULL
)
```

Arguments

scale	Scale applied to the first harmonic and third coordinate.
t.range	Admissible parameter interval.
ambient.dim	Ambient dimension.
frame, frame.algorithm, frame.matrix, offset	Frame parameters.

Value

A synthetic geometry component.

Examples

```
synthetic.trefoil(scale = 0.5, t.range = c(0, pi))
```

validate.maximal.packing	<i>Validate a Maximal Packing</i>
--------------------------	-----------------------------------

Description

Validates whether a given vertex packing is maximal and correctly satisfies the distance constraints. A packing is valid if all vertices are separated by at least the specified radius, and is maximal if no additional vertices can be added without violating this constraint.

Usage

```
validate.maximal.packing(
  adj.list,
  length.list,
  packing.vertices,
  max.packing.radius
)
```

Arguments

<code>adj.list</code>	A list where each element is a vector of adjacent vertex indices (1-based) for the corresponding vertex.
<code>length.list</code>	A list where each element is a vector of edge weights corresponding to the adjacencies in <code>adj.list</code> .
<code>packing.vertices</code>	An integer vector of vertex indices (1-based) that form the packing to be validated.
<code>max.packing.radius</code>	A numeric value representing the minimum distance that should separate any two vertices in the packing.

Details

This function performs two key validations:

1. **Packing Property:** Verifies that all vertices in the packing are separated by at least `max.packing.radius`.
2. **Maximality:** Verifies that no additional vertex can be added to the packing without violating the packing property.

The function uses the `igraph` package to compute shortest path distances between vertices using Dijkstra's algorithm.

Value

A list with class "packing_validation" containing validation results:

<code>valid</code>	Logical indicating whether the packing satisfies the distance constraint
<code>min.packing.distance</code>	The minimum distance found between any two packing vertices
<code>max.coverage.distance</code>	The maximum distance from any non-packing vertex to its nearest packing vertex
<code>violations</code>	A data frame containing details of any violations found, or NULL if none. Contains columns: type, vertex1, vertex2, distance
<code>is.maximal</code>	Logical indicating whether the packing is maximal (no vertices can be added)
<code>potential.additions</code>	Integer vector of vertex indices that could potentially be added to the packing if it's not maximal, or NULL if maximal

Examples

```
adj.list <- list(c(2), c(1, 3), c(2, 4), c(3, 5), c(4))
length.list <- list(c(1), c(1, 1), c(1, 1), c(1, 1), c(1))
packing <- c(1, 3, 5)
radius <- 2

result <- validate.maximal.packing(adj.list, length.list, packing, radius)
result$valid
result$is.maximal
```

`validate.synthetic.geometry`*Validate a geometry specification or its latent coordinates*

Description

Validate a geometry specification or its latent coordinates

Usage

```
validate.synthetic.geometry(geometry, latent = NULL)
```

Arguments

<code>geometry</code>	A geometry component constructed by this package.
<code>latent</code>	Optional latent coordinate matrix.

Value

With no latent input, the unchanged geometry invisibly. Otherwise, the validated latent coordinates as a double matrix.

Examples

```
validate.synthetic.geometry(synthetic.circle(), matrix(c(0, pi), ncol = 1))
```

```
validate.synthetic.sampling
```

Validate a point-sampling specification and geometric support

Description

Validate a point-sampling specification and geometric support

Usage

```
validate.synthetic.sampling(sampling, geometry = NULL)
```

Arguments

sampling	A sampling component constructed by this package.
geometry	Optional geometry component for support checks.

Value

The unchanged sampling specification, invisibly.

Examples

```
validate.synthetic.sampling(synthetic.sampling.uniform.disk(0.5),
  synthetic.sphere.cap())
```

```
verify.maximal.packing
```

Verify Maximal Packing Created by create.maximal.packing

Description

A convenience function to verify the correctness of a maximal packing created using the [create.maximal.packing](#) function. This function validates both the packing property (minimum separation distance) and maximality (no vertices can be added).

Usage

```
verify.maximal.packing(packing.result, verbose = TRUE)
```

Arguments

packing.result	The result returned by create.maximal.packing , which must be an object of class "maximal_packing".
verbose	Logical indicating whether to print detailed validation results. Default is TRUE.

Details

This function takes the output of `create.maximal.packing` and verifies two key properties:

1. The packing vertices are all separated by at least `max_packing_radius`
2. The packing is maximal (no more vertices can be added without violating the distance constraint)

When `\code{verbose = TRUE}`, the function prints:

```
\itemize{
  \item Graph diameter
  \item Packing radius used
  \item Number of vertices in the packing
  \item Minimum distance between packing vertices
  \item Maximum coverage distance
  \item Validity and maximality status
  \item Any violations or potential additions (if applicable)
}
```

Value

A logical value: TRUE if the packing is both valid (satisfies the distance constraint) and maximal (no vertices can be added), FALSE otherwise.

See Also

[create.maximal.packing](#), [validate.maximal.packing](#)

Examples

```
adj.list <- list(c(2), c(1, 3), c(2, 4), c(3, 5), c(4))
length.list <- list(c(1), c(1, 1), c(1, 1), c(1, 1), c(1))
result <- create.maximal.packing(adj.list, length.list, grid.size = 2)

verify.maximal.packing(result, verbose = FALSE)
```

vertices

Extract Vertices from a Graph Result

Description

Extract Vertices from a Graph Result

Usage

```
vertices(object, ...)
```

Arguments

object Object from which vertices should be extracted.
 ... Additional arguments passed to methods.

Value

Object-specific vertex indices.

Examples

```
chain <- create.graph("chain", n = 5)
extrema <- detect.local.extrema(graph.adjacency(chain), graph.lengths(chain), y = c(1, 3, 1, 2,
  0), max.radius = 1, min.neighborhood.size = 2)
vertices(extrema, extrema$labels[[1]])
```

```
vertices.local_extrema
```

Extract a Local-Extremum Neighborhood

Description

Extract a Local-Extremum Neighborhood

Usage

```
## S3 method for class 'local_extrema'
vertices(object, label, include.center = TRUE, ...)
```

Arguments

object Object from which vertices should be extracted.
 label Character scalar identifying an extremum in object\$labels.
 include.center Logical; include the extremum vertex itself.
 ... Additional arguments passed to methods.

Value

An integer vector of one-based vertex indices in the selected extremum's stored neighborhood, optionally excluding its center.

Examples

```
chain <- create.graph("chain", n = 5)
extrema <- detect.local.extrema(graph.adjacency(chain), graph.lengths(chain), y = c(1, 3, 1, 2,
  0), max.radius = 1, min.neighborhood.size = 2)
vertices(extrema, extrema$labels[[1]])
```

wgraph.prune.long.edges

Prune Long Edges in a Weighted Graph

Description

Prune Long Edges in a Weighted Graph

Usage

```
wgraph.prune.long.edges(
  adj.list,
  length.list,
  alt.path.len.ratio.thld,
  use.total.length.constraint = TRUE,
  verbose = FALSE
)
```

Arguments

adj.list	A graph adjacency list.
length.list	Edge-length list matching adj.list.
alt.path.len.ratio.thld	Alternative-path threshold.
use.total.length.constraint	If TRUE, compare total alternative path length with the original edge. Otherwise require every edge on the alternative path to be shorter than the original edge times the threshold.
verbose	Logical progress flag.

Value

A dgraph object. Use [graph.adjacency\(\)](#), [graph.lengths\(\)](#), [graph.edges\(\)](#) and [graph.stages\(\)](#) to inspect its stored graph stages. Construction and diagnostic information is stored in metadata.

Examples

```
graph <- list(c(2L, 3L), c(1L, 3L), c(1L, 2L))
lengths <- list(c(1, 2), c(1, 1), c(2, 1))
graph.adjacency(wgraph.prune.long.edges(graph, lengths, alt.path.len.ratio.thld = 1.1))
```

Index

- * **package**
 - dgraphs-package, [5](#)
- as_igraph, [6](#)
- build.ian.backend, [7](#)
- build.ian.backend(), [32](#), [33](#)
- build.iknn.graphs.and.selectk, [8](#)
- compare.adj.lists, [10](#)
- compare.paths, [11](#)
- compute.geodesic.stats, [11](#)
- compute.graph.diameter, [13](#)
- compute.graph.distance, [13](#)
- compute.graph.endpoint.scores, [14](#)
- compute.graph.summary.pmf, [16](#)
- compute.graph.summary.pmf(), [81](#)
- compute.graph.summary.stability, [18](#)
- compute.graph.summary.stability(), [19](#)
- compute.stability.metrics, [19](#)
- compute.vertex.geodesic.stats, [20](#)
- convert.adjacency.list.to.adjacency.matrix,
[21](#)
- convert.adjacency.to.edge.matrix, [22](#)
- convert.to.undirected, [23](#)
- convert.weighted.adjacency.matrix.to.adjacency.list,
[23](#)
- count.edges, [24](#)
- create.cknn.graph, [24](#)
- create.cmst.graph, [26](#), [108](#), [128](#)
- create.fermat.sknn.graph (fermat.knn),
[69](#)
- create.geodesic.iknn.graph, [28](#)
- create.graph, [29](#)
- create.graph(), [6](#)
- create.grid.graph, [30](#)
- create.ian.graph, [31](#)
- create.ian.graph(), [7](#), [8](#)
- create.iknn.graphs, [34](#), [123](#)
- create.iknn.graphs(), [9](#), [19](#)
- create.iterated.iknn.graphs, [36](#)
- create.iterated.iknn.graphs(), [124](#)
- create.maximal.packing, [38](#), [150](#), [151](#)
- create.mknn.graph, [39](#), [43](#)
- create.mknn.graphs, [41](#), [42](#)
- create.path.graph, [44](#)
- create.path.graph(), [6](#), [83](#), [84](#)
- create.plm.graph, [45](#)
- create.plm.graph(), [110](#)
- create.rknn.graph, [45](#)
- create.rknn.graph(), [6](#), [48](#)
- create.rknn.graphs, [48](#)
- create.rknn.graphs(), [129](#), [130](#)
- create.single.iknn.graph, [49](#)
- create.sknn.graph, [52](#)
- create.sknn.graph(), [6](#), [55](#), [56](#), [69](#), [70](#)
- create.sknn.graphs, [55](#)
- create.subgraph, [56](#)
- create.subgraph(), [79](#)
- create.threshold.distance.graph, [57](#)
- detect.graph.endpoints, [57](#)
- detect.local.extrema, [60](#)
- detect.local.extrema(), [57](#), [59](#), [126](#)
- dgraph, [61](#)
- dgraph(), [29](#), [33](#)
- dgraphs (dgraphs-package), [5](#)
- dgraphs-package, [5](#)
- edge.diff, [62](#)
- edge.lengths.synthetic.geometry, [63](#)
- embed.quadform.surface, [63](#)
- embed.synthetic.geometry, [64](#)
- explore.graphs, [65](#)
- explore.graphs(), [113](#), [114](#)
- extract.trajectory.edge.lengths, [66](#)
- fermat.distances, [67](#)
- fermat.distances(), [70](#)
- fermat.knn, [69](#)

- geodesic.core.endpoints, 71
- geodesic.disk, 72
- geodesic.knn, 73
- geodesic.knn(), 74
- geodesic.knnx, 74
- geodesic.knnx(), 73
- get.knn, 116
- get.shortest.path, 75
- get.shortest.path(), 44
- graph.adjacency(dgraph), 61
- graph.adjacency(), 29, 31, 41, 51, 54, 57, 153
- graph.connected.components, 75
- graph.connected.components(), 80
- graph.edge.attribute(dgraph), 61
- graph.edges(dgraph), 61
- graph.edges(), 29, 31, 41, 51, 54, 57, 153
- graph.embedding, 76
- graph.embedding(), 79, 96, 97
- graph.geodesic.distances, 77
- graph.geodesic.distances(), 6, 69, 70, 73
- graph.lengths(dgraph), 61
- graph.lengths(), 29, 31, 41, 51, 54, 57, 153
- graph.order(dgraph), 61
- graph.order(), 29
- graph.spectral.embedding, 78
- graph.spectral.embedding(), 80
- graph.spectrum, 79
- graph.spectrum(), 78, 79
- graph.stages(dgraph), 61
- graph.stages(), 31, 41, 51, 54, 57, 153
- graph.summary.divergence, 81
- graph.summary.divergence(), 18
- graphics::par(), 95
- graphics::plot.default(), 98
- identical.vertex.set.weighted.graph.similarity, 82
- inspect.path.graph, 83
- inspect.path.graph.series, 84
- inspect.synthetic_geometry_sample, 85
- isometry.distance.correlations, 85
- isometry.distortion.quantiles, 86
- isometry.geodesic.diagnostics, 87
- isometry.rel.abs.error, 88
- isometry.rel.rms.error, 89
- isometry.scale, 90
- jensen.shannon.divergence, 90
- jensen.shannon.divergence(), 16, 81
- join.graphs, 91
- minh.limit, 92
- nerve.graph, 92
- overlap.distribution.plot, 93
- path.dist, 93
- path.dist(), 94, 120
- path.length, 94
- path.length(), 94, 120
- plot.build_iknn_graphs_and_selectk, 95
- plot.cst_graph_mixing_stats, 96
- plot.dgraph, 96
- plot.dgraph(), 6
- plot.geodesic_stats, 98
- plot.iknn_stability_metrics, 99
- plot.IkNNgraphs, 100
- plot.vertex_geodesic_stats, 101
- print.adaptive_radius_graph
(print.graph.constructors), 104
- print.build_iknn_graphs_and_selectk, 102
- print.cknn_graph
(print.graph.constructors), 104
- print.dgraph, 103
- print.geodesic_stats, 103
- print.graph.constructors, 104
- print.knn.outliers, 105
- print.maximal_packing, 106
- print.mknn_graph, 106
- print.mknn_graphs, 107
- print.mst_completion_graph, 108
- print.packing_validation, 109
- print.path.graph(inspect.path.graph), 83
- print.path.graph.plm, 109
- print.path.graph.series
(inspect.path.graph.series), 84
- print.radius_graph
(print.graph.constructors), 104
- print.rknn_graphs
(print.graph.constructors), 104
- print.sknn_graph
(print.graph.constructors), 104
- print.sknn_graphs
(print.graph.constructors), 104

print.summary.knn.outliers, 110
 print.summary.local_extrema
 (summary.local_extrema), 126
 print.summary.mst_completion_graph,
 111, 128
 print.summary.synthetic_geometry_sample
 (inspect.synthetic_geometry_sample),
 85
 print.synthetic_geometry_sample
 (inspect.synthetic_geometry_sample),
 85

 quadform.gradient, 112
 quadform.metric, 112
 quantile, 116

 read.graph.benchmark, 113
 read.graph.benchmark(), 66, 114
 register.graph.project, 114
 register.graph.project(), 65, 66, 113
 remove.knn.outliers, 115
 rm.self.loops, 117

 sample.synthetic.geometry, 118
 sample.synthetic.geometry(), 6, 30, 85
 shiny::runApp(), 65, 66
 stats::prcomp(), 28
 subdivide.path, 119
 subdivide.path(), 94
 summarize.isometry.deviation, 120
 summary, 108
 summary.geodesic_stats, 121
 summary.IkNN, 122
 summary.iknn_graphs, 122
 summary.iterated_iknn_graphs, 124
 summary.knn.outliers, 125
 summary.local_extrema, 126
 summary.mknn_graphs, 41, 43, 126
 summary.mst_completion_graph, 108, 111,
 128
 summary.path.graph
 (inspect.path.graph), 83
 summary.path.graph.series
 (inspect.path.graph.series), 84
 summary.rknn_graphs, 129
 summary.synthetic_geometry_sample
 (inspect.synthetic_geometry_sample),
 85
 summary.vertex_geodesic_stats, 130

 synthetic.circle, 131
 synthetic.helix, 132
 synthetic.point.line.junction, 132
 synthetic.quadform, 133
 synthetic.sampling.clustering, 134
 synthetic.sampling.dirichlet.zeros,
 135
 synthetic.sampling.gapped.uniform, 136
 synthetic.sampling.grid.interval, 137
 synthetic.sampling.quadform.lab, 137
 synthetic.sampling.truncated.normal,
 138
 synthetic.sampling.uniform.box, 139
 synthetic.sampling.uniform.disk, 140
 synthetic.sampling.uniform.interval,
 140
 synthetic.sampling.uniform.rectangle,
 141
 synthetic.simplex, 142
 synthetic.sphere.cap, 142
 synthetic.stratified, 143
 synthetic.stratum.point, 144
 synthetic.stratum.rectangle, 144
 synthetic.stratum.segment, 145
 synthetic.torus.patch, 146
 synthetic.trefoil, 147

 validate.maximal.packing, 39, 147, 151
 validate.synthetic.geometry, 149
 validate.synthetic.sampling, 150
 verify.maximal.packing, 39, 150
 vertices, 151
 vertices.local_extrema, 152

 wgraph.prune.long.edges, 153